
F.G.R.

GEOLOGICAL REPORT ON EXPLORATION FOR COAL TUBED BLOCK AURANGA COALFIELD DISTRICT-LATEHAR JHARKHAND

VOLUME-I
TENT & ANNEXURES





MINERAL EXPLORATION CORPORATION LIMITED
(A Government of India Enterprise)

EASTERN ZONE

RANCHI

MARCH - 2006

GEOLOGICAL REPORT ON EXPLORATION FOR COAL TUBED BLOCK, AURANGA COALFIELD DISTRICT - LATEHAR, JHARKHAND (UNDER PRIORITY CATPIVE MINING BLOCKS)

SALIENT FEATURES

1. Name of the Block : 2. Area of the Block :

Tubed

4.6 Sq.km.

3. Location of the Block:

- i) Located in the northern part of Auranga Coalfield, Dist. Latehar, Jnarkhand.
- ii) Included in Survey of India Toposheet No. 73A/9 (R.F. 50,000).

III) Co-ordinates:

Latitudes (N): 23° 48′20″ to 23° 50′09″

Longitudes (E): 84°34′09" to 84° 35′45"

4. Objective

- i) To prove the lay and disposition of coal seams
- ii) To determine the quality and grade-wise reserves of the coal seams.
- iii) To assess the opencast / underground Poten-tiality of the coal seams.
- 5. Duration of Field Operation : 14,06,2004 to 07.01,2005

Quantum of work: Ó.

TABLE: I QUANTUM OF WORK DONE IN TUBED BLOCK

SI.No	NATURE OF	WORK DONE	QUANTUM			
	Agency - MECL	100 May 100 Ma	I.			
1	Survey and Mapping:					
	i) Triangulation		4.6 Sg. Km.			
	ii) Topographica	Survey :	4.6 Sq. Km.			
	iii) Co-ordinate	: a)	20 Bhs.(MAT-1 to MAT-20)			
		b)	28 Stations			
	iv) Reduced leve	ls a)	20 Bhs			
		b)	28 stations			
	v) Geological Ma	pping	4.6 Sq. Km.			
2	Exploratory Drilling:					
	Agency	Quantum(m)	Borehole (Nos)			
	MECL (Non-CIL)	3011.15	20 (MAT series)			
	GSI	315.00 (Approx)	2 (AR series)			
	Sub Total :	3326.15	22 Bhs.			
	the case of the ca					
)	Coal Sampling (m)	: 783.11 m, 20 Bh	s (MAT-1 to 20)			
1	Core Logging (m): 3011.15 m, 20 Bhs (MAT-1 to 20)					
	Chemical analysis	*				
	a) Band-by-Band	· CFRI, Ranchi :	783.11 m, 20 Bhs.			
	b) Overall	: CFRI, Ranchi :	12 Bhs.			
	c) Special test					
	i) Ultimate Analysis : CFRI, Ranchi : 2 Bhs. (1 Bh. is pending)					
	ii) HGI		2 Bhs (1 Bh. is pending)			
	iii) AFT		2 Bhs (1 Bh. is pending)			
	iv) Ash Analysis					
	v) CV	: CCRI, Ranchi :	2 Bhs (1 Bh. is pending)			
	vi) Petrographic results : CMPDIL, Ranchi: 2 Bins*					
	vii) Mineraiogical S	Study : 2 Bhs.*				

7.

Accessibility: Tubed block is well connected to district headquarter Latehar by a fair weather road at a distance of about 12 km. Ranchi-Daltonganj State Highway passes through the district headquarter Latehar. The nearest rail head Latehar on Barkakana-Daltonganj broad gauge loop of Eastern Railway is about 15 km. from the block. Ranchi, the important city is located at a distance of about 100 km. from Latehar. Ranchi is well connected by road, rail and air ways.

- 8. Mining Activity: The block is virgin.
- O. Geology of Tubed Block: Tubed Block is located in the northern part of Auranga Coalfield. It is represented by formations of Lower Gondwana Group.

Geological sequence of the block is given below in Table-II

TABLE – II GEOLOGICAL SEQUENCE OF TUBED BLOCK

Period	Group	Sub-Group	Formation (Thickness)	Lithology		
Recent & Sub-Recent	×		Alluvium (2.50 to 12.00m)	Soil & Sub-soil		
Citto Trecom		Unconfi	ormity			
Lower Permian	Lower Gondwana Group	Daniuda Sub-Group	Barakar (15.90 to 268.00m)	Sandstones, shale, carbonaceous shale and coal scams		
Permo- Carboniferous			Auranga	Absent		
CarocinterousUnconformity						
Precaminan			Archaeans Metemorphics (0.95 to 12.00m)			

- of 13 correlatable coal seams in the Barakar Formation. These coal seams in descending order are Seam VII (Top), VII (Botton), VI, V (Top), V (Bottom), IV (Top), IV (Bottom), III (Top), III (Middle), III (Bottom), II, I (Top) & I (Bottom). Among these seam VII (Top) & VII (Bottom) are found as coalesed seam in a small patch. Seam I (Bottom) is unworkable over major part of the block. Seam I (Top) is unworkable in 3 small scattered patches while seam VI is unworkable in the entire block. Remaining seams are workable in this block. The sequence of coal seams is given in Table-III.
- Geological Structure: Structurally the block is simple. The general strike of the beds is north-south in the major part of the block which swings to NE-SW in the extreme southern part of the block. The beds dip easterly with amount varying from 3° to 10°. However, in south central part of the block dip increases to 15°.
- Fault: The block is traversed by 4 nos, of faults varying in thrown from 0m to 110m. In addition a two major faults, one of them is located in the northern part of the block and further towards east marks the eastern boundary of the block. The other one fault marks the western boundary of the block in the southwestern part.
- Ouality: The coals of Tubed Block are high moisture, non-coking type, grading between C to G. in general the grade varies from F to G. Coke type and swelling index of coal seams are A & O. Seam-wise quality variations are given in Table-TV. Special tests of coal seam are included in Table TVA & TVB.

from 'D' to 'G' has been established in Tubed block, out of which 151.87 million tonnes account for "Proved" opencest, 19.90 million tonnes "Indicated" open cast and 18.06 million tonnes for underground. In underground area reserves 15.10 m tonnes occur in 'Proved' category & 2.96m. tonnes in 'Indicated' category. The break up of reserves is given below:

	MANAGERIA ANTONIS SALVENIS SA	Reserves in million tonnes	
Details of reserves	Proved	Indicated	Total
Opencast	151.87	19.90	171.77
Underground	15.10	2.96	18.06
Total	166.97	22.86	189.83

The summary of seam-wise reserves under "Proved", "Indicated", opencast and underground categories is given in Table VA, the sector-wise, seam-wise, depth-wise, grade-wise opencast and underground reserves is given in Table-VB. While the seam-wise, barrier-wise, ratio-wise summarised reserves are tabulated in Table-VC and VD respectively.

- 11. **Overburden and Stripping Ratio :** The volumes of overburden and stripping ratio estimated are given in Tables VI.
- Conclusion: The present expioration has established the presence of a total of 13 correlatable coal seams in the Barakar Formation. These coal seams in descending order are Seam VII (Top), VII (Bottom), VI, V (Top), V (Bottom), IV (Top), IV (Bottom), III (Top), III (Middle), III (Bottom), II, I (Top) & I (Bottom). Among these seam VII (Top) & VII (Bottom) are found as coalesced seam in a small patch. Seam I (Bottom) is unworkable over major part of the block. Seam I (Top) is unworkable in 3 small scattered patches while seam VI is unworkable in the entire block. Seam II to Seam VII (Top) are favourably disposed for opencast mining. Seam I (Top) can be developed by underground method.
- 13. Recommendation: A total of 22 boreholes have been drilled in Tubed block occupying 4.6 Sq.km. of area. It is recommended to drill some boreholes to bring the Indicated category reserves into 'Proved' category. It is also recommended to drill a few boreholes to precisely locate the incrops of seams and trace of fault FS & F6 before taking of mining decision to exploit these seams.