SEEPAT ROAD

P.O.: SECL BILASPUR



साउथईस्टर्नकोलफिल्डस्लिमिटे

South Eastern Coalfields Limited

(कोलइण्डियाकाएकअंश/A subsidiary of Coal India Ltd.)
CIN U10102CT1985GOI003161

Website: www.secl-cil.in

कार्यालयः महाप्रबंधक, गेवरा क्षेत्र

OFFICE OF THE GENERAL MANAGER

जिला: कोरबा(छत्तीसगढ़) GEVRA AREA

पिन:495452



STD :07815 275430(O)

: 7815 275032(R)

Fax :07815 275434

email:gevraenvt@gmail.com

पो0आ0:गेवराप्रोजेक्ट

P.O.: GEVRA PROJECT

Distt.: Korba (C.G.)

Pin: 495452

क्रमांक/एस.ई.सी.एल/मप्र/गे.क्षे./ पर्यावरण/2023 / 374

दिनांक 3/ 11 /2023

TO The DFO Katghora Range Katghora Korba CG

SUB: Half Yearly Compliance of Diverted Forest land 100.898 Ha. of Gevra Opencast Mine, SECL, September 2023

REF: Forest clearance: F.NO.8-33/2005-FC DT: 05.05.2008.

Dear Sir

Please find enclosed herewith the Half Yearly Compliance of the Diverted Forest land 100.898 Ha. of Gevra Opencast Mine, SECL, September 2023.

Thanking you.

Yours Sincerely

General Manage

SECL Gevra Area

Copy to:

1. Additional Principal Chief Conservator of Forest(Land Management), Raipur

2. Chief Conservator of Forest, Bilaspur

Yearly Compliance of 100.898 Ha. Diverted Forest Land For Gevra OC Mining Project of M/S South Eastern Coalfields Limited (SECL) in Korba District of Chhattisgarh.

MoEF&CC Clearance No:8-33/2005-FC Dtd:05.05.2008

	MoEF&CC Clearan	ice No:8-33/2005-FC Dtd:05.05.2008
S.No	Condition	Status of Compliance
01	Legal status of forest land remain unchanged	Agreed and complied
02 a	Compensatory afforestation shall be raised and maintained by the State Forest department at the project cost.	Payments made to CAMPA fund under CA is as follows: • An amount of Rs.9897892/-paid vide D.D. No.087920 dt.26.07.07. • An amount Rs.20,78,499/- paid vide D.D. No.751489, 751490,751491 Dtd: 20.11.07. • Differential Amount of Rs:1311876 /-paid vide DD No:693528 Dtd:27.12.2012. Total amount paid under CA head is Rs.13288267.00/-
b	Fencing protection and regeneration of the safety zone area (100 metres strip all along the outer boundary of the mining lease area as recommended by the State Government) shall be done at the project cost. Beside this ,afforestation on degraded forest land, to be selected elsewhere, measuring one and a half times the area under safety zone ,shall also be done at the project cost	Payment made under Regeneration cost of safety zone is as follows: • An amount of Rs.45,616.00 vide DD No.466781 dt.13.07.07.An additional amount of Rs.9579/- paid vide DD No.751488 Dtd: 20.11.2007. Payment made under CA against Safety Zone is as follows: • An amount of Rs.68,425/- paid vide DD No.466782Dtd:13.07.07.An additional amount of Rs.14,369/-paid vide DD No:751492 Dtd:20.11.07. • For safety Zone Fencing an amount Rs.2,51,000/- paid vide DD No.468815 dt.31.08.07. Safety Zone Fencing & afforestation work has been taken up by CGRVVN vide S.No/SECL/BSP/FOREST no. 151 DT: 01.10.16 as per the guidelines issued by MoEF&CC at Project Cost. Work of safety zone along 14 KM has been completed with plantation of 28000 saplings and inspection report enclosed as Annex 1
c	Wherever possible and technically feasible, the User Agency shall undertake afforestation measures in the blanks within the lease area, as well as along the roads outside the lease area diverted under this approval, in consultation with the State Forest Department at the project cost.	carried out in consultation with CGRVVN. Plantation is done in both on plain and Dump areas. Till date 44.53 lakhs saplings planted since 1986 in Gevra OC including downwind direction. Details enclosed as Annex 2

3	Following activities shall be undertake	en by the	User A	gency	at the p	roject cost.	
(i)	Proper mitigative measures to minimize soil erosion and choking of streams shall be prepared and implemented	be	een pr	epare	d and in	ration plan has aplementation of (Annex 3)	
(ii)	Planting of adequate drought hardy plant species and sowing of seed to arrest soil erosion	rith CGRVVN for sion work. The sion is 2500 in area and 3500 area. The species on are medicinal, ralue tress, fruit o, Bel, Bamboo, hok, Golmohar, k, Jamun, Bogan vallia, arood, Kathal, cc.					
(iii)	Construction of check dam retention/toe wall to arrest sliding down of the excavated material along the contour.	Dump a trench, bolders. Year 2022 2021 2018	Conto Trenc (per trench 11845 7200 300 toe wa	ave be dam ur h	Check Dams (per CUM) 11845 7500 20 taining w	Bunds with stone Bunds with stone boulders (per CUM) 11845 7500 20 vall & gabion wall to arrest sliding	
				Location		Dimension 182m X 5m ht. 1.2mX0.9m RCC Drain	
				Alon belt Near Juna Sidir Exte	r idih ng	240mX 5m ht. 300mX 2m 2050m X 2m ht. 1.2m X 0.9m drain 650m X 1m ht. Top width 200mm	

		Gabion wall	From weigh bridge W5 to LK seam coal face side Along toe of dump no. 4 near E2/ E1 TRS	5.72		
(iv)	The area shall be reclaim keeping in view the international practice of stabilizing the dumps by grading /benching so that angles of repose (normally) less than 28 at any given place are maintained.	are technologic To Nos reclaim	hnically reclar ag and it al reclamation of External ed both ally.	d Internal dumps imed with proper is stabilized by a. Dump has been technically and enclosed as Annex		
(v)	The top soil management plan should be strictly adhered to	Top Soil Management Plan incorporated in Soil Conservation plan is followed. Top soil generated is utilized for the biological reclamation/plantation purpose.				
4	The forest land shall not be used for any propose other than that specified in the proposal.	Agreed and co				
5	The approval under the Forest (Conservation) Act.1980 is subject to the environmental clearance under the Environmental Protection Act.1986	Agreed		2*		
6	The user agency will make arrangement for free supply of coal to laborers and staff working on the project site so as to avoid any pressure on the adjacent forest areas	Project to fac connection to avoid damage	cilitate the su the people wo ge / felling			
7	The period of permission for lease under forest (Conservation) Act.1980 will be for 20 years subject to possession of valid lease by User Agency under the MMDR Act.1957.	Agreed				
8	Demarcation of mine lease area will be done on the ground at project cost using four feet high reinforced cement concrete pillars with serial number, forward & back bearing and	Complied Demarcation l	nas been done			

	distance from pillar to pillar.	
9	Mining/reclamation schedule shall be implemented by the user agency at their cost as per Environmental Management plan/phased programme.	Agreed
10	The user agency shall take up afforestation and soil moisture conservation works inside the forest area in 100 M. radius from the permitted lease area in consultation with the forest department wherever the forest density is less than 0.4,gap plantation should be taken up.	Agreed.
11	The user agency shall take up study on soil erosion / soil flow from the overburden areas with the help of GIS in consultation with the forest department	Comprehensive Catchment area treatment plan within 5 KM from Mine Lease Boundary is prepared through Chhattisgarh Council of Science & Technology, Govt. of CG, Raipur Final report has been submitted by CCOST on 17.03.2020. For the implementation of proposed structure in the report an amount of Rs. 8447900/- was estimated. Following which DFO Katghora raised a Demand note of Rs 8447900/ Payment of the said amount has been made on 08.11.2021 in CAMPA.
12	The user agency shall take up the de-silting of the village tanks within five Km. area from the mine lease boundary as a Corporate's social responsibility so as to mitigate the impact of siltation of such tanks if any.	Desiltation scheme was prepared by identifying the water bodies located within the 5 Km of ML area and the same has been verified by DFO Katghora. A total of 41 ponds were identified, which will be carried out in phased manner. • In the 1st phase 9 ponds were considered. Work order was issued on 14.08.2020 for an amount of Rs. 53.82 lakh, which includes 9 ponds from villages : Marwadhora, Ralia, Navapara, Vijaynagar, Binjhra. The work of desiltation of 1st phase 9 ponds has been completed May 2021. • In the 2nd phase (Rs. 10135886/-), 8 nos ponds have been identified in Villages Barbhatta (1), Murianar (1), Chhindpur (2), Dipka (2), Dhurena (1), Kuchena (1) LoA issued on 31st March 2022. Work completed. • In the third Phase (Rs. 13178677), 8

		ponds have been de-silted, Bhilai Bazar (2), Khodri (2), Hardi bazaar (2), Suhabori (1) & Malgaon (1) Work order issued on dt:25.06.2023 (Annex 5)
13	In case of the underground mining the user agency shall take up plantation over the surface area wherever the forest density is less than 0.4 Gap planting should be taken up in the areas where density is between 0.4 and 0.7. The user agency will protect the area till the life of the underground mining in consultation with Forest department	Not applicable
14	Any other condition that the State Govt. or the Chief Conservator of Forest(Central)Regional office, Bhopal may impose from time to in the interest of conservation protection or development of Forests.	• Agreed

Crapauli, 03/11/2023

नोडल ऑफीसर (पर्यावरण/वन) Modal Officer (ENV/Forest) SECL/Gavra Area एस.ई.सी.एल./गेदरा क्षेत्र

संयुक्त निरीक्षण प्रतिवेदन

वन विकास निगम द्वारा वर्षवार पौधों का संयुक्त निरीक्षण/गणना समिति द्वारा दिनांक 23.09.2023 को किया गया। जिसका विवरण निम्नानुसार है :-

क.	रोपण वर्ष	रोपण क्षेत्र की नोम	पौधों की संख्या	जीवित पौधों की संख्या	जीवित पौधों का प्रतिशत	रिमार्क
1	2019-20	Near Ganga Nagar	45500	42056	92.43	
		Plain area in between Ext. Dump no. 6 & 7 and laxman	7250	6690	92.28	
	*	Hardi Bazaar Road	10000	9222	92.22	
2	2020-21	Laxman Project Dump (Mangaon) (Slope & Dump Top)	55950	51726	92.45	
3	2021-22	Dump No. 7 Slope	52500	49424	94.14	
		Non Dump (Shramik Chowk)	5000	4726	94.52	
		Non Dump Add. (Awadh Nagar)	31998	30331	94.79	
		Vertical Greenery System	1500	1421	94.73	
4	2022-23	Dump No. 6 & 7 Back Side (Slope)	82770	79252	95.75	
		Non Dump (Magazine Side)	38200	36366	95.20	
		Bhathora Basahat Patch	5125	4914	95.88	
		Railway colony Front	5125	4815	93.95	
5	2023-24	Near Shakti Nagar Pond ND	19415	19330	99.56	
12		Gevra Non-Dump	19255	19024	98.80	
		Front of Railway Colony ND	3825	3796	99.24	
		Kabristan Back Side Awadhnagar Non-Dump	56705	56195	99.10	
		Magazine Back Side ND	26792	26551	99.10	
		Sal Nursery 10.00. hact.	100000	100000	100.00	

निरीक्षण के दौरान जीवित पौधा का प्रतिशत संतोषजनक पाया गया।

ment Officer SECL Gevra Project

Dy. General Manager (Civil) SECL Gevra Project

Dy. Manager (Survey)

SECL Gevra Project

Gevra Range

Gevra Range

Nodal Officer (Envt.)

SECL Gevra Area

SECL Gevra Project

					F PLANTATI	ON OF GE	VICATIO	DECI	Γ
YEAR	On Plain area (nos)	On intern al dumps (nos)	On External dumps (nos)	Total Plantation on dumps (nos).	Total Plantation done (in nos)	CPT (1.5mx0 .9mx0.7 5m) (in Rmtrs)	GRAS S BED (Nos.)	Area/ Ha.	Location
1	2	3	4	5=(3+4)	6=(2+3+4)	7	8	9	
1986	236000	0	0	0	236000	0	0	74.3	MGR Loc Roadsic Roadsic Inside color Gevr. Kusmunda Ros Distrbuted employees
1987	245750	0	46000	46000	291750	0	0	82.93	1. Ext. OB Dum No. 1 near MG 2. Aroun Magazine 3. Colony Ros 4. Inside colony
1988	419500	0	0	0	419500	0	0	93.22	1. Near E&B. workshop & D GM Offic 2. Near CH 3. Road side a Gevra 4. Road side a VTC/CETI 5. Gevra Kusmunda Roa 6. Bareli villag 7. Near Magazin 8. Colony
1989	454000	0	0	0	454000	0	0	100.8	1. Gevra Kusmunda Ros 2. Near Bare Village 3. Near CE 4. Gevra Color 5. Near CH Bunker 6. SILO Ros 7. Vacant spain color 8. Near Magazir
1990	372883	0	0	0	372883		0	82.86	1. Nes Magazine, Ganganagar 2. Laripara ple 3. Old Dipk Barrier (Plante by Dipka project of the second of the seco
1991	360000	0	0	0	360000	0	0	80	Bareli Bhat Village Bareli Bhat Village Bareli Bhat Village Helipade sid

									4. D Type quarters 5. Nehru nagar (Planted by Dipka project at Dipka unit) 6. CEWS 7. Guest Houses 8. CETI 9. Dipka - Pali Road (Planted by Dipka project) 10. Kusmunda - Gevra Road
1992	64900	0	0	0	64900	0	0	14.42	1. Gevra Township 2. Railway Sising 3. Gevra Mine 4. Near Bareli Pondi Bhata Village
1993	87230	0	26970	26970	114200	0	0	27	1. Shakti Nagar Colony 2. Dipka project colony (Planted by Dipka project at Diopka unit 3. Dipka Ext. Dump no. 1 (Planted by Dipka project at Dipka unit) 4. NCH Colony 5. CEWS 6. Dipka MTK office (Planted by Dipka project at Dipka unit) 7. Gevra Ext. Dump no. 2 8. Gevra Railway siding 9. Kusmund Barrier Pond etc.
1994	, 0	0	0	0	0	0	0	0	
1995	77000	0	0	0	77000	0	0	17.11	Gevra Kusmunda Road Infront of Old GCM Office
1996	68000	0	64000	64000	132000	0	0	29.33	1. Dipka Dump no. 3 (Planted by Dipka project at Dipka unit) 2. Beltikri Dump (Planted by Dipka project at Dipka unit) 3. CGM Office 4. Boundry wall at Dipka (Planted by Dipka project at Dipka unit) 5. Dipka Border line (Planted by Dipka project at Dipka unit) 6. Magazine side
1997	50000	17500	105500	123000	173000	0	0	38.44	1. Dump no. 3 (Planted by Dipka project at Dipka unit) 2. Near Magazine 3. External Dump no. 2,3 & 4 4. External Dump no. 5 5. Internal no. 1
1998	42000	52150	31850	84000	126000	0	15000	31.5	1. Internal Dump no.3 (Amrakanan) 2. Internal Dump no.1 3. External Dump no. 2,3 & 4 4. Khusrudih Road & Dump

									slope 5. Near water tank at Gevra project 6. Magazine side
1999	11950	0	65000	65000	76950	3150	18000	19.23	1. External Dump no.2,3 & 4 2. Near Helipad Gevra 3. External Dump no.3 (Planted by Dipka project at Dipka unit) 4. Near Selting pond (Commercial)
2000	0	0	130000	130000	130000	0	15000	32.5	1.External Dump no. 2,3 & 4 2. External Dump no. 5 3. External Dump 3 (Planted by Dipka project at Dipka unit)
2001	0	0	66000	66000	66000	0	13000	16.5	1. External OB Dump No. 2,3&4 (Top) 2. External OB Dump No. 2,3&4 (Slope)
2002	10000	0	30000	30000	40000	500	4000	16	1. External Dump No 6 2. Back Filling 3. Dump No 6
2003	30000	81000	20000	101000	131000	1270	15000	35	(Slop) 1. Old Dipka Dump No. 3 2. Pragati Nagar 3. Gandhi Nagar 4. Dump No. 1&2
2004	22000	5500	78500	84000	106000	3583	36000	32	1. North side of Dump No. 2,3&4 Near Toe 2. In side Shakti nagar colony 3. Inside Centeral work shop 4. Shakti nagar Gate to DETP (road side green belt strengthening) 5. Dipka barrier to Gevra Water filter (road side green belt strengthening) 6. Kusmunda road side green belt 7. Dump No. 5 8. south side Slope of Dump No. 2,3&4 9. North side Slope of Dump No. 2,3&4 10. Old Internal Dump (East Section) Toe Ince Green belt 11. Dump No. 1 Slope Internal East Section)
2005	76000	0	39500	39500	115500	4800.33	39500	38	1.Dump No.3 Dipka Unit 2. Dump No 2,3&4 North Slope) west side of Helipad 3. Along Kusmunda Road (North side of 2,3,&4 No Dump (2KM X 50 m) 4. Center Park

2005	41500	0	0	0	41500	2000	0		(with in MGR) 5. Along Main Road both sides (From CETI to Dipka Barrier in patches) 6. Dump No 2,3& 4 western side Dump 7. Back side of Shakti Nagar Colony
		40000	5000	45000	120000	4500	45000	48	
2006	75000 50000	0	3000	0	50000	0	0	20	1. Hydro Seeding of grasses On B/F Dump No 3
2008	5000	0	20000	20000	25000	0	0	15	& 6 1. Near Magazine 2. Near DETP 3. Kusmunda road (in between MGR& railway Line 4. Dipka Barrier to Hardi Bazar road side (Near 3 no. Dump of Dipka Unit)
2009	32500	0	30000	30000	62,500	0	20000	21	1. Near Magazine 2. Kusmunda road (in between MGR& Railway Line) 3. Dipka barrier to Hardi Bazar road side (Near 3 No. Dupm of Dipka Unit) 4. Dump NO. 3 (External)Dipka Unit 5. South side Slope of Ext.Dump No 3 (Dipka Unit)
2010	2500	36500		36500	39,000	0	0	25	1. Dump No. 3 (Internal) 2. South East side Slope of Internal Dump No 3 3. Around DETP,CHP,Feed er Breaker, TA office (Urja
2011	0	27500	0	27500	27,500	0	12500	16	Nagar), CTI 1.Dump No. 3 (Internal) 2. South - Bast side Slope of internal Dump No. 3 3. On Plain Area Near Dipka Railway Track
2012	10000	20000	0	20000	30000	0	3125	12	Dump No. 6&7 (Internal) On Plain area Behind Urja Nagar C-Type
2013	5000	0	35000	35000	40000	0	5000	14	Quarter 1. On External Dump No.6&7 (Top& Slope) 2.On Plain area GOLF Ground (Near Silo)
2014	0	0	20000	20000	20000	0	0	10	1. External OB Dump No 6&7 2. Side Slope of External OB Dump No 6&7
2015	0	0	80000	80000	80000	0	10000	26	1. On External Dump No.6&7 (

					- 4				Top& Slope)
2016	0	0	50000	50000	50000	0	0	20	1. On Externa Dump No.6&7 Top& Slope)
2017	0	0	100000	100000	100000	0	5000	30	1. On Externa Dump No 6&7 (Top & Slope)
2018	6500	0	60000	60000	66500	0	0	0	1. On Externa Dump 6&7 (Top. 2. on Road side (New Coatransport Road)
2019	62750	0	0	0	62750	0	0	21.1	1. Near Ganga Nagar 2. Plain Area in Between External Dump No 6&7 and Laxman Both Side
2021	31998	52500	0	52500	84498	0	18750	27.79	Avad Nagar (Magazine Plot). Avad Nagar (Road Side)
2022	48450	0	0	0	48450	0	29613	19.38	Bhatora Basahat Magzine side
2023	19415	0	0	0	19415	0	0	7.766	Near Shakti Nagar Pond
Total	301782 6	33265 0	1103320	1435970	4453796	19803.3	30448 8		
Plante d area (Ha)	689.465	137.6	367.2	504.8	1194.265	10			

		GAP	PLANTATION DETAILS				
Year of Gap Area No. of saplings plantation in Ha. Planted		No. of saplings	Location				
2020-21	17	55950	Mangaon Dump, (Laxman Project)				
2021-22	2	5000	Shramil Chouk to Dipka Chouk				
2022-23	23.69	82915	External Dump 6&7 (slope)				
2023-24	43.405	106577	Awad Nagar Behind Kabaristhan, Between NTPC & private rail track, Behind Magazine & Infront of Railway Colony Shakti Nagar				

नोडल ऑफीसर (पर्यावरण/वन) Nodal Officer (ENV/Forest) SECL/Gevra Area एस.ई.सी.एल./गेवरा क्षेत्र



SOIL CONSERVATION PLAN

GEVRA OPEN CAST MINE SOUTH EASTERN COALFIELDS LIMITED


03/11/2023

नोडल ऑफीसर (पर्यावरण/वन) Modal Officer (ENV/Forest) SECL/Gevra Area एस.ई.सी.एल./गेवरा क्षेत्र

INTRODUCTION

Location & Accessibility

The Gevra OCM is an existing mega opencast project of South Eastern Coalfields Limited (SECL) with present EC capacity of 52.50 MTPA. The Block is located in the South Central Part of Korba Coalfield in Korba District of Chhattisgarh. The Gevra Mining block having an area of 20.37Sq.Km is bounded by latitudes 22°18'00" to 22°21'42" N and longitudes 82°32'00" to 82°39'30" E. It is included in the survey of India Toposheet No. 64 J/ 11. The location map of the area is as shown.



The block is well connected by rail and road. Gevra Road and Korba Railway Station on Champa-Gevra Road branch line of S.E. Railway are at a distance of 10 km and 16 km respectively. Railway siding has been extended up to and beyond Gevra OCP and coal is being transported from the pit head CHP through rail/MGR to the various consumers. SECL HQ Bilaspur is at a distance of about 90 km by road.

The existing capacity of the project is 52.50 MTY. Mining of Coal from Gevra OCP is done by Open Cast method. It is characterized by the presence of four open- castable seams (Composite seam D, E&F Seam, UK Seam, LK Seam) with dip angles of 20-60. Seam thickness ranges from 1.10 m to 45.23m. The thickest seam is Lower Kusmunda (19.28m to 45.23 m). The Maximum width along strike is 9.1 KM and Maximum length along dip is 3.29KM. The present maximum depth of the quarry is 203 m. The mineable reserve is 265.73 MT (as on 01.04.2023) with an average stripping ratio of 1.30. The total quarry has been divided into three sections i.e Western Section, Central Section & Eastern Section. It is proposed to mine all the three identified sections simultaneously. However mining operations will be staggered between the sections.

The total Mine Lease area of the project is 4184.486 Ha. The total Forest Land involved is 1016.412 Ha out of which 904.027 Ha. has already been diverted for nonforest purpose after receiving the Stage II Forest Clearance. The remaining 112.385 Ha. of Revenues Forest land has obtained Final/Stage II approval vide MoEF&CC Clearance L.No. 841/2017-FC dated 21.06.2022 (Handing over awaited from State Forest Department). The project is proposed for capacity enhancement to 70 MTPA with Mine lease area of 4781.798 Ha. Therefore diversion of Additional 94.293 ha. of Revenue Forest Land is involved in this proposed expansion.

Physiography & Drainage

The general topography of the block is gently undulating. The surface contour ranges from 288-328 m above MSL. The general slope of the terrain is towards East. Water from the mine and nearby area flows into the seasonal nalla namely Laxman Nala located on the northern side. Ahiran River located towards NE. In addition there are quite a few ponds. Ahiran and Hasdeo River control the drainage of the area and are situated towards N-E and East respectively of the area under consideration.

The climate of the area is dry to moist tropical with well-defined summer from April to June, rainy season from July to September and winter from November to February. The temperature rises to a maximum of 48°Cin May and drops to a minimum of 7°C in December. The annual rainfall for 2022 is 1433 mm.

MINE WATER ENVIRONMENT

Surface Water Resources


Hasdeo River, a major tributary of Mahanadi River flowing along the eastern side in North—South Direction is the master drainage of the area. The mine block is drained by Laxman nallah flowing in West- East direction and joins Ahiran Nadi, a tributary of Hasdeo river at about 4.5 KM in NE from the mine. Kholar stream which is also a tributary of Hasdeo River controls the drainage in the northern part whereas Lilager Nadi and Gangadel nallah controls the SW and SE respectively. These streams are mostly perennial and behave as constant recharge sources. The pattern of the drainage in the area is mostly dendritic in nature.

Ground Water Resources

The formations within the study area are Barakars, Talchirs and Metamorphics. Major portion of the study area is occupied by Gondwanas. Talchirs and metamorphics occupy the rest. The Project area is situated in Barakars formation comprising sandstone of different grain sizes with shale beds and coal seams. This permeable sandstone is saturated and behaves as aquifers. Shale and coal seams act as aquicludes. Stratification and the presence of aquicludes lead the aquifer system into multi aquifer system.

The formation comprising mainly of alluvium and sandstone (average thickness 50.0 m), lying above the working seam E&F behave as unconfined aquifer. Whereas, lower formations consisting of compact sandstone mainly with secondary porosity behave as semi-confined/confined aquifer.

In the unconfined aquifer ground water moves laterally through the intergranular pore spaces in the sandstone. Whereas, in lower aquifers the groundwater movement is restricted mainly through joints and fractures (i.e. secondary porosity). With intercalation of shales and carbonaceous shale beds and reduction in permeability with depths in the lower aquifers are very poor in potential. A flat water table with a gradient of 1.8×10^{-2} , slopping towards east, was observed in the area.



Plan showing hydrological features of the area

A. PREPARATION AND IMPLEMENTATION OF A PLAN CONTAINING APPROPRIATE MITIGATIVE MEASURES TO MINIMIZE SOIL EROSION AND CHOKING OF STREAMS

Soil conservation in its widest sense includes not only control over erosion but all those measures like correction of soil defects, application of manures and fertilizers, proper crop rotations, irrigation, drainage etc. which aim at maintaining the productivity of the soil at a high level. In this sense, soil conservation is closely allied to improvement of land use in general.

In OC mines, the earth material is dug out to extract coal. The excavated over burden material consists of alluvial, top soil, sub soil and rocks. The OB is placed in the nearby areas in the form of dumps. If no measures are taken for the management of OB dumps, after precipitation, water will take away the soil particles along with itself thereby causing soil erosion. This eroded soil will flow into the nearby streams, rivers, water channels and cause choking/contamination of the water bodies. In order to prevent this, an effective soil erosion management plan needs to be prepared and implemented.

MITIGATIVE MEASURES TO MINIMIZE SOIL EROSION AND CHOKING OF STREAMS

In order to control soil erosion, a step by step procedure needs to be adopted so that the water flows through a proper path and does not take away with it the essential soil material. The steps to be followed are:

1. Garland Drains: To arrest the surface runoff into the quarry, garland drains with suitable dimension (4 m x 1.5m) to carry the peak discharge are constructed.



B. PLANTING OF ADEQUATE DROUGHT HARDY PLANT SPECIES AND SOWING OF SEEDS IN THE APPROPRIATE AREA WITHIN THE MINING LEASE TO ARREST SOIL EROSION

In view of importance of vegetation cover towards environment, the technical reclamation will be strengthened by biological reclamation for conserving the environment.

Plantation Technique on Overburden Dumps

To improve the environment and greenery in the area, SECL had taken up plantation on a larger scale. The improvement in vegetation cover has a direct bearing on augmentation of ground water recharge. The compensatory afforestation has been carried out through the State Forest Departments. In addition to compensatory afforestation, to improve the greenery and dust control, the project did heavy plantation both on reclaimed and at various other locations

in the project area. This greenery not only controls air pollution but also controls the soil erosion and increase groundwater recharge.

The top surface of the overburden dumps selected for plantation will be roughly levelled by dozer keeping a mild slope of about 1 in 200 for surface water drainage.

Seeds of grass legumes will be sown on beds of 1.5m x 0.5 m, alternating with slopes to be planted with tree species. Gully plugging and constructing check dams on water courses flowing through OB dumps with boulders, will also be made to arrest soil erosion.

In SECL Plantations are carried out by CGRVVN (Chhattisgarh Rajya Van Vikas Nigam Limited). Long term MoU has been signed between SECL and CGRVVN Ltd. Raipur for five consecutive years plantation works with subsequent maintenance of four years in SECL command area in Chhattisgarh State.

Various species suggested for plantation are:

- Fruit bearing (15%) & Medicinal / Herbal (35%): Jamun, Imli, Ganga Imli, Bel, Mango, Neem, Bahera, Amla, Mahua, Kusum, Arjuna etc.
- Timber/ forest (48%): Teak, Shisham, Siris, Bamboo, Babool, Ghamhar, Pipal etc.
- Ornamental / avenue (2%): Gulmohar, Kachnar, Gravelia, Ashok, August etc.
- Grass Species: StyloHemata, Dinanath on slope of OBD

TOP SOIL MANAGEMENT PLAN

Introduction

The topsoil at Gevra OC Expansion (35.0-70.0Mty) comprises of rich humus with minerals and nutrients. Proper handling and management is necessary for future vegetation growth in the mine reclaimed area. The thickness of the top soil varies between 25 cm to 35 cm.

Objectives of the Soil Stripping management plan

The objectives of Top Soil Management are to:

- Maintain a topsoil balance that achieves rehabilitation objectives during the life of
- · Ensure effective topsoil removal techniques are employed to maximize volumes of suitable topsoil removed and minimize wastage.

 Maintain topsoil viability during stripping, spreading, and stockpiling, through best practice technique and effective stockpile design and treatment.

In accordance with the objective of providing sufficient stable soil material for rehabilitation and to optimize soil recovery, the following strategies will be adopted during the mining operation at Gevra opencast mines.

Prior to the commencement of stripping, areas will be cleared of vegetation. Soil stripping will be undertaken by dozers and hydraulic backhoe excavators to maximize the preservation of the quality of the soil. The HEMM operators and supervisors should be trained and made aware for the same. This will ensure that all suitable topdressing material resources are salvaged and that the quality of the stripped top dressing material is not reduced through contamination with unsuitable soils. Care will be taken during stripping, stockpiling, and re-spreading to ensure that structural degradation of the soil is avoided and that excessive compaction does not occur during stockpiling.

Stock piling

- Where possible, top dressing material will be re-spread directly from stripped areas onto areas being rehabilitated. Where this is not possible, topdressing material will be stored in stockpiles.
- Stock piles will be dumped at places where they would not be disturbed by future mining. Sediment fences or other barriers can be used where necessary to retain
- The overall topography for the graded surface should be designed to minimize the uncontrolled flow of runoff.
- Dispersed sheet flow should be broken up by terraces or benches along the slope that also follow topographic contours.
- On a fine scale the ground surface can be roughened by the tracks of a bulldozer perpendicular to the slope. Construction of stockpiles with a "rough" surface condition will reduce erosion hazard, improve drainage and promote re-vegetation.

Stockpiling topsoil may result in disruption & loss of beneficial soil microorganisms and nutritional values, hence needs the following amendments during preservation:-

- 1) Re-vegetation of the stockpile will be done as scheduled below to protect the soil from erosion, discourage weeds and maintain active populations of beneficial soil microbes.
 - Temporary Seeding- To protect topsoil stockpiles by temporarily seeding as soon as possible, within 30 days after the formation of the stockpile.
 - Permanent Vegetation- If stockpiles will not be used within 12 months they will be stabilized with permanent vegetation to control erosion and weeds. Likely grass species for re-vegetating top soil stock piles are green panic, Japanese millet (spring sowing), Oats (winter sowing), Dryland Lucerne, Seaton park sub-clover.

Topsoil can be mixed with organic material or manufactured soil amendments to improve the growing capability.

2) To the extent practicable, above ground vegetation, including tree litter should be mixed or otherwise incorporated into the topsoil.

3) Soil amendments: Soil amendments should be applied before seeding or planting. Common soil amendments used are bio-solids, compost, manure, lime and coal

combustion byproducts.

Prior to the placement, the top 0.30cm of the stock pile material should be mixed with the remainder of stockpile to ensure that living organisms are distributed throughout the top soil material at the time of final placement. In case, the material has been stockpiled for over nine months period, used of micro organisms inoculates may be necessary to reestablish microorganisms in the top soil material. The quantity should be 200ml for one Ha. area in case of Azatobactor and Rhizobium.

Site Preparation

· Before spreading topsoil, establish erosion and sedimentation control structures such as diversions, berms, dikes, waterways and sediment basins.

Adjust grades and elevations for receipt of topsoil.

Roughening - Immediately prior to spreading the topsoil, loosen the sub-grade to ensure bonding of the topsoil and subsoil.

Soil horizons will be replaced in the same order that they were removed.

Top soil will be uniformly distributed to pre-mining thickness. Topsoil will not be spread while it is frozen or muddy.

The topsoil will be compacted to ensure good contact with the underlying soil, but excessive compaction will be avoided, as it increases runoff and inhibits seed germination. Light compaction with roller will be done where turf is to be established.


On slopes and areas that will not be mowed, the surface will be left rough after spreading topsoil.

Monitoring


Specific team / manpower is to be deployed for this most important step of topsoil management. The team will monitor the area and quantum of top soil management with the authorities of mine on quarterly basis and regularly monitor the given points of significant importance:

- · Monitoring Erosion Control: This step is necessary during stock piling as well as reclamation stage of topsoil management. Take corrective measure in areas showing evidence of erosion, sedimentation or slope failure. This is a serious problem, because erosion causes fertile farmland to lose nutrients and water retention ability
- · Regular monitoring of top soil management should be done until vegetation is demonstrated to be successfully established.
- Reseeding: Take appropriate measures to address evidence of invasive species or poorly established vegetation. Reseeding should be done, if germination is not uniform or poor.


YEARWISE PLANTATION AT GEVRA AREA



AVENUE PLANTATION




- C. CONSTRUCTION OF CHECK DAMS, RETENTION/TOE WALLS ALONG THE CONTOUR TO ARREST SLIDING DOWN OF THE EXCAVATEDMATERIAL
 - 1. Catch Drain: 2.8 KM of pucca catch drains of dimension 1.5 X 1.5 m were constructed for chanelling of surface runoff during Rainy Period.
 - 2. Check Dams & Retaining Wall: To prevent soil Erosion & arrest sliding down of excavated material along the contour. Regular maintenance is carried out to prevent siltation.



 2018-19 Plantation dump area have been provided with Contour trench 300 per trench, check dam 20 per cubic meter and bund with stone bolders 20 per cubic meter.







A toe wall is constructed at External Dump no. 6 & 7 of dimensions: Length 650 meters, height above ground 1.00 meters and top width of wall 200 mm in the year 2018-19

Year	Contour Trench (per trench)		Bunds with stone boulders (per CUM)
2022	11845	11845	11845
2021	7200	7500	7500
2018	300	20	20

Structure	Location	Dimension
Retaining wa with Drain	near W1 TRS	
	Along J3 belt	240mX 5m ht. 300mX 2m
	Near Junadih Siding	2050m X 2m ht. 1.2m X 0.9m drain
~	External Dump no. 6 & 7	650m X 1m ht. Top width 200mm
Gabion wall	From weigh bridge W5 to LK seam coal face side	1200m length, 3 stage, 3m height
	Along toe of dump no. 4 near E2/E1 TRS	342m, 3 stage, 3m height

STABILIZE THE OVERBURDEN DUMPS BY APPROPRIATE GRADING/BENCHING SO AS TO ENSURE THAT THAT ANGLES OF REPOSE AT ANY GIVEN PLACE IS LESS THAN 28°

PROGRAMME OF O.B. REMOVAL, DUMPING & PLANTATION:

		ОВ	Dump (Mc		Dump area a reclamati	vailable for on (Ha.)		lantation Nos / Ha.	Total plantation @ 2500 Nos / Ha.
ear	Coal production (MTes)	removal (Mcum)	External	Internal	External	Internal	External	Internal	O PROBABILITY OF THE PROPERTY
	40	72.69	0	72.69	0	0	0	0	0
1	65-95 N	72.67	0	72.67	0	0	0	0	0
2	41	100000	0	73.8	0	0	0	0	0
3	41	73.8			0	0	0	0	0
4	45	82.12	0	82.12	0	0	0	0	0
5	49	86.92	0	86.92		3975	0	147825	147825
6	61	108.62	0	108.62	0	59.13		147825	147825
7	70	125.06	0	125.06	0	59.13	0		147825
8	70	125.53	0	125.53	0	59.13	0	147825	SECRETE:
	70	125.51	0	125.51	0	59.12	0	. 147800	147800
9	1	125.17	0	125.17	0	59.12	0	147800	147800
10	70			125.09	0	63.36	0	158400	158400
11	70	125.09	0	124,000,000,000,000	0	63.36	0	158400	158400
12	70	125.51	0	125.51	N#8	63.36	0	158400	158400
13	70	125.54	0	125.54	0		0	158400	158400
14	70	124.82	0	124.82	0	63.36			158400
15	70	124.95	0	124.95	0	63.36	0	158400	The state of the s
16	70	107.8	0	107.8	0	63.36	0	158400	158400
	70	107.66		107.66	0	63.36	0	158400	158400
17			0	86.34	0	63.36	0	158400	158400
18	70	86.34			0	63.36	0	158400	158400
19	70	84.96	0	84.96		63.36	0	158400	158400
20	70	85.18	0	85.18		(A. T. C. S.	0	158400	158400
21	50	40.8	0	40.8	0	63.36		158400	200
22	30.68	29.89	0	29.89	0	63.36	0		
MC		0	0	0	0	77.3	0	193250	
	1	0	0	0	0	77.3	0	193250	
MC	*	0	0	0	0	77.3	0	193250	193250
MC	2.5e			2166.6	0	1287.8	5 0	321962	5 3219625
Tot	al 1337.68	2166.6	0	2100.0	,,				

The spoil dump benches in the internally backfilled OB will be in the form of benches. With the sufficient advance of coal production bench, the non-active backfilled OB will be leveled with dozer. Dumper/Tipper will transport soil/alluvium OB from the top OB bench and will dump the soil directly on the leveled backfilled OB. Otherwise; top soil will be removed and stored separately. This soil will be directly spread over the levelled graded backfilled spoil for reclamation of the quarried out land. OB dumps will be properly benched and the maximum height of the bench will be kept not more than 30m. Dump benches will have a mild gradient of 0.6% to facilitate the drainage. Wherever possible, simultaneous land reclamation will be done along with the OB dumping.

The following design criteria have been considered for waste dumps.

- (i) OB in external dumps will be stacked in 30 m high benches.
- (ii) OB in internal dumps will also be stacked in 30 m high benches.
- (iii) Dozers to be deployed for shaping the dumps overall slope is 28°.
- (iv) Final reclamation will be achieved using the equipment provided for the purpose.

Once, the external dumping is completed, the spoil will be graded and landscaped in harmony with surrounding topography and biological reclamation carried out. Alternatively, the final void at the end of mining operations in the mine can be converted into a water reservoir.

RECLAMATION SCHEDULE

E. STRICT ADHERENCE TO THE PRESCRIBED TOP SOIL MANAGEMENT

Systematic handling of topsoil

Topsoil shall be removed before any drilling, blasting, mining, or other surface disturbance. The stock piling of top soil will be as follows:


 Top soil and other materials removed shall be stock piled only when it is impractical to promptly redistribute such materials on regarded areas. • Stock-piled materials shall be selectively placed on a stable area, not distributed, and protected from wind and water erosion, unnecessary compaction, and contaminants which lessen the capability of the materials to support vegetation when redistributed.


Top soil redistribution

After the final grading the top soil would be redistributed in a manner that achieves an approximate uniform stable thickness consistent with the post mining land uses, contours, and surface water drainage system.

Biological reclamation

In view of importance of vegetation cover towards environment, the technical





reclamation will be strengthened by biological reclamation for conserving the environment.

FINANCIAL PROVISIONS

Financial provision for soil erosion management

C 11	Activity	Amount (in Rs. Lakhs)
S. No.	9	30.00
1.	Garland Drains Arboriculture/plantation in industrial area	5.67
z. 3	Barbed fencing/boundary walls/Toe walls/Gabion structures for the project	19.37
	Land Reclamation / Restoration	42.50
4.	Green Belt in and around the Mine	10.00
5	Green Belt in and around the Mine Total	107.54

^{*} Subsequent additional provision will be made as and when required.

Existing Mine Closure Cost as per approved MCP

As per the guidelines of the MoC, the cost of the mine closure cost was computed based on project area of Gevra OCP i.e, 4184.486Ha. Considering the wholesale price index as 136.30, as on April 2010, the updated cost of the mine closure is estimated to be Rs. 6.312 lakhs per hectare (considering three decimal places) considering the admissible escalation over Rs. 6.00 lakh per Ha as on August 2009 when wholesale price index was 129.60.

Total Final mine closure cost (@ Rs.6.312 Lakh/Ha.): Rs.26412.48lakhs

Table-1: Existing Fund deposit & Reimbursement Schedule

Year	Fund Deposited in Escrow Fund	Fund to be Re (Maximum)	eimbursed	
1	1100.52	Nil		
2	1155.55	Nil		
3	1213.32	Nil		
4	1273.99	Nil		
5	1337.69	Nil		
1st phase	6081.07	4864.85		
6	1404.57	Nil		
7	1474.80	Nil		
8	1548.54	Nil		
9	1625.97	Nil	(+) accrue	
10	1707.27	Nil	interest as applicable	
2nd phase	7761.15	6208.92	- applicable	
11	1792.63	Nil	1	
12	1882.26	Nil		
13	1976.38	Nil		
14	2075.19	Nil		
15	2178.95	Nil		
3rd phase	9905.42	7924.33		
16	2287.90	Nil		
17	2402.30	Nil		

18	2522.41	Nil
19	2648.53	Nil
20	2780.96	Nil
4th Phase	12642.10	10113.68
21	2920.01	Nil
22	3066.01	Nil
23	3219.31	Nil
24	3380.27	Nil
final phase	12585.60	19863.54
Total	48975.34	48975.34

REVISED MINE CLOSURE PLAN(PHASE 1& 2)-

The Mine closure plan for Gevra OC 70 Mty was part of the Project report & is deemed approved along with the Project report. All MCP activities for this Mining plan will be as per mentioned in the PR.

A-REVISED ABONDONED COST & FINANCIAL ASSURANCE (As per the new Guidelines & Latest WPI)

TABLE-2: Progressive & Final cost distribution table in an OC mine as per New Mine Closure Guidelines issued by MoC on 16/12/2019

S. No.	Activity	Progressive	Final
Ā	Dismantling of Structure		
	Service building	0	8.50
	Residential Building		
	Industrial Structure		
В	Safety & Security		
	Random rubble masonry/concrete wall		
	Toe wall around dump/Gabion wall	6.50	3.20
	Barbered wire fencing		
	Fencing/boundary wall, fencing around water		

S. No.	Activity	Progressive	Fina
	body		
	Garland drains	-	
C	OB Dump Reclamation		
I	Technical Reclamation		_
	Re-handling of OB	1	
	Levelling by Dozer		
	Grading	60.50	60.50
	Levelling and grading of high wall slopes & OB Dump	-	
II	Biological Reclamation & Plantation		
	Top soil Management		
	Grassing of OB dump	1	
	Plantation around virgin Area, safety zone, green belt, over external Dump and internal reclaimed area	15.00	11.70
	Plantation post care (including manpower)		
	Plantation over cleared area obtained after dismantling		
	Landscaping of the open space in leasehold area for improving its aesthetic. Drain, Pipe lines, Peripheral road, gates, View points, cemented steps on bank	4.00	5.50
	Development of Agriculture land		
Е	Environment mitigation & management		
	Air Quality (Water tanker, Sprinkler & other Control measures)	12.00	1.50
,	Water Quality (ETP & STP etc operating cost)		2.00
	Manpower Cost and supervision		
F	Post Closure Monitoring	0.00	

S. No.	Activity	Progressive	Final
	Air Quality		
	Water Quality		
	Power Cost		
	Manpower Cost and supervision	_	
G	Entrepreneurship Development (Vocational/skill development training for sustainable income of affected people)	1.00	0.50
Н	Miscellaneous & Other measures like Golden Handshake, one time financial grant, alternative jobs, other services etc.	1.00	5.40
	Total	100.00	100.0

22.3 Financial Assurance

A- Financial Assurance

Revised Mine Closure Cost based on latest WPI and adjustment of amount already deposited in the escrow account, as per the direction of CCO office

The amount that has to be deposited in Escrow account acts as a security against the mine activities to be carried out for the closure of the mine is based on the project area.

As per para 2.6 (Escrow Account Calculation) of MOC guideline no. F. No. 34011/28/2019-CPAM, Ministry of Coal dt 16th December 2019 & 29th May 2020, in case of the mine where escrow account is already open, the annual closure cost is to be computed considering the total project area at the above mentioned rates minus the amount already deposited and dividing the same by the balance life of the mine in years and annual cost as arrived should be compounded @5% annually.

The total Land Area envisaged in the project (Phase I & 2) is 4781.798 Ha

As per the latest guidelines of MOC, the amount to be deposited in Escrow account is evaluated as per detailed below:

TABLE-3: EVALUATION OF REVISED MINE CLOSURE AMOUNT- PHASE I

A	BASE RATE/HA IN LAKH RS AS ON 1st APR 2019	9
В	WPI AS ON 01.04.2019	121.1
C	MCP LAND IN HA	4781.798
D	WPI AS ON MAR 2022*	148.9
E	ESCALATION FACTOR (D/B)	1.2295623
F	RATE/HA IN LAKH Rs (E * A)	11.066
G	CORPUS IN LAKH Rs (F * C)	52915.669
H	Balance life in years as on 01.04.2022	16
Ι	Amount Deposited till 31.03.2022-lakh Rs	17517.11
J	Final corpus amount in lakh Rs (G-I)	35398.559
K	First Year amount in lakh Rs(J/H)	2212.4099
L	Total amount to be deposited in balance years in Lakh Rs.	52340.070
	□ WPI of Apr 2022 & May 2022 are provisional	

Table-4: Fund deposit & Reimbursement Schedule from 2022 onwards

Year	Year No	Fund Schedule in Lakh Rs	Fund to be Reimbursed (Maximum) in lakh Rs
EXISTIN	IG MCP DEPO	OSIT SCHEDULE	UPTO 2021-22
2020-21		1792.630	
2021-22		1882.260	
REVISE	D MCP DEPO	SIT SCHEDULE V	V.E.F 2022-23
2022-23	1	2212.410	
2023-24	2	2323.030	

Progressive	Phase-1	6974.622	50% of balance amount at the end of Phase-1
2025-26	4	2561.141	
2026-27	5	2689.198	
2027-28	6	2823.658	
2028-29	7	2964.841	
2029-30	8	3113.083	
Progressive	Phase-II	14151.921	
2030-31	9	3268.737	
2031-32	10	3432.174	
2032-33	11	3603.783	
2033-34	12	3783.972	
2034-35	13	3973.170	
Progressive	Phase-III	18061.836	
2035-36	14	4171.829	
2036-37	15	4380.420	
2037-38	16	4599.441	
MC1	17		
MC2	18		
MC3	19		
Final Phase		13152	100% of balance
GRAND TOTAL	40	52340	of final Phase

Table-5: COST ESTIMATE FOR PROFRESSIVE & FINAL CLOSURE ACTIVITIES

COST OF ACTIVITIES TO BE TAKEN UP FOR PROGRESSIVE CLOSURE OF MINE

Head	PARAMETERS	Unit	Amoun "Rs. Cr
Progressive closure	Water quality management	LS	9.06
	Air quality management	LS	16.31
	*Waste Management	LS	7.25
	Barbed wire fencing	LS	1.96
	Barbed wire fencing around the Pit	LS	1.96
	Filling of Void - Rehandling of Crown Dump	LS	18.27
	Top Soil management	LS	22.65
	Technical l Reclamation of Mined out of land and OB Dump	LS	155.31
	Biological Reclamation of Mined out of land and OB Dump, Plantation over virgin area including green belt	LS	20.39
	Manpower Cost and supervision	LS	18.20
	Toe Wall around the dump	LS	2.94
	Garland drain	LS	3.62
	Garland Drain around the dump	LS	2.42
	Any other Activity	LS	3.02
Dismantaling of Infrastructure & Disposal/ rehabilitation of Mining machinery	Dismantling of workshop	LS	18.82
	Rehabilitation of the dismantled Facilities	LS	
	Dismantling of pumps and Pipes/ other facilities	LS	
	Dismantling of stowing bunker, provisioning of pumps for bore well pumping arrangement	LS	
	Dismantling of UG equipment	LS	

	Rearranging water pipeline to dump top park/ Agricultural land	LS	
		LS	
11	Barbed wire fencing	LS	1.96
ŀ	Barbed wire fencing around the Pit	LS	1.06
	Barbed wire fencing with masonry pillars	LS	0.35
	Concrete wall with Masonry pillars around the pit	LS	
	Securing air shaft and installation of bore well pump	LS	
	Securing of Incline	LS	
	Concrete wall fencing around the water body	LS	
	Boundary wall around the water body		8.72
	Stabilisation! viz benching, pitching etc) of side walls of the water body		
	Toe Wall around the dump	LS	3.38
	Garland drain	LS	4.87
	Garland Drain around the dump		
	MISC SAFETY WORKS	LS	2.40
Technical and Biological Reclamation of Mined out of land and OB Dump	Drainage Channel from main Ob dump	LS	4.85
	Filling of Void	LS	66.97
	Top Soil management	LS	10.36
	OB Rehandling for backfilling	LS	66.97
	Terracing, blanketing with soil and vegetation of External OB Dump	LS	7.77
	Peripheral road, gates, view point, cemented steps on bank	LS	4.24
	Expenditure on development of Agricultural land	LS	1.22
	Landscaping and Plantation	LS	9.60
Post Closure management and	Power Cost	LS	1.04
	Post Mining Water quality management	LS	2.08

supervision	Post Mining Air quality management	LS	4.16
Ì	Subsidence monitoring for 5 years	LS	0.00
	Waste Management	LS	2.08
	Manpower Cost and supervision	LS	1.04
	Entrepreneurship development (vocational/skill development training for sustainable income of affected people	LS	4.13
	Golden Handshake / Retrenchment benefits to 100 employees of OC	LS	
Others	Golden Handshake / Retrenchment benefits to 200 employees of UG	LS	
	Onetime financial grant to societies / institutions /organisations which is dependent upon the project;	LS	11.96
	Provide jobs in other mines of the company	LS	
	Continuation of other services like running of schools etc.	LS	
Total	COST FOR THE ENTIRE LIFE (Prog & Final)		523.40
Total			323.40
10001	TOTAL ANNUAL COST		32.71
Total	PROGRESSIVE COST FOR THE ENTIRE LIFE		302.01
Total	ANNUAL PROGRESSIVE COST		18.88

TIME SCHEDULE

The time scheduling is being provided on the basis of time interval of five year as required in the MoC guidelines. This period of 5 years is considered as one phase of five years and reclamation of one phase must be taken-up before commencement of mining activity in the subsequent phase. The action plan for progressive closure activities has been provided in the Figure below:


Sl. No.	Activities	Time Frame
1.	Preparation of Survey & Disposal Report	One month
2.	Slope Stability study for high walls and	One month
	internal backfilled dumps	
3.	Disposal of P&M including HEMM, CHP,	2 and half
	W/S, Siding	years
4.	Backfilling of mined out Area (OC)	2 years
5.	Dismantling of Industrial structure	2 years
6.	Grading & dozing of high walls for OC	2 years
7.	Fencing of quarry	2 years
8.	Clearing of Coal Stock and Infrastructural	2 years
	Area.	
9.	Disposal / Dismantling of Residential colony	2 &1/2 years
9.	Disposal / Dismantling of Residential colony	2 & 1/2

REIMBURSEMENT OF EXPENDITURE INCURRED ON PROGRESSIVE MINE CLOSURE ACTIVITIES OF GEVRA OCP

The Progressive Mine Closure Plan for Gevra OCP has been approved in the 218th meeting of SECL Board held on 28.11.2013. Accordingly, Escrow Account No: 423803800000294 is opened in Union Bank of India, Bilaspur and Annual Deposits as per the approved MCP have been made in the above account regularly since 2010-11 and the balance amount as on 31.03.2023 is Rs.1346459196/-only in the said account. As per the clause No: 6 of MoC guidelines dated 07.01.2013 and provisions of approved MCP, the reimbursement of expenditure on Mine closure activities has been received in respect

of Gevra OCP for the activities undertaken from 2010-11 to 2014-15. A total amount of Rs. 514721000/- was recommended for release by Coal Controller on 17.08.2017.

For the period from 2015-16 to 2019-20, an amount of Rs. 577323000/-has been reimbursed under Progressive Mine Closure.



SOUTH EASTERN COALFIELDS LIMITED

GEVRA AREA STATUS OF TECHNICAL & BIOLOGICAL LAND RECLAMATION DETAILS OF GEVRA PROJECT AS ON 01.07.2023

					Section Printed	S. C. BAAAKER	ED AREA DETAILS	LS (In Mect.)			æ	EXTERNAL 08 D	UMPS DET/	VLS (in Hact.		Total Reci	Total Reclaimed area
Name of Area	Zana A	Approved EC Capacity (MTY)	Total Quartable area of the project as per apparoved EMP(OVTN) (Hac.)	Void be left at the closure of the project as per approved EMP(70MTY)	Total Area Prorate area excavated as not required to be to be 01 07 2023 Beachfield (Ha) (Ha)	Provate area not required to be Becidilled (Ha.)	Total area technichally reclaimed Aeddited as on 01.07.2023 (Hac.) (InVDump)	Balance area to be Technically reclaimed becidited at as on 01 07 2023 (Hect)	Area aiready biological reclaimed as on 01.07.2023 (Hact.)	Area arready Balance area to biological to be expected as a reclaimed as on 01.07.2023 (Heact)	Total area of Enternal OB dump as on 01.07.2023 (Hect.)	Area of Ext. OB dump technically reclaimed QE - as on 01.07 2023	Area of Ext. Balance area free already exert technically to be Bologi-cally reclaimed technically reclaimed technically reclaimed as as on reclaimed as as on on 01.07.2023 on 01.07.2023	Area already Bollogi- cally redairred as on 01.07.2023	Batance area to be biolog-ically rectamied as on 01.07.2023	Total Technically reclaimed as on 01.07.2023	Total Bollogically reclaimed as on 01.07.2023
Section 18												2	N-1-W	0	2	H-11	9
	•		0			0-(2-2)-0	z	H-0-H		7	1					-	-
4	-	VTV GS CS	3037 260	659.250	1796 216	661.869	945 267	271.050	137.600	1078.717	374.331	374.331	0.000	367.200	7.131	1319,098	904.60
Sevra area	50 845	Gevra area Covra Cor	-														

F= 1778,863+21,863 = 1781,216 H= 836,382 + 8,806 = 946,267 J= 122,800+16,00= 137,800

DY GM/COLLERY MANAGER GEVRA PROJECT

ENVIRONMENT OFFICER
GEVRA PROJECT THE

DY MANAGER (SURVEY)
GEVRA PROJECT

AREA SURVEY OFFICER GEVRA AREA

Co Bylander

GENERAL MANAGER GENRA PROJECT

NODAL OFFICER (ENVIFOREST) GEVRA AREA

GENERAL MANAGER GEVRA AREA

Quataly Rand Recommise

साउध ईस्टर्न कोलफील्ड्स लिमिटेड (एक मिनियुत्न कम्पनी) कार्यालय, महाप्रबंधक गेबराक्षेत्र पो आ -गेवरा प्रोजेक्ट,जिला -कोरबा पिन -495452फोन : 07815-275438 फैक्सः 07815-275434



South Eastern Coalfields Limited

(A Mini Ratna Company) Office of the General Manager Gevra Area, PO -Gevra Project, District - Korba(C.G.) Pin -495452 Phone: 07815 - 275438Fax: 07815 -275434 mail: socgevra@gmail.com,

Letter Number: SECL/GA/GM(C)/LOA/TA/23/ 278

Date: 25. 06.2023

BY SPEED POST

To

Santosh Agrawal, Bhairotal Surakachhar, Korba (CG)

e-mall:- santoshagrawal.2010@rediffmail.com

PAN -AGJPA2217J

GSTIN - 22AGJPA2217J1ZY Contact No: Mob-9329126511

विषय/Subject

Letter of Acceptance (LOA) for the work of "Desiltation of ponds for "

Bhilai Bazar, Khodri, Hardibazar, Suhabori & malgaon Village at GA."

सन्दर्भ/Reference :

NIT No. : SECL/GA/GM(C)/ETN/23-77/27, DT 16/05/2023

Tender Id: 2023_SECL_279379_ II.

III. Bid Id: 953264

Dear Sir,

With reference to above, this is to communicate the approval of the Competent Authority for award of the subject work to you for an amount of ₹ 80,71,200.00 (Rupees Eighty lakh seventy one thousand two hundred) only inclusive of Goods and Service Tax (GST) with following

Description	Amount. (₹)
Quoted Offer without Goods and Services Tax (GST) component [Cost To Company(CTC) being a case of Input Tax Credit (ITC) Not Available]	68,40,000.00
Goods and Service Tax @18% on Quoted Offer	12,31,200.00 <
Total Award Value including Goods and Service Tax (GST) [(i) + (ii)]/Total Contract Price	80,71,200.00
	Quoted Offer without Goods and Services Tax (GST) component [Cost To Company(CTC) being a case of 'Input Tax Credit (ITC) Not Available] Goods and Service Tax @18% on Quoted Offer Total Award Value including Goods and Service Tax

This Letter of Acceptance (LOA is subject to the following terms and conditions:

PERFORMANCE SECURITY DEPOSIT (PSD):

(a) An amount of Rs 1,64,800.00 (Rupees One lakh sixty four thousand eight hundred)deposited ONLINE through AXIS Aggregator Bank Net banking is vide UTR No.137278100 being adjusted as a part of Performance Security Deposit (PSD).

119.36, 110

You have to deposit a sum of ₹ 2,38,760.00 (Rupees Two lakh thirty eight thousand seven hundrd sixty) only against amount of PSD to make the total Performance Security Deposit (PSD) as 5% of the contract value [i.e. ₹ 80,71,200.00 (Rupees Eighty lakh seventy one thousand two hundred) only)], within 21 (Twenty-One) days of issuance of LOA, as per Clause No.4 (Security Deposit) of General Terms & Conditions of Contract.

- (b) Performance Security Deposit (PSD) as mentioned at (a) above may be deposited in any of the form given below:
 - Demand Draft drawn in favour of South Eastern Coalfields Limited, Gevra Area on any Scheduled Bank payable at its Branch at Gevra (C.G.).

Govt. Securities or FDR duly pledged in favour of South Eastern Coalfields Limited Gevra

 Bank Guarantee in SFMS (Structured Financial Messaging System) mode from any Scheduled Bank in the prescribed format as given at Annexure-V of bid document. The BG issued from outstation Bank should be operative at its local Branch at Bilaspur (C.G.) or at their branch at Kolkata (if the issuing bank does not have any branch at Bilaspur).

 The Bank Guarantee (BG) issued by the issuing Bank on behalf of contractor in favour of "South Eastern Coalfields Limited" shall be in paper form as well as issued under "Structured Financial Messaging System (SFMS)". The details of Beneficiary Bank for issue of BG under SFMS Platform have been mentioned under Cl. No.4 of General Terms & Conditions of Bid Document. Performance Security Deposit (PSD) submitted in the form of BG shall be valid for a period of one year or 90 days beyond the period of Contract/extended Contract period (if any), whichever is more.

Failure to comply with the requirement as above shall constitute sufficient ground for cancellation of the award of work and forfeiture of EMD. Additionally, you will not be allowed to participate in the re-tendering process and you also be debarred from participating in future tenders in SECL for a minimum period of 12 (Twelve) months.

(c)That all Running on Account bills shall be paid at 95 % (ninety five percent) of the executed work value. The balance 5 % (Five Percent) shall be treated as Retention Money and will be second part of Security Deposit.

GOODS & SERVICE TAX:

(i) Applicable.

(ii) Input Tax Credit is Not Available to SECL.

(iii) In the event of recovery of any claim towards LD Charges, Penalty, fee, fine or any other charges from the contractor, the same will be recovered along with the applicable GST and the amount shall be adjusted with the payment to be made to the contractor against their bill/invoice or any other dues.

PERIOD OF COMPLETION:

That the work should be completed within a period of 150 (One hundrfed fifty days) from the date of commencement which shall be reckoned from the 10th day of issue of this LOA or from 7th day of handing over of the site, whichever is later.

PRICE VARIATION CLAUSE:

Price Variation Clause [Cl.No.2] of Additional Terms and Conditions of Contract is Not APPLICABLE for this contract.

You will arrange necessary electricity at your own cost for the work and your own establishment. ELECTRICITY: However, if available and feasible the company may arrange electricity at one point hear the work

site and necessary recovery of cost of energy consumed will be made at rates prescribed by the company from time to time. Energy meter for this purpose shall be provided by you.

WATER:

You will arrange necessary water for the work and your own establishment and nothing extra will be paid for the same. Such water used by you shall be fit for construction purposes. However, if available and feasible the company may arrange water, on your written request, to the extent possible, at one point near the work site for which recovery @ 1%(One Percent)of the contract value of work done will be made from your bills. You will make your own arrangement of water connection and laying of pipe lines from main source of supply. Department do not guarantee to maintain uninterrupted supply of water. No claim of damage or refund of water charges will be entertained on account of such break down.

EMPLOYMENT OF LABOUR:

(a) That you have to make payment to the labours engaged by you for this work as per Minimum Wages fixed by Central/State Govt.(higher) as per Minimum Wages R&A Act, 1970or minimum wages recommended by High Power Committee of CIL(for labours engaged in mining activities),

(b) The payment to the contractor's labourers has to be made through Bank only and necessary payment certificate shall be obtained from the authorized representative of the department.

(c) That the payment of Provident Fund for the workmen employed by you for the work as per the Laws prevailing under provision of CMPF/EPF and allied scheme valid from time to time shall be your responsibility. You will also submit statutory returns.

(d) That you have to comply with statutory requirements of various acts including Child Labour (Prohibition & Regulation) Act, 1986 as mended from time to time and all rules, regulations and schemes framed there under from time to time in addition to other applicable labour laws. If it is reported and proved that child labour is engaged by you, then you will be penalized 10% of the

(e) That you have to follow other guidelines as incorporated at Clause No.13 of General Terms & Conditions of NIT covered under Additional Responsibilities of the Contractor(s).

(f) Bonus is to be paid to the contract workers engaged by the Contractor as per the provisions of

(g) The contractors shall register themselves on the Contract Labour Payment Management Portal (CLPMP) of CIL within 30 days of issue of work order and will have to enter and update periodically the following details in the portal: (i). Work Order details

(ii). Contractor workers details and Wages payment details in respect of each Work Order.

(h) Coal Mines Pension (Amendment) Scheme, 2018

(A) In consideration of changes in statutory provisions, CMPF (Coal Mine Provident Fund) /EPF (Employee Provident Fund) Contribution is to be deducted @12% (Twelve Percent) as both Employer & Employee Share. Hence, Employers (SECL in present case) share of CMPF/EPF Contribution @12% (Twelve Percent) has been loaded as input in minimum wage while formulating the proposal/estimate. Hence, the contractor shall pay the employer's share i.e. 12% (Twelve Percent) towards CMPF/EPF contribution to the labour who have been engaged in the work. No reimbursement shall be made to the contractor on this account.

(B) In consideration of changes in statutory provisions, CMPS (Coal Mine Pension Scheme) Contribution is to be deducted @7% (Seven Percent) as both Employer & Employee Share. Hence, Employers (SECL in present case) share of CMPS Contribution @7% (Seven Percent) has been loaded as input in minimum wage while formulating the proposal/estimate. Hence, the contractor shall pay the employer's share i.e. 7% (Seven Percent) towards CMPS contribution to

the labour who have been engaged in the work. No reimbursement shall be made to the contractor on this account.

(i) Attendance of Contractors' Workers through Bio-metric Attendance System:

The attendance of all the employees/workers engaged by Contractors' is to be marked through Biometric Attendance System only.

8. ALR & AHR ITEMS:

That in accordance to the provisions under Clause No.5.6 of 'Conditions of Contract' of the NIT document, the rate quoted by you for the following items will be treated as Abnormally Low Rate (ALR) and Abnormally High Rate (AHR) items for the work as per BOQ (Bill of Quantity) in tender:

ALR ITEMS: 1.01

AHR ITEMS: NIL

That 'Additional Performance Security (APS)' Deposit is ₹ 31,30,675.00 (Rupees Thirty one lakh thirty thousand six hundred seventy five), as per letter No. GM©/SECL/BSP/e-proc./Standard NIT/2020-21/990 dtd. 04.12.2020, issued by GM(C/HOD, having salient features with provision of no Earnest Money Deposit (EMD), 3% Performance Security Deposit (PSD) and no Additional Performance Security (APS).

9. INSURANCE POLICY:

That you have to take necessary insurance for the full contract period for (i). Workmen Compensation & (ii). Contractors All Risk (CAR) Policy, in the joint name of South Eastern Coalfields Limited and the Contractor as per Clause No.13 (xviii) of General Terms & Conditions of NIT. The Policies and certificates for insurance shall be delivered by you to the Engineer-in-Charge for his approval before commencement of the work.

10. SAFETY MEASURES:

That the Precautions shall be exercised at all times by you for the protection of persons (including employees) and property. The safety required or recommended by all applicable laws, codes, statutes and regulations shall be observed by you. In case of accident, you will be responsible for compliance with all the requirements imposed by the Workmen's Compensation Act or any other similar laws enforce and indemnify the Company against any claim on this account.

11. WORKER'S WELFARE CESS:

That an Amount of 1% (one percent) of the work value payable to you will be deducted from all Bills towards the worker's welfare under "The Building and Other Construction Worker's Welfare Cess Act,1996" and "The Building and Other Construction Worker's Welfare Cess Rules,1998" (as applicable in the State).

- 12. That all other terms and conditions as given in the tender document shall also be binding on you.
- 13. That matters relating to any dispute or differences arising out of this work order and subsequent contract agreement entered, based on this tender and work order shall be subject to the jurisdiction of District Court, Korba (CG) only.
- 14. That as per Clause No.6 under General Terms & Conditions of Contract, you have to submit a detailed time and progress chart prepared based on Bar Chart/ PERT-CPM techniques on the basis of

construction schedule in consultation with the Engineer-in-Charge showing the order in which the work is proposed to be carried out within the time specified in the LOA/Work Order.

- 15. That as per Clause No.1 (vii) of General Terms & Conditions of Contract, the Engineer-in-Charge for
- 16. That the Paying Authority for this work will be the Area Financial Manager", SECL, Gevra Area.
- 17. That you have to submit the following documents and to attend this office for signing the agreement
 - An amount of ₹2,38,760.00(Rupees Two lakh thirty eight thousand seven hundred sixty) only towards Performance Security Deposit (PSD)[as per Cl. No.1 (a) of LOA].
 - An amount of ₹ 31,30,675.00 (Rupees Thirty one lakh thirty thousand six hundred seventy five) only towards Additional Performance Security Deposit (APSD)[as per Cl. No. 8

Site handover and takeover certificate, jointly signed by Engineer-in-Charge and the

- iv. Labour License as per Contract Labour (Regulation & Abolition) Act, 1970.
- Insurance Certificates as per Clause No.13 (xviii) of General Terms & Conditions of NIT.
- vii. Detail Time and Progress Chart, jointly signed by Engineer-in-Charge and the Contractor.
- vili. Mandate Form duly signed by you and the Bank Officials for e-Payment as per Clause No.
- ix. List of Technical & Supervisory Personnel to be deployed for Execution of the work.
- 18. Time bound completion of work along with quality assurance to be ensured strictly. All statutory payments including Minimum Wages, Bonus and PF to be ensured as per uploading

(https://coalindiatenders.nic.in) shall be treated as the date of receipt of this LOA/ Work Order by you.

For further instructions, please contact C.M.(C)/TA,GA

Failure to comply clause 17 within 21 days will lead to termination of contract. forfeiture of EMD, additionally the company shall ban such defaulting contractor from participating in future tenders in concerned Subsidiary/CIL HQ for a period of minimum 1 (one) year from the date of issue of such letter*. In case of JV/Partnership firm, the banning shall also be applicable to all individual partners of JV/Partnership

Encl: BOQ

General Manager (Civil) Gevra Area

Yours_faithfu

Copy to:

1. ALC, Torwa Naka, Bilaspur, Chhattisgarh, PIN-495006.

2. AFM/GA vide BC No. GA/23-24/OCW/TA/110/32 DT 19.06.2023 For ₹ 20,00,000/-, Input Tax

3. C.M.(C)/TA,GA - with an advice to immediately handover the site to the Contractor with intimation

- 4. APM/GA with a request to kindly arrange for issuance of LPC of previous month latest by 10th of next month after proper verification and confirmation of records and to send a copy of the LPC to this office. LPC should be issued every month for which documents should be spught from contractor. LPC should bear the dated signature of issuing Officer & Contractor with sea 5. O/S, GA
- 6. Work file

Biddin

Item Rate BoQ

	nviting Authority: General Manager (Civil),SECL : Gevra Area Desiltation of ponds for Bhilal Bazar, Khodri, Hardibazar, Suhabori & M Village at Gevra Area.	algaon I	NITNo:SECL/G 16.05.2023	Á/GM(C)/ETN/23-24	<i>I</i> 27 DT
	Category of Services (To Be Selected by Department)	Category of Bidder (To Be Selected by Bidder)	* *		
ITC Not Availa	Works Contract	Bidder's Status (Mandato ry)	The same of the same of	GST to be Paid By Bidder (in Rs.)	GST to be Paid By CIL/Subsidiary (In Rs.)
ble Name of the Bidder		GST Registere d Bidder(b	1231200.00	1231200.00	0.00

(This BOQ template must not be modified/replaced by the bidder and the same should be uploaded after filling the relevent columns, else the bidder is liable to be rejected for this tender. Bidders are allowed to enter the Bidder Name and Values only)

	is liable to be rejected for this tender. Bidd	NUMBER#	TEXT#	NUMBER#	NUMBER#	TEXT#
SI. No.	TEXT *	Quantity	Units	BASIC RATE	Without Taxes in Rs. P	TOTAL AMOUNT In Words
	Part of the State	3	4	6	1 7	1 -
1	2			/	,	
	Item Description/ Heading		Cum	70.00	6300000.00	INR Sixty Three Lakh
	Earth work in excavation by mechanical means (Hydraulic excavator) over areas (exceeding 30 cm in depth. 1.5 m in width as well as 10 sqm on plan) including disposal of excavated earth, with lead of 3.00 km and all lifts, disposed earth to be levelled and nearly dressed. All kind of soil. (like spillage / OB muck, slush earth etc.)		metre	20.00	540000.00	INR Five Lakh Forty Thousand Only
1.02	Extra rates for quantities of works, executed: In or under water and/or liquid mud, including pumping out water as required. Not for this tender:- 1) Initial levels & final levels have to be taken this shall be basis of payment. 2) Daily work done shall be photographed / videographed & digital record to be maintaine (showing latitute & longitute co-ordinates).	e &	depth			INR Twelve Lakh Thir
		1.00	0 Nos		1231200.00	One Thousand Two
2 00	Add: GST @ 18%	1	# J. 1000/CV			00 INR Eighty Lakh Seve
					8071200.	OU INTO CIGINA DELLA CONT
Total in	n Figures	I IND E	ahty La	kh Seventy	One Thousand	Two Hundred Onl
Quoted	Rate in Words	INK E	girty La			1

General Manager(Civil) Gevra Area

SEEPAT ROAD

P.O.: SECL BILASPUR



साउथईस्टर्नकोलफिल्डस्लिमिटे

South Eastern Coalfields Limited

(कोलइण्डियाकाएकअंश/A subsidiary of Coal India Ltd.) CIN U10102CT1985GO1003161

Website: www.secl-cil.in

कार्यालयः महाप्रबंधक, गेवरा क्षेत्र

OFFICE OF THE GENERAL MANAGER GEVRA AREA

जिला: कोरबा(छत्तीसगढ़) पिन:495452 1500 OF CHARGE O

STD :07815 275430(O)

: 7815 275032(R) :07815 275434

email :gevraenvt@gmail.com

पो0आ0:गेवराप्रोजेक्ट

P.O.: GEVRA PROJECT

Distt.: Korba (C.G.)

Pin: 495452

क्रमांक/एस.ई.सी.एल/मप्र/गे.क्षे./ पर्यावरण/2023 / 375

दिनांक 3/ 11/2023

To The DFO Katghora Range Katghora Korba CG

SUB: Half Yearly Compliance of Diverted Forest land 192.046 Ha., 46.198 Ha., 564.885 Ha. of Gevra Opencast Mine, SECL, September 2023

REF: Forest clearance: F.NO.8-77/2006-FC DT: 20.04.2015,: F.NO.8-79/2006-FC DT: 20.04.2015; F.NO.8-81/2006-FC DT: 20.04.2015.

Dear Sir

Please find enclosed herewith the Half Yearly Compliance of the Diverted Forest land 192.046 Ha., 46.198 Ha., 564.885 Ha. of Gevra Opencast Mine, SECL, September 2023.

Thanking you.

Yours Sincerely

General Manager

SECL Gevra Area

Copy to:

1. Additional Principal Chief Conservator of Forest(Land Management), Raipur

2. Chief Conservator of Forest, Bilaspur

YEARLY COMPLIANCE OF 192.046 Ha. DIVERTED FOREST LAND FOR GEVRA MINING PROJECT OF M/S SOUTH EASTERN COALFIELDS LIMITED (SECL) IN KORBA DISTRICT OF CHHATTISGARH.

भारत सरकार, पर्यावरण एवं वन मंत्रालय, नई दिल्ली का पत्र क्र. / $F.No.\ 8-77\ /2006$ - FC दिनांक 20.04.2015.

	FC दिनांक	20.04.2015.
	MOEF&CC Condition	Compliance
1	Legal status of diverted forest land shall remain unchanged	Agreed.
2	degraded forest land twice in extent to the forest land being diverted shall be reised and maintained by State Forest	Agreed. Funds deposited as per different demand note raised by DFO Katghora of Rs.33664895/ The balance amount @ of Rs. 141105/- per Ha. as raised by DFO Katghora vide demand note no. 3815 dated 19/06/15 is deposited through RTGS vide reference UTR no. SBIN52015092420336167 Dt: 24.09.15 for Rs. 170125543/- which includes amt of Rs. 40606641/- against CA and PCA to make full and final payment as per above demand note.
3	maintained over degraded forest land	Agreed. Funds deposited as per different demand note raised by DFO Katghora of Rs.33664895/ The balance amount @ of Rs. 141105/- per Ha. as raised by DFO Katghora vide demand note no. 3815 dated 19/06/15 is deposited through RTGS vide reference UTR no. SBIN52015092420336167 Dt: 24.09.15 for Rs. 170125543/- which includes amt of Rs. 40606641/- against CA and PCA to make full and final payment as per above demand note.
4	The User Agency either himself or through the State Forest Department shall undertake fencing, protection and afforestation of the safety zone area (7.5 meter stop all along the outer boundary of the mining lease or mining cluster, as applicable, and such other areas as specified in the approved mining plan at the project cost.	has been awarded in favor of CGVVN vide S.No/SECL/BSP/FOREST no. 151 DT: 01.10.16. Work of safety zone along 14 KM has been completed with plantation of 28000 saplings. 2. Safety zone inspection report Enclosed as (ANNEX 1).
5	The following activities shall be undertaken by the User Agency under supervision of the State Fores Department at the project cost. i. Proper mitigative measures to minimize soil erosion and choking of streams shall be prepared and implemented.	nos. of internal dumps. The external dump nos. 1, 2, 3, 4, 5, 6 & 7 is already biologically reclaimed during the year 1987 to 2018. Internal Dump no 1 is biologically reclaimed. The rest Internal

ii. Planting of adequate drought hardy plant species and sowing of seeds to arrest soil erosion.

iii. Construction of check dams, retention / toe walls to arrest sliding down of the excavated material along the contour.

4, 5 & 6 are Biologically reclaimed. Details along with the Soil Conservation Plan is enclosed (ANNEX 2). Check dams & bunds with stone boulders are provided in areas of soil erosion & stream choking

Year	Contour Trench (per trench)	Check Dams (per CUM)	Bunds with stone boulder s (per CUM)
2022	11845	11845	11845
2021	7200	7500	7500
2018	300	20	20

- 2. Year wise Plantation details on Plain areas & Dumps is enclosed. (ANNEX 3) Species planted include Sal, Neem, Karenj, Amla, Siras, Sissoo, Bel, Bamboo, GangaImli, Bahera, Ashok, Golmohar, Satwan, Cassia Gemec, Teak, Jamun, Peltaforum, CassiaGulco, Bogan vallia, Khamar, Sitaphal, Amrood, Kathal, Imli, Mango, Sisham jatropa etc. Dump areas have been provided with Contour trench, check dam and bund with stone bolders.
- 3. A toe wall/ retaining wall & gabion wall have been provided to arrest sliding down of the excavated material along the contour

Structure	Location	Dimension
Retaing wall with Drain	Along P3 Q3 belt near W1 TRS	ht. 1.2mX0.9m RCC Drain
	Along J3 belt	240mX 5m ht. 300mX 2m
	Near Junadih Siding	2050m X 2m ht. 1.2m X 0.9m drain
	External Dump no. 6 & 7	650m X 1m ht. Top width 200mm

			From weigh bridge W5 to LK seam coal face side Along toe of dump no. 4 near E2/E1	1200m length, stage, height 342m, stage, height	3 3m 3 3m
6		3017826 nos. over plain area within done.	an area of 68	9.465 Ha.	in the
7	The User Agency shall pay the additional NPV, if so determined, as per the final decision of Hon'ble Supreme Court of India.	Agreed. NPV has Rs. 176682320/- ha	been paid. A s been deposi	amount for ted.	NPV
8	The period of diversion under this approval shall be coterminous with the mining lease subject to possession of valid lease by User Agency under the MMDR Amendment Act, 2015.				
9	The forest land shall not be used for any purpose other than that specified in the proposal.	Agreed.			
10	No damage shall be caused to the top- soil and the user agency will follow the top soil management plan.		Plan incorp		
11	No labour camp shall be set up inside the forest area.	There is no Labor o	amp inside F	orest Area	
12	The user agency shall provided fuel wood preferably alternate fuel to the labour working at the site to avoid damage / felling of trees.	to facilitate the sup	oply of LPG g at the site to	as connect avoid dar	ion to
13	Any tree felling shall be done only when it is unavoidable under strict supervision of the State Forest Department.	Agreed.			

14	No damage to the flora and funna of the adjoining area shall be caused.	
15	The user agency shall submit the annual self compliance report in respect of the above conditions to the State Government and to the concerned Regional Officer of the Ministry regularly.	
16	Any other condition that the concerned Regional Officer of this Ministry may stipulate from time to time in the interest of conservation, protection and development of forests and wildlife.	
17	The User Agency and the State Government shall ensure compliance to provision of the all Act, Rules, Regulations and Guidelines, for the time being in force, as applicable to the project.	

Grafourely 12023

नोडल ऑफीसर (पर्यावरण/वन) Wodal Officer (ENV/Forest) SECL/Gavra Area एस.ई.सी.एल./गेवरा क्षेत्र

YEARLY COMPLIANCE OF 46.198 Ha. DIVERTED FOREST LAND FOR GEVRA MINING PROJECT OF M/S SOUTH EASTERN COALFIELDS LIMITED (SECL) IN KORBA DISTRICT OF CHHATTISGARH.

भारत सरकार, पर्यावरण एवं वन मंत्रालय, नई दिल्ली का पत्र क्र. / $F.No.\ 8-81\ /2006$ - FC दिनांक 20.04.2015.

	MOEF Condition	Compliance
1	Legal status of diverted forest land shall remain unchanged	Agreed.
2	degraded forest land twice in extent to the forest land being diverted shall be raised and maintained by State Forest	Agreed. Funds deposited as per different demand note raised by DFO Katghora of Rs.8098325/ The balance amount @ of Rs. 141105/- per Ha. as raised by DFO Katghora vide demand note no. 3813 dated 19/06/15 is deposited through RTGS vide reference UTR no. SBIN52015092420336167 Dt: 24.09.15 for Rs. 170125543/- which includes amt of Rs. 9593544/-against CA and PCA to make full and final payment as per above demand note.
3		Agreed. Funds deposited as per different demand note raised by DFO Katghora of Rs.8098325/ The balance amount @ of Rs. 141105/- per Ha. as raised by DFO Katghora vide demand note no. 3813 dated 19/06/15 is deposited through RTGS vide reference UTR no. SBIN52015092420336167 Dt: 24.09.15 for Rs. 170125543/- which includes amt of Rs. 9593544/-against CA and PCA to make full and final payment as per above demand note.
4	The User Agency either himself or through the State Forest Department shall undertake fencing, protection and afforestation of the safety zone area (7.5 meter stop all along the outer boundary of the mining lease or mining cluster, as applicable, and such other areas as specified in the approved mining plan) at the project cost.	has been awarded in favor of CGVVN vide S.No/SECL/BSP/FOREST no. 151 DT: 01.10.16. Work of safety zone along 14 KM has been completed with plantation of 28000 saplings. 2. Safety zone inspection report Enclosed as
5	The following activities shall be undertaken by the User Agency under supervision of the State Forest Department at the project cost. i. Proper mitigative measures to minimize soil erosion and choking of	of internal dumps. The external dump nos. 1, 2, 3, 4, 5, 6 & 7 is already biologically reclaimed during the year 1987 to 2018. Internal Dump no 1 is biologically

streams shall be prepared and implemented.

ii. Planting of adequate drought hardy plant species and sowing of seeds to arrest soil erosion.

iii. Construction of check dams, retention / toe walls to arrest sliding down of the excavated material along the contour.

3, 4, 5, 6, 7 & 8 are running dumps, However part of Dump nos. 2, 3, 4, 5 & 6 are Biologically reclaimed. Details along with the Soil Conservation Plan is enclosed (ANNEX 2). Check dams & bunds with stone boulders are provided in area of soil erosion & stream choking.

Year	Contour Trench (per trench)	Check Dams (per CUM)	Bunds with stone boulders (per CUM)
2022	11845	11845	11845
2021	7200	7500	7500
2018	300	20	20

- 2. Year wise Plantation details on Plain areas & Dumps is enclosed. (ANNEX 3) Species planted include Sal, Neem, Karenj, Amla, Siras, Sissoo, Bel, Bamboo, GangaImli, Bahera, Ashok, Golmohar, Satwan, Cassia Gemec, Teak, Jamun, Peltaforum, CassiaGulco, Bogan vallia, Khamar, Sitaphal, Amrood, Kathal, Imli, Mango, Sisham jatropa etc. Dump areas have been provided with Contour trench, check dam and bund with stone bolders.
- A toe wall/ retaining wall & gabion wall have been provided to arrest sliding down of the excavated material along the contour

Structure	Location	Dimension
Retaing wall with Drain	Along P3 Q3 belt near W1 TRS	182m X 5m ht. 1.2mX0.9m RCC Drain
	Along J3 belt	240mX 5m ht. 300mX 2m
	Near Junadih Siding	2050m X 2m ht. 1.2m X 0.9m drain
	External Dump no. 6 & 7	650m X 1m ht. Top width 200mm

	3			Ē	
		Gabion wall	From weigh bridge W5 to LK seam coal face side Along toe of dump no. 4 near E2/E1	1200m length, 3 stage, 3m height 342m, 3 stage, 3m height	
6	Wherever possible and technically feasible, the User Agency shall undertake by involving local community, the afforestation measures in the blank within the lease area, as well as along the roads outside the lease area diverted under this approval, in consultation with the State Forest Department at the project cost.	3017826 nos. over plain area withi	r an area of 68	89.465 Ha. in the	
7	The User Agency shall pay the additional NPV, if so determined, as per the final decision of Hon'ble Supreme Court of India.				
8	The period of diversion under this approval shall be coterminous with the mining lease subject to possession of valid lease by User Agency under the MMDR Amendment Act, 2015.				
9	The forest land shall not be used for any purpose other than that specified in the proposal.	The second secon			
10		Agreed. No damage is caused to the top soil. Top Soil Management Plan incorporated in Soi Conservation plan is followed.			
11	No labour camp shall be set up inside the forest area.	There is no Labor camp inside Forest Area			
12	preferably alternate fuel to the labourers	A Cooperative Society is set up in Gevra Project to facilitate the supply of LPG gas connection to the people working at the site to avoid damage felling of trees. LPG Connection given till date is 7669.			
13	Any tree felling shall be done only when it is unavoidable under strit supervision of the State Forest Department.				
14	No damage to the flora and funna of the	Agreed.			

	adjoining area shall be caused.	
15	The user agency shall submit the annual self compliance report in respect of the above conditions to the State Government and to the concerned Regional Officer of the Ministry regularly.	Last Submitted Compliance Report vide no.91 Dt. 13.05.2023
16	Any other condition that the concerned Regional Officer of this Ministry may stipulate from time to time in the interest of conservation, protection and development of forests and wildlife.	Agreed.
17	The User Agency and the State Government shall ensure compliance to provision of the all Act, Rules, Regulations and Guidelines, for the time being in force, as applicable to the project.	Agreed.

नोडल ऑफीसर (पर्यावरण /वन) Modal Officer (ENV/Forest) SECL/Gevra Area एस.ई.सी.एल./गेवरा क्षेत्र

YEARLY COMPLIANCE OF 564.885 Ha. DIVERTED FOREST LAND FOR GEVRA MINING PROJECT OF M/S SOUTH EASTERN COALFIELDS LIMITED (SECL) IN KORBA DISTRICT OF CHHATTISGARH.

भारत सरकार, पर्यावरण एवं वन मंत्रालय, नई दिल्ली का पत्र क्र. / F.No. 8-79 /2006 - FC दिनांक 20.04.2015.

	FC दिनांक 20.04 MOEF Condition	Compliance
1	Legal status of diverted forest land shall remain unchanged	
2	forest land being diverted shall be raised and maintained by State Forest Department from the funds deposit by the User Agency.	Agreed. Funds deposited as per different demand note raised by DFO Katghora of Rs.99022877/ The balance amount @ of Rs. 141105/- per Ha. as raised by DFO Katghora vide demand note no. 3811 dated 19/06/15 is deposited through RTGS vide reference UTR no. SBIN52015092420336167 Dt: 24.09.15 for Rs. 170125543/- which includes amt of Rs. 119925358/- against CA and PCA to make full and final payment as per above demand note.
3		demand note wareed has DEO IZ
4	The User Agency either himself or through the State Forest Department shall undertake fencing, protection and afforestation of the safety zone area (7.5 meter stop all along the outer boundary of the mining lease or mining cluster, as applicable, and such other areas as specified in the approved mining plan) at the project cost.	 Safety Zone Fencing afforestation work has been awarded in favor of CGVVN vide S.No/SECL/BSP/FOREST no. 151 DT: 01.10.16. Work of safety zone along 14 KM has been completed with plantation of 28000 saplings. Safety zone inspection report Enclosed as (ANNEX 1).
5	The following activities shall be undertaken by the User Agency under supervision of the State Forest Department at the project cost. i. Proper mitigative measures to minimize	1. There are 7 nos. of external dump & 8 nos. of internal dumps. The external dump nos. 1, 2, 3, 4, 5, 6 & 7 is already biologically reclaimed

soil erosion and choking of streams shall be prepared and implemented.

ii. Planting of adequate drought hardy plant species and sowing of seeds to arrest soil erosion.

iii. Construction of check dams, retention / toe walls to arrest sliding down of the excavated material along the contour.

during the year 1987 to 2018. Internal Dump no 1 is biologically reclaimed. The rest Internal Dump nos. 2, 3, 4, 5, 6, 7 & 8 are running dumps, However part of Dump nos. 2, 3, 4, 5 & 6 are Biologically reclaimed. Details along with the Soil enclosed is Plan Conservation 2). Check dams & (ANNEX bunds with stone boulders are provided in area of soil erosion & stream choking

Year	Contour Trench (per	Check Dams (per	Bunds with stone boulders (per CUM)
2022	trench) 11845	CUM) 11845	11845
2021 2018	7200 300	7500	7500 20

 Year wise Plantation details on Plain areas & Dumps is enclosed. (ANNEX

Species planted include Sal, Neem, Karenj, Amla, Siras, Sissoo, Bel, Bamboo, GangaImli, Bahera, Ashok, Golmohar, Satwan, Cassia Gemec, Teak, Jamun, Peltaforum, CassiaGulco, Bogan vallia, Khamar, Sitaphal, Amrood, Kathal, Imli, Mango, Sisham jatropa etc. Dump areas have been provided with Contour trench, check dam and bund with stone bolders.

3. A toe wall/ retaining wall & gabion wall have been provided to arrest sliding down of the excavated material along the contour

Structure	Location	Dimension	
Retaing wall with Drain	Along P3 Q3 belt near W1 TRS	182m X 5m ht. 1.2mX0.9m RCC Drain	
	Along J3 belt	240mX 5m ht. 300mX 2m	

	The state of the s		Near Junadih Siding	2050m X 2m ht. 1.2m X 0.9m drain
			External Dump no. 6 & 7	650m X 1m ht. Top width 200mm
		Gabion wall	From weigh bridge W5 to LK seam coal face side	1200m length, 3 stage, 3m height
			Along toe of dump no. 4 near E2/ E1 TRS	342m, 3 stage, 3m height
6	Wherever possible and technically feasible, the User Agency shall undertake by involving local community, the afforestation measures in the blank within the lease area, as well as along the roads outside the lease area diverted under this approval, in consultation with the State Forest Department at the project cost.	3017826 nos. over the plain area was been done.	er an area of	689 465 Ha i
7	The User Agency shall pay the additional NPV, if so determined, as per the final decision of Hon'ble Supreme Court of India.	NPV has been p	oaid. Amour been deposit	nt for NPV Reced.
8	The period of diversion under this approval shall be coterminous with the mining lease subject to possession of valid lease by User Agency under the MMDR Amendment Act, 2015.			
9	The forest land shall not be used for any purpose other than that specified in the proposal.	Agreed.		
	No damage shall be caused to the top - soil	Agreed. No dama	ge is caused	to the top soil
10	and the user agency will follow the top soil management plan.	Soil Conservation	plan is follo	wed.

12	The user agency shall provided fuel wood preferably alternate fuel to the labourers working at the site to avoid damage / felling of trees.	A Cooperative Society is set up in Gevra Project to facilitate the supply of LPG gas connection to the people working at the site to avoid damage / felling of trees. LPG Connection given till date is 7669.
13	Any tree felling shall be done only when it is unavoidable under strit supervision of the State Forest Department.	Agreed.
14	No damage to the flora and funna of the adjoining area shall be caused.	
15	The user agency shall submit the annual self compliance report in respect of the above conditions to the State Government and to the concerned Regional Officer of the Ministry regularly.	
16	Any other condition that the concerned Regional Officer of this Ministry may stipulate from time to time in the interest of conservation, protection and development of forests and wildlife.	
17	The User Agency and the State Government shall ensure compliance to provision of the all Act, Rules, Regulations and Guidelines, for the time being in force, as applicable to the project.	

नोडल ऑफीसर (पर्यावरण/वन) Nodal Officer (ENV/Forest) SECL/Gevra Area एस.ई.सी.एल./गेवरा क्षेत्र

संयुक्त निरीक्षण प्रतिवेदन

वन विकास निगम द्वारा वर्षवार पौधों का संयुक्त निरीक्षण/गणना समिति द्वारा दिनांक 23.09.2023 को किया गया। जिसका विवरण निम्नानुसार है :--

Ф.	रोपण वर्ष	रोपण क्षेत्र का नाम	पौधों की संख्या	जीवित पौधों की संख्या	जीवित पौधों का प्रतिशत	रिमार्क
1	2019-20	Near Ganga Nagar	45500	42056	92.43	
		Plain area in between Ext. Dump no. 6 & 7 and laxman	7250	6690	92.28	
		Hardi Bazaar Road	10000	9222	92.22	
2	2020-21	Laxman Project Dump (Mangaon) (Slope & Dump Top)	55950	51726	92.45	
3	2021-22	Dump No. 7 Slope	52500	49424	94.14	
		Non Dump (Shramik Chowk)	5000	4726	94.52	
		Non Dump Add. (Awadh Nagar)	31998	30331	94.79	
	į.	Vertical Greenery System	1500	1421	94.73	
4	2022-23	Dump No. 6 & 7 Back Side (Slope)	82770	79252	95.75	
		Non Dump (Magazine Side)	38200	36366	95.20	
		Bhathora Basahat Patch	5125	4914	95.88	
-		Railway colony Front	5125	4815	93.95	
5	2023-24	Near Shakti Nagar Pond ND	19415	19330	99.56	
		Gevra Non-Dump	19255	19024	98.80	
		Front of Railway Colony ND	3825	3796	99.24	
		Kabristan Back Side Awadhnagar Non-Dump	56705	56195	99.10	
		Magazine Back Side ND	26792	26551	99.10	
		Sal Nursery 10.00. hact.	100000	100000	100.00	

Gevra Range

Environment Officer SECL Gevra Project

Dy. General Manager (Civil)
SECL Gevra Project

Dy. Manager (Survey) SECL Gevra Project

Debark

Gevra Range

Nodal Officer (Envt.) SECL Gevra Area .

SECL Gevra Project



SOIL CONSERVATION PLAN

GEVRA OPEN CAST MINE
SOUTH EASTERN COALFIELDS LIMITED


नोडल ऑफीसर (पर्यावरण/वन) Modal Officer (ENV/Forest) SECL/Gevra Area

एस.ई.सी.एल./गेवरा क्षेत्र

INTRODUCTION

Location & Accessibility

The Gevra OCM is an existing mega opencast project of South Eastern Coalfields Limited (SECL) with present EC capacity of 52.50 MTPA. The Block is located in the South Central Part of Korba Coalfield in Korba District of Chhattisgarh. The Gevra Mining block having an area of 20.37Sq.Km is bounded by latitudes 22°18'00" to 22°21'42" N and longitudes 82°32'00" to 82°39'30" E. It is included in the survey of India Toposheet No. 64 J/ 11. The location map of the area is as shown.



The block is well connected by rail and road. Gevra Road and Korba Railway Station on Champa-Gevra Road branch line of S.E. Railway are at a distance of 10 km and 16 km respectively. Railway siding has been extended up to and beyond Gevra OCP and coal is being transported from the pit head CHP through rail/MGR to the various consumers. SECL HQ Bilaspur is at a distance of about 90 km by road.

The existing capacity of the project is 52.50 MTY. Mining of Coal from Gevra OCP is done by Open Cast method. It is characterized by the presence of four open castable seams (Composite seam D, E&F Seam, UK Seam, LK Seam) with dip angles of 2°-6°. Seam thickness ranges from 1.10 m to 45.23m. The thickest seam is Lower Kusmunda (19.28m to 45.23 m). The Maximum width along strike is 9.1 KM and Maximum length along dip is 3.29KM. The present maximum depth of the quarry is 203 m. The mineable reserve is 265.73 MT (as on 01.04.2023) with an average stripping ratio of 1.30. The total quarry has been divided into three sections i.e Western Section, Central Section & Eastern Section. It is proposed to mine all the three identified sections simultaneously. However mining operations will be staggered between the sections.

The total Mine Lease area of the project is 4184.486 Ha. The total Forest Land involved is 1016.412 Ha out of which 904.027 Ha. has already been diverted for nonforest purpose after receiving the Stage II Forest Clearance. The remaining 112.385 Ha. of Revenues Forest land has obtained Final/Stage II approval vide MoEF&CC Clearance L.No. 8-

41/2017-FC dated 21.06.2022 (Handing over awaited from State Forest Department). The project is proposed for capacity enhancement to 70 MTPA with Mine lease area of 4781.798 Ha. Therefore diversion of Additional 94.293 ha. of Revenue Forest Land is involved in this proposed expansion.

Physiography & Drainage

The general topography of the block is gently undulating. The surface contour ranges from 288-328 m above MSL. The general slope of the terrain is towards East. Water from the mine and nearby area flows into the seasonal nalla namely Laxman Nala located on the northern side. Ahiran River located towards NE. In addition there are quite a few ponds. Ahiran and Hasdeo River control the drainage of the area and are situated towards N-E and East respectively of the area under consideration.

The climate of the area is dry to moist tropical with well-defined summer from April to June, rainy season from July to September and winter from November to February. The temperature rises to a maximum of 48°Cin May and drops to a minimum of 7°C in December. The annual rainfall for 2022 is 1433 mm.

MINE WATER ENVIRONMENT

Surface Water Resources

Hasdeo River, a major tributary of Mahanadi River flowing along the eastern side in North –South Direction is the master drainage of the area. The mine block is drained by Laxman nallah flowing in West- East direction and joins Ahiran Nadi, a tributary of Hasdeo river at about 4.5 KM in NE from the mine. Kholar stream which is also a tributary of Hasdeo River controls the drainage in the northern part whereas Lilager Nadi and Gangadel nallah controls the SW and SE respectively. These streams are mostly perennial and behave as constant recharge sources. The pattern of the drainage in the area is mostly dendritic in nature.


Ground Water Resources

The formations within the study area are Barakars, Talchirs and Metamorphics. Major portion of the study area is occupied by Gondwanas. Talchirs and metamorphics occupy the rest. The Project area is situated in Barakars formation

comprising sandstone of different grain sizes with shale beds and coal seams. This permeable sandstone is saturated and behaves as aquifers. Shale and coal seams act as aquicludes. Stratification and the presence of aquicludes lead the aquifer system into multi aquifer system.

The formation comprising mainly of alluvium and sandstone (average thickness 50.0 m), lying above the working seam E&F behave as unconfined aquifer. Whereas, lower formations consisting of compact sandstone mainly with secondary porosity behave as semi-confined/confined aquifer.

In the unconfined aquifer ground water moves laterally through the inter granular pore spaces in the sandstone. Whereas, in lower aquifers the groundwater movement is restricted mainly through joints and fractures (i.e. secondary porosity). With intercalation of shales and carbonaceous shale beds and reduction in permeability with depths in the lower aquifers are very poor in potential. A flat water table with a gradient of 1.8×10^{-2} , slopping towards east, was observed in the area.



Plan showing hydrological features of the area

A. PREPARATION AND IMPLEMENTATION OF A PLAN CONTAINING APPROPRIATE MITIGATIVE MEASURES TO MINIMIZE SOIL EROSION AND CHOKING OF STREAMS


Soil conservation in its widest sense includes not only control over erosion but all those measures like correction of soil defects, application of manures and fertilizers, proper crop rotations, irrigation, drainage etc. which aim at maintaining the productivity of the soil at a high level. In this sense, soil conservation is closely allied to improvement of land use in general.

In OC mines, the earth material is dug out to extract coal. The excavated over burden material consists of alluvial, top soil, sub soil and rocks. The OB is placed in the nearby areas in the form of dumps. If no measures are taken for the management of OB dumps, after precipitation, water will take away the soil particles along with itself thereby causing soil erosion. This eroded soil will flow into the nearby streams, rivers, water channels and cause choking/contamination of the water bodies. In order to prevent this, an effective soil erosion management plan needs to be prepared and implemented.

MITIGATIVE MEASURES TO MINIMIZE SOIL EROSION AND CHOKING OF STREAMS

In order to control soil erosion, a step by step procedure needs to be adopted so that the water flows through a proper path and does not take away with it the essential soil material. The steps to be followed are:

1. Garland Drains: To arrest the surface runoff into the quarry, garland drains with suitable dimension (4 m x 1.5m) to carry the peak discharge are constructed.



B. PLANTING OF ADEQUATE DROUGHT HARDY PLANT SPECIES AND SOWING OF SEEDS IN THE APPROPRIATE AREA WITHIN THE MINING LEASE TO ARREST SOIL EROSION

In view of importance of vegetation cover towards environment, the technical reclamation will be strengthened by biological reclamation for conserving the environment.

Plantation Technique on Overburden Dumps

To improve the environment and greenery in the area, SECL had taken up plantation on a larger scale. The improvement in vegetation cover has a direct bearing on augmentation of ground water recharge. The compensatory afforestation has been carried out through the State Forest Departments. In addition to compensatory afforestation, to improve the greenery and dust control, the project did heavy plantation both on reclaimed and at various other locations

in the project area. This greenery not only controls air pollution but also controls the soil erosion and increase groundwater recharge.

The top surface of the overburden dumps selected for plantation will be roughly levelled by dozer keeping a mild slope of about 1 in 200 for surface water drainage.

Seeds of grass legumes will be sown on beds of 1.5m x 0.5 m, alternating with slopes to be planted with tree species. Gully plugging and constructing check dams on water courses flowing through OB dumps with boulders, will also be made to arrest soil erosion.

In SECL Plantations are carried out by CGRVVN (Chhattisgarh Rajya Van Vikas Nigam Limited). Long term MoU has been signed between SECL and CGRVVN Ltd. Raipur for five consecutive years plantation works with subsequent maintenance of four years in SECL command area in Chhattisgarh State.

Various species suggested for plantation are:

- Fruit bearing (15%) & Medicinal / Herbal (35%): Jamun, Imli, Ganga Imli, Bel, Mango, Neem, Bahera, Amla, Mahua, Kusum, Arjuna etc.
- Timber/ forest (48%): Teak, Shisham, Siris, Bamboo, Babool, Ghamhar, Pipal etc.
- Ornamental / avenue (2%): Gulmohar, Kachnar, Gravelia, Ashok, August etc.
- Grass Species: StyloHemata, Dinanath on slope of OBD

TOP SOIL MANAGEMENT PLAN

Introduction

The topsoil at Gevra OC Expansion (35.0-70.0Mty) comprises of rich humus with minerals and nutrients. Proper handling and management is necessary for future vegetation growth in the mine reclaimed area. The thickness of the top soil varies between 25 cm to 35 cm.

Objectives of the Soil Stripping management plan The objectives of Top Soil Management are to:

- Maintain a topsoil balance that achieves rehabilitation objectives during the life of Mine.
- Ensure effective topsoil removal techniques are employed to maximize volumes of suitable topsoil removed and minimize wastage.

 Maintain topsoil viability during stripping, spreading, and stockpiling, through best practice technique and effective stockpile design and treatment.

In accordance with the objective of providing sufficient stable soil material for rehabilitation and to optimize soil recovery, the following strategies will be adopted during the mining operation at Gevra opencast mines.

Prior to the commencement of stripping, areas will be cleared of vegetation. Soil stripping will be undertaken by dozers and hydraulic backhoe excavators to maximize the preservation of the quality of the soil. The HEMM operators and supervisors should be trained and made aware for the same. This will ensure that all suitable topdressing material resources are salvaged and that the quality of the stripped top dressing material is not reduced through contamination with unsuitable soils. Care will be taken during stripping, stockpiling, and re-spreading to ensure that structural degradation of the soil is avoided and that excessive compaction does not occur during stockpiling.

Stock piling

 Where possible, top dressing material will be re-spread directly from stripped areas onto areas being rehabilitated. Where this is not possible, topdressing material will be stored in stockpiles.

Stock piles will be dumped at places where they would not be disturbed by future mining. Sediment fences or other barriers can be used where necessary to retain

sediment.

The overall topography for the graded surface should be designed to minimize the uncontrolled flow of runoff.

Dispersed sheet flow should be broken up by terraces or benches along the slope

that also follow topographic contours.

On a fine scale the ground surface can be roughened by the tracks of a bulldozer perpendicular to the slope. Construction of stockpiles with a "rough" surface condition will reduce erosion hazard, improve drainage and promote re-vegetation.

Stockpile preservation

Stockpiling topsoil may result in disruption & loss of beneficial soil microorganisms and nutritional values, hence needs the following amendments during preservation:-

1) Re-vegetation of the stockpile will be done as scheduled below to protect the soil from erosion, discourage weeds and maintain active populations of beneficial soil microbes.

Temporary Seeding- To protect topsoil stockpiles by temporarily seeding as soon as

possible, within 30 days after the formation of the stockpile.

 Permanent Vegetation- If stockpiles will not be used within 12 months they will be stabilized with permanent vegetation to control erosion and weeds. Likely grass species for re-vegetating top soil stock piles are green panic, Japanese millet (spring sowing), Oats (winter sowing), Dryland Lucerne, Seaton park sub-clover.

Topsoil can be mixed with organic material or manufactured soil amendments to improve

the growing capability.

2) To the extent practicable, above ground vegetation, including tree litter should be mixed or otherwise incorporated into the topsoil.

3) Soil amendments: Soil amendments should be applied before seeding or planting. Common soil amendments used are bio-solids, compost, manure, lime and coal

combustion byproducts.

Prior to the placement, the top 0.30cm of the stock pile material should be mixed with the remainder of stockpile to ensure that living organisms are distributed throughout the top soil material at the time of final placement. In case, the material has been stockpiled for over nine months period, used of micro organisms inoculates may be necessary to reestablish microorganisms in the top soil material. The quantity should be 200ml for one Ha. area in case of Azatobactor and Rhizobium.

Site Preparation

· Before spreading topsoil, establish erosion and sedimentation control structures such as diversions, berms, dikes, waterways and sediment basins.

Adjust grades and elevations for receipt of topsoil.

Roughening - Immediately prior to spreading the topsoil, loosen the sub-grade to ensure bonding of the topsoil and subsoil.

Soil horizons will be replaced in the same order that they were removed.

Top soil will be uniformly distributed to pre-mining thickness. Topsoil will not be

spread while it is frozen or muddy.

The topsoil will be compacted to ensure good contact with the underlying soil, but excessive compaction will be avoided, as it increases runoff and inhibits seed germination. Light compaction with roller will be done where turf is to be established.


On slopes and areas that will not be mowed, the surface will be left rough after spreading topsoil.

Monitoring

Specific team / manpower is to be deployed for this most important step of topsoil management. The team will monitor the area and quantum of top soil management with the authorities of mine on quarterly basis and regularly monitor the given points of significant importance:


- Monitoring Erosion Control: This step is necessary during stock piling as well as reclamation stage of topsoil management. Take corrective measure in areas showing evidence of erosion, sedimentation or slope failure. This is a serious problem, because erosion causes fertile farmland to lose nutrients and water retention ability
- Regular monitoring of top soil management should be done until vegetation is demonstrated to be successfully established.
- Reseeding: Take appropriate measures to address evidence of invasive species or poorly established vegetation. Reseeding should be done, if germination is not uniform or poor.

YEARWISE PLANTATION AT GEVRA AREA



AVENUE PLANTATION


- C. CONSTRUCTION OF CHECK DAMS, RETENTION/TOE WALLS ALONG THE CONTOUR TO ARREST SLIDING DOWN OF THE EXCAVATEDMATERIAL
 - 1. Catch Drain: 2.8 KM of pucca catch drains of dimension 1.5 X 1.5 m were constructed for chanelling of surface runoff during Rainy Period.
 - Check Dams & Retaining Wall: To prevent soil Erosion & arrest sliding down of excavated material along the contour. Regular maintenance is carried out to prevent siltation.



 2018-19 Plantation dump area have been provided with Contour trench 300 per trench, check dam 20 per cubic meter and bund with stone bolders 20 per cubic meter.







A toe wall is constructed at External Dump no. 6 & 7 of dimensions: Length 650 meters, height above ground 1.00 meters and top width of wall 200 mm in the year 2018-19

Year	Contour Trench (per trench)	Check Dams (per CUM)	Bunds with stone boulders (per CUM)
2022	11845	11845	11845
2021	7200	7500	7500
2018	300	20	20

Location	Dimension
Along P3 Q3 belt near W1 TRS	
Along J3 belt	240mX 5m ht. 300mX 2m
Near Junadih Siding	2050m X 2m ht. 1.2m X 0.9m drain
External Dump no. 6 & 7	650m X 1m ht. Top width 200mm
From weigh bridge W5 to LK seam coal face side	1200m length, 3 stage, 3m height
Along toe of dump no. 4 near E2/ E1 TRS	342m, 3 stage, 3m height
	Along P3 Q3 belt near W1 TRS Along J3 belt Near Junadih Siding External Dump no. 6 & 7 From weigh bridge W5 to LK seam coal face side Along toe of dump no.

STABILIZE THE OVERBURDEN DUMPS BY APPROPRIATE GRADING/BENCHING SO AS TO ENSURE THAT THAT ANGLES OF REPOSE AT ANY GIVEN PLACE IS LESS THAN 28°

PROGRAMME OF O.B. REMOVAL, DUMPING & PLANTATION:

	Coal	ОВ	Dump (Mc		Dump area a reclamati	ivailable for ion (Ha.)		lantation Nos / Ha.	Total plantation @ 2500 Nos / Ha.
ear	production (MTes)	removal (Mcum)	External	Internal	External	Internal	External	Internal	
	40	72.69	0	72.69	0	0	0	0	0
1			0	72.67	0	0	0	0	0
2	41	72.67		73.8	0	0	0	0	0
3	41	73.8	0		32	0	0	0	0
4	45	82.12	0	82.12	0			0	0
5	49	86.92	0	86.92	0	0	0		147825
6	61	108.62	0	108.62	0	59.13	0	147825	
		125.06	0	125.06	0	59.13	0	147825	147825
7	70		0	125.53	0	59.13	0	147825	147825
8	70	125.53		Alexander Color	0	59.12	0	147800	147800
9	70	125.51	0	125.51		59.12	0	147800	147800
10	70	125.17	0	125.17	0	7845764		158400	158400
11	70	125.09	0	125.09	0	63.36	0		- Description
12	70	125.51	0	125.51	0	63.36	0	158400	158400
	70	125.54	0	125.54	0	63.36	0	158400	158400
13			0	124.82	0	63.36	0	158400	158400
14	70	124.82		COVARIE OF A SEC	0	63.36	0	158400	158400
15	70	124.95	0	124.95	- 1		0	158400	158400
16	70	107.8	0	107.8	0	63.36			158400
17	70	107.66	0	107.66	0	63.36	0	158400	40000 ACCAS
	70	86.34	0	86.34	0	63.36	0	158400	158400
18		84.96	0	84.96	0	63.36	0	158400	158400
19			0000	85.18	0	63.36	0	158400	158400
20	70	85.18	0			63.36	0	158400	158400
21	50	40.8	0	40.8	0		0	158400	
22	30.68	29.89	0	29.89		63.36			
MC		0	0	0	0	77.3	0	193250	
MC	1	0	0	0	0	77.3	0	193250	
	*	0	0	0	0	77.3	0	193250	193250
MC				2166.6		1287.8	5 0	321962	5 3219625
Tot	tal 1337.68	2166.6	0	2166.6	0	1237.00	100 J		

The spoil dump benches in the internally backfilled OB will be in the form of benches. With the sufficient advance of coal production bench, the non-active backfilled OB will be leveled with dozer. Dumper/Tipper will transport soil/alluvium OB from the top OB bench and will dump the soil directly on the leveled backfilled OB. Otherwise; top soil will be removed and stored separately. This soil will be directly spread over the levelled graded backfilled spoil for reclamation of the quarried out land. OB dumps will be properly benched and the maximum height of the bench will be kept not more than 30m. Dump benches will have a mild gradient of 0.6% to facilitate the drainage. Wherever possible, simultaneous land reclamation will be done along with the OB dumping.

The following design criteria have been considered for waste dumps.

- OB in external dumps will be stacked in 30 m high benches.
- (ii) OB in internal dumps will also be stacked in 30 m high benches.
- (iii) Dozers to be deployed for shaping the dumps overall slope is 28°.
- (iv) Final reclamation will be achieved using the equipment provided for the purpose.

Once, the external dumping is completed, the spoil will be graded and landscaped in harmony with surrounding topography and biological reclamation carried out. Alternatively, the final void at the end of mining operations in the mine can be converted into a water reservoir.

RECLAMATION SCHEDULE

E. STRICT ADHERENCE TO THE PRESCRIBED TOP SOIL MANAGEMENT

Systematic handling of topsoil

Topsoil shall be removed before any drilling, blasting, mining, or other surface disturbance. The stock piling of top soil will be as follows:

 Top soil and other materials removed shall be stock piled only when it is impractical to promptly redistribute such materials on regarded areas. • Stock-piled materials shall be selectively placed on a stable area, not distributed, and protected from wind and water erosion, unnecessary compaction, and contaminants which lessen the capability of the materials to support vegetation when redistributed.


Top soil redistribution

After the final grading the top soil would be redistributed in a manner that achieves an approximate uniform stable thickness consistent with the post mining land uses, contours, and surface water drainage system.

Biological reclamation

In view of importance of vegetation cover towards environment, the technical





reclamation will be strengthened by biological reclamation for conserving the environment.

FINANCIAL PROVISIONS

I. Financial provision for soil erosion management

A . Livitar	Amount (in Rs. Lakhs)
100 Maria	30.00
Garland Drains	5.67
Arboriculture/plantation in industrial area	
Barbed fencing/boundary walls/Toe walls/Gabion structures	19.37
	42.50
Land Reclamation / Restoration	10.00
Green Belt in and around the Mine Total	107.54
	Activity Garland Drains Arboriculture/plantation in industrial area Barbed fencing/boundary walls/Toe walls/Gabion structures for the project Land Reclamation / Restoration Green Belt in and around the Mine

^{*} Subsequent additional provision will be made as and when required.

Existing Mine Closure Cost as per approved MCP

As per the guidelines of the MoC, the cost of the mine closure cost was computed based on project area of Gevra OCP i.e, 4184.486Ha. Considering the wholesale price index as 136.30, as on April 2010, the updated cost of the mine closure is estimated to be Rs. 6.312 lakhs per hectare (considering three decimal places) considering the admissible escalation over Rs. 6.00 lakh per Ha as on August 2009 when wholesale price index was 129.60.

Total Final mine closure cost (@ Rs.6.312 Lakh/Ha.): Rs.26412.48lakhs

Table-1: Existing Fund deposit & Reimbursement Schedule

Year	Fund Deposited in Escrow Fund	Fund to be Re (Maximum)	eimbursed
1	1100.52	Nil	
2	1155.55	Nil	-
3	1213.32	Nil	-
4	1273.99	Nil	313
5	1337.69	Nil	
1st phase	6081.07	4864.85	
6	1404.57	Nil	
7	1474.80	Nil	-
8	1548.54	Nil	+ .
9	1625.97	Nil	(+) accrued
10	1707.27	Nil	interest as applicable
2nd phase	7761.15	6208.92	applicable
11	1792.63	Nil	
12	1882.26	Nil	
13	1976.38	Nil	-
14	2075.19	Nil	
15	2178.95	Nil	-
3rd phase	9905.42	7924.33	1
16	2287.90	Nil	
17	2402.30	Nil	

18	2522.41	Nil
19	2648.53	Nil
20	2780.96	Nil
4th Phase	12642.10	10113.68
21	2920.01	Nil
22	3066.01	Nil
23	3219.31	Nil
24	3380.27	Nil
inal phase	12585.60	19863.54
Total	48975.34	48975.34

REVISED MINE CLOSURE PLAN(PHASE 1& 2)-

The Mine closure plan for Gevra OC 70 Mty was part of the Project report & is deemed approved along with the Project report. All MCP activities for this Mining plan will be as per mentioned in the PR.

A-REVISED ABONDONED COST & FINANCIAL ASSURANCE (As per the new Guidelines & Latest WPI)

TABLE-2: Progressive & Final cost distribution table in an OC mine as per New Mine Closure Guidelines issued by MoC on 16/12/2019

S. No.	Activity	Progressive	Final
A	Dismantling of Structure		
	Service building	0	8.50
	Residential Building		
	Industrial Structure		
В	Safety & Security		1
	Random rubble masonry/concrete wall	6.50	3.20
	Toe wall around dump/Gabion wall	0.50	0.20
	Barbered wire fencing	_	
	Fencing/boundary wall, fencing around water		

S. No.	Activity	Progressive	Final
-	body		
•	Garland drains	1	
C	OB Dump Reclamation		
I	Technical Reclamation	+	
	Re-handling of OB	-	
	Levelling by Dozer	-	
	Grading	60.50	60.50
	Levelling and grading of high wall slopes & OB Dump		
II	Biological Reclamation & Plantation		
	Top soil Management		
	Grassing of OB dump	1	
	Plantation around virgin Area, safety zone, green belt, over external Dump and internal reclaimed area	15.00	11.70
	Plantation post care (including manpower)	1	
	Plantation over cleared area obtained after dismantling		
D	Landscaping of the open space in leasehold area for improving its aesthetic. Drain, Pipe lines, Peripheral road, gates, View points, cemented steps on bank	4.00	5.50
	Development of Agriculture land		
Е	Environment mitigation & management		
	Air Quality (Water tanker, Sprinkler & other Control measures)	12.00	1.50
	Water Quality (ETP & STP etc operating cost)		
	Manpower Cost and supervision		
F	Post Closure Monitoring	0.00	3.20

S. No.	Activity	Progressive	Final
	Air Quality		
	Water Quality		
	Power Cost		
*	Manpower Cost and supervision		
G	Entrepreneurship Development (Vocational/skill development training for sustainable income of affected people)	1.00	0.50
Н	Miscellaneous & Other measures like Golden Handshake, one time financial grant, alternative jobs, other services etc.	1.00	5.40
	Total	100.00	100.0

22.3 Financial Assurance

A- Financial Assurance

Revised Mine Closure Cost based on latest WPI and adjustment of amount already deposited in the escrow account, as per the direction of CCO office

The amount that has to be deposited in Escrow account acts as a security against the mine activities to be carried out for the closure of the mine is based on the project area.

As per para 2.6 (Escrow Account Calculation) of MOC guideline no. F. No. 34011/28/2019-CPAM, Ministry of Coal dt 16th December 2019 & 29th May 2020, in case of the mine where escrow account is already open, the annual closure cost is to be computed considering the total project area at the above mentioned rates minus the amount already deposited and dividing the same by the balance life of the mine in years and annual cost as arrived should be compounded @5% annually.

The total Land Area envisaged in the project (Phase I & 2) is 4781.798 Ha

As per the latest guidelines of MOC, the amount to be deposited in Escrow account is evaluated as per detailed below:

TABLE-3: EVALUATION OF REVISED MINE CLOSURE AMOUNT- PHASE I

A	BASE RATE/HA IN LAKH RS AS ON 1st APR 2019	9
В	WPI AS ON 01.04.2019	121.1
C	MCP LAND IN HA	4781.798
D	WPI AS ON MAR 2022*	148.9
E	ESCALATION FACTOR (D/B)	1.229562
F	RATE/HA IN LAKH Rs (E * A)	11.066
G	CORPUS IN LAKH Rs (F * C)	52915.669
Н	Balance life in years as on 01.04.2022	16
I	Amount Deposited till 31.03.2022-lakh Rs	17517.11
J	Final corpus amount in lakh Rs (G-I)	35398.559
K	First Year amount in lakh Rs(J/H)	2212.4099
L	Total amount to be deposited in balance years in Lakh Rs.	52340.070
	☐ WPI of Apr 2022 & May 2022 are provisional	

Table-4: Fund deposit & Reimbursement Schedule from 2022 onwards

Year	Year No	Fund Schedule in Lakh Rs	Fund to be Reimbursed (Maximum) in lakh Rs
EXISTIN	G MCP DEPO	OSIT SCHEDULE	UPTO 2021-22
2020-21		1792.630	
2021-22		1882.260	
REVISE	D MCP DEPO	SIT SCHEDULE V	V.E.F 2022-23
2022-23	1	2212.410	
2023-24	2	2323.030	
-020 21			

Progressive	Phase-1	6974.622	50% of balance amount at the end of Phase-1
2025-26	4	2561.141	
2026-27	5	2689.198	
2027-28	6	2823.658	
2028-29	7	2964.841	
2029-30	8	3113.083	
Progressive	Phase-II	14151.921	
2030-31	9	3268.737	
2031-32	10	3432.174	
2032-33	11	3603.783	
2033-34	12	3783.972	
2034-35	13	3973.170	
Progressive	Phase-III	18061.836	
2035-36	14	4171.829	
2036-37	15	4380.420	
2037-38	16	4599.441	
MC1	17		
MC2	18		
MC3	19		
Final Phase		13152	100% of balance
GRAND TOTAL		52340	amount at the end of final Phase

Table-5: COST ESTIMATE FOR PROFRESSIVE & FINAL CLOSURE ACTIVITIES

COST OF ACTIVITIES TO BE TAKEN UP FOR PROGRESSIVE CLOSURE OF MINE

Head	PARAMETERS	Unit	Amoun "Rs. Cr	
	Water quality management	LS	9.06	
	Air quality management	LS	16.31	
	*Waste Management	LS	7.25	
	Barbed wire fencing	LS	1.96	
	Barbed wire fencing around the Pit	LS	1.96	
	Filling of Void - Rehandling of Crown Dump	LS	18.27	
_	Top Soil management	LS	22.65	
Progressive closure	Technical l Reclamation of Mined out of land and OB Dump	LS	155.31	
	Biological Reclamation of Mined out of land and OB Dump, Plantation over virgin area including green belt	LS	20.39	
	Manpower Cost and supervision	LS	18.20	
	Toe Wall around the dump	LS	2.94	
	Garland drain	LS	3.62	
	Garland Drain around the dump	LS	2.42	
	Any other Activity	LS	3.02	
	Dismantling of workshop	LS		
Dismantaling of Infrastructure & Disposal/ rehabilitation of Mining machinery	Rehabilitation of the dismantled Facilities	LS		
	Dismantling of pumps and Pipes/ other facilities	LS	18.82	
	Dismantling of stowing bunker, provisioning of pumps for bore well pumping arrangement	LS		
	Dismantling of UG equipment	LS		

	Rearranging water pipeline to dump top park/ Agricultural land	LS	
[7	Dismantling of Power lines	LS	1.00
	Barbed wire fencing	LS	1.96
-	Barbed wire fencing around the Pit	LS	1.06
	Barbed wire fencing with masonry pillars	LS	0.35
	Concrete wall with Masonry pillars around the pit	LS	
	Securing air shaft and installation of bore well pump	LS	
	Securing of Incline	LS	
Safety and ecurity	Concrete wall fencing around the water body		
· ·	Boundary wall around the water body	LS	8.72
	Stabilisation! viz benching, pitching etc) of side walls of the water body		3
	Toe Wall around the dump	LS	3.38
	Garland drain	LS	4.87
	Garland Drain around the dump		
	MISC SAFETY WORKS	LS	2.40
	Drainage Channel from main Ob dump	LS	4.85
	Filling of Void	LS	66.97
	Top Soil management	LS	10.36
Technical and	OB Rehandling for backfilling	LS	66.97
Biological Reclamation of	Terracing, blanketing with soil and vegetation of External OB Dump	LS	7.77
Mined out of land and OB Dump	Peripheral road, gates, view point, cemented steps on bank	LS	4.24
	Expenditure on development of Agricultural land	LS	1.22
	Landscaping and Plantation	LS	9.60
	Power Cost	LS	1.04
Post Closure management and	- i was a liter management	LS	2.08

supervision	Post Mining Air quality management	LS	4.16		
	Subsidence monitoring for 5 years	LS	0.00		
	Waste Management	LS	2.08		
	Manpower Cost and supervision	LS	1.04		
	Entrepreneurship development (vocational/skill development training for sustainable income of affected people	LS	4.13		
	Golden Handshake / Retrenchment benefits to 100 employees of OC	LS			
Others	Golden Handshake / Retrenchment benefits to 200 employees of UG	LS	11.96		
	Onetime financial grant to societies / institutions /organisations which is dependent upon the project;	LS			
	Provide jobs in other mines of the company	LS			
	Continuation of other services like running of schools etc.	LS	,		
Total	*******		523.40		
Total			32.71		
Fotal	PROGRESSIVE COST FOR THE ENTIRE LIFE	302.01			
Total	ANNUAL PROGRESSIVE COST				

TIME SCHEDULE

The time scheduling is being provided on the basis of time interval of five year as required in the MoC guidelines. This period of 5 years is considered as one phase of five years and reclamation of one phase must be taken up before commencement of mining activity in the subsequent phase. The action plan for progressive closure activities has been provided in the Figure below:


Sl. No.	Activities	Time Frame							
1.	Preparation of Survey & Disposal Report	One month							
2.	1 2 414 11 1								
3.	Disposal of P&M including HEMM, CHP, W/S, Siding	2 and half years							
4.	Backfilling of mined out Area (OC)	2 years							
5.	Dismantling of Industrial structure	2 years							
6.	Grading & dozing of high walls for OC	2 years							
7.	Fencing of quarry	2 years							
8.	Clearing of Coal Stock and Infrastructural Area.	2 years							
9.	Disposal / Dismantling of Residential colony	2 &1/2 years							

REIMBURSEMENT OF EXPENDITURE INCURRED ON PROGRESSIVE MINE CLOSURE ACTIVITIES OF GEVRA OCP

The Progressive Mine Closure Plan for Gevra OCP has been approved in the 218th meeting of SECL Board held on 28.11.2013.Accordingly, Escrow Account No: 423803800000294 is opened in Union Bank of India, Bilaspur and Annual Deposits as per the approved MCP have been made in the above account regularly since 2010-11 and the balance amount as on 31.03.2023 is Rs.1346459196/-only in the said account. As per the clause No: 6 of MoC guidelines dated 07.01.2013 and provisions of approved MCP, the reimbursement of expenditure on Mine closure activities has been received in respect

of Gevra OCP for the activities undertaken from 2010-11 to 2014-15. A total amount of Rs. 514721000/- was recommended for release by Coal Controller on 17.08.2017.

For the period from 2015-16 to 2019-20, an amount of Rs. 577323000/-has been reimbursed under Progressive Mine Closure.



	F	PLANTAT	ION DONE	ON		100000000000000000000000000000000000000			
YEAR	On Plain area (nos)	On intern al dumps (nos)	On External dumps (nos)	Total Plantation on dumps (nos).	Total Plantation done (in nos)	CPT (1.5mx0 .9mx0.7 5m) (in Rmtrs)	GRAS S BED (Nos.)	Area/ Ha.	Location
1	2	3	4	5=(3+4)	6=(2+3+4)	7	8	9	
1986	236000	0	0	0	236000	0	0	74.3	MGR Loc Roadsid Inside color Gevr Kusmunda Road Distrbuted to employees
1987	245750	0	46000	46000	291750	0	0	82.93	1. Ext. OB Dum No. 1 near MG 2. Aroun Magazine 3. Colony Roa 4. Inside colony
1988	419500	0	0	0	419500	0	0	93.22	1. Near E&N workshop & D GM Offic 2. Near CH 3. Road side a Gevra 4. Road side a VTC/CETI 5. Gevra Kusmunda Roa 6. Barcli villag 7. Near Magazin 8. Colony
1989	454000	0	0	0	454000	0	0	100.8	1. Gevra Kusmunda Roa 2. Near Bare Village 3. Near CET 4. Gevra Colon 5. Near CH Bunker 6. SILO Roa 7. Vacant spacin colon 8. Near Magazin
1990	372883	0	0	0	372883		0	82.86	1. Nea Magazine, Ganganagar 2. Laripara plo 3. Old Dipk. Barrier (Plante by Dipka unit 4. Vijaynaga village 5. Near Conveyo Belt - Clif 6. Near Hospita 7. Roadsid 6. Barrier (Plante by Dipka projec at Dipka unit 9. Boathside old Barrier (Plante by Dipka projec at Dipka unit 10. Conveyor Bel Latipara 11. Mine boundri 11. Mine boundri near Barel 12. Inside Colony
1991	360000	0	0	0	360000	0	0	80	1. Bareli Bhati Village (A 2. Bareli Bhati Village (B 3. Helipade side

									4. D Type quarters 5. Nehru nagar (Planted by Dipka project at Dipka unit) 6. CEWS 7. Guest Houses 8. CETI 9. Dipka - Pali Road (Planted by Dipka project) 10. Kusmunda - Gevra Road
1992	64900	0	0	0	64900	0	0	14.42	1. Gevra Township 2. Railway Sising 3. Gevra Mine 4. Near Bareli Pondi Bhata Village
1993	87230	0	26970	26970	114200	0	0	27	1. Shakti Nagar Colony 2. Dipka project colony (Planted by Dipka project at Diopka unit 3. Dipka Ext. Dump no. 1 (Planted by Dipka project at Dipka unit) 4. NCH Colony 5. CEWS 6. Dipka MTK office (Planted by Dipka project at Dipka unit) 7. Gevra Ext. Dump no. 2 8. Gevra Railway siding 9. Kusmund Barrier Pond etc.
1994	0	0	0	0	0	0	0	0	Darrier rond co.
1995	77000	0	0	0	77000	0	0	17.11	Gevra Kusmunda Road Infront of Old GCM Office
1996	68000	0	64000	64000	132000	0	0	29.33	1. Dipka Dump no. 3 (Planted by Dipka project at Dipka unit) 2. Beltikri Dump (Planted by Dipka project at Dipka unit) 3. CGM Office 4. Boundry wall at Dipka (Planted by Dipka project at Dipka unit) 5. Dipka Border line (Planted by Dipka project at Dipka unit) 6. Dipka unit) 6. Magazine side
1997	50000	17500	105500	123000	173000	0	0	38.44	1. Dump no. 3 (Planted by Dipka project at Dipka unit) 2. Near Magazine 3. External Dump no. 2,3 & 4 4. External Dump no. 5 5. Internal no.1
1998	42000	52150	31850	84000	126000	0	15000	31.5	1. Internal Dump no.3 (Amrakanan) 2. Internal Dump no.1 3. External Dump no. 2,3 & 4 4. Khusrudih Road & Dump

					£ 4 1			19.23	slope 5. Near water tank at Gevra project 6. Magazine side 1. Externa Dump no.2,3 & s
1999	11950	0	65000	65000	76950	3150	18000		2. Near Helipad Gevra 3. Externa Dump no.3 (Planted by Dipka project at Dipka unit 4. Near Selting pond (Commercial)
2000	0	0	130000	130000	130000	0	15000	32.5	1.External Dump no. 2.3 & 2 2. Externa Dump no. 3 3. Externa Dump 3 (Planted by Dipka project at Dipka unit)
2001	0	0	66000	66000	66000	0	13000	16.5	1. External OF Dump No. 2,3&4 (Top 2. External OF Dump No. 2,3&4 (Slope)
2002	10000	0	30000	30000	40000	500	4000	16	1. External Dump No 6 2. Back Filling 3. Dump No 6 (Slop)
2003	30000	81000	20000	101000	131000	1270	15000	35	1. Old Dipka Dump No. 3 2. Pragati Nagar 3. Gandhi Nagar 4. Dump No 1&2
								32	1.North side of Dump No. 2,3&4 Near Toe 2. In side Shakti nagar colony 3. Inside Centeral work shop 4. Shakti nagar Gate to DETP (road side green belt strengthening) 5. Dipka barrier to Gevra Water filter (road side side side side side side side sid
2004	22000	5500	78500	84000	106000	3583	36000		green bel' strengthening) 6. Kusmunds road side green belt 7. Dump No. 5 8. south side Slope of Dump No. 2.3&4 9. North side Slope of Dump No. 2.3&4 10. Old Internal Dump (East Section) Toe Ince Green bell 11. Dump No. 1 Slope Internal East Section)
2005	76000	0	39500	39500	115500	4800.33	39500	38	East Section) 1. Dump No.3 Dipka Unit 2. Dump No 2.3&4 North Slope) west side of Helipad 3. Along Kusmunda Road (North side of 2.3,&4 No Dump (2KM X 50 m) 4. Center Park

,									(with in MGR) 5. Along Main Road both sides (From CETI to Dipka Barrier in patches) 6. Dump No 2,3& 4 western side Dump 7. Back side of Shakti Nagar Colony
2005	41500	0	0	0	41500	2000	0		
2006	75000	40000	5000	45000	120000	4500	45000	48	
2007	50000	0		0	50000	0	0	20	1. Hydro Seeding of grasses On B/F Dump No 3 & 6
2008	5000	0	20000	20000	25000	0	0	15	Near Magazine Near DETP Kusmunda road (in between MGR& railway Line Dipka Barrier Hardi Bazar road side (Near 3 no. Dump of Dipka Unit)
2009	32500	0	30000	30000	62,500	0	20000	21	1. Near Magazine 2. Kusmunda road (in between MGR& Railway Line) 3. Dipka barrier to Hardi Bazar road side (Near 3 No. Dupm of Dipka Unit) 4. Dump NO. 3 (External)Dipka Unit 5. South side Slope of Ext.Dump No 3 (Dipka Unit)
2010	2500	36500		36500	39,000	0	0	25	1. Dump No. 3 (Internal) 2. South East side Slope of Internal Dump No 3 3. Around DETP,CHP,Feed er Breaker, TA office (Urja Nagar), CTI
2011	0	27500	0	27500	27,500	0	12500	16	1.Dump No. 3 (Internal) 2. South -East side Slope of internal Dump No 3 3. On Plain Area Near Dipka Railway Track
2012	10000	20000	0	20000	30000	0	3125	12	1. Dump No. 6&7 (Internal) 2. On Plain area Behind Urja Nagar C-Type Quarter
2013	5000	0	35000	35000	40000	0	5000	14	1. On External Dump No.6&7 (Top& Slope) 2.On Plain area GOLF Ground (Near Silo)
2014	0	0	20000	20000	20000	0	0	10	1. External OB Dump No 6&7 2. Side Slope of External OB Dump No 6&7
2015	0	0	80000	80000	80000	0	10000	26	1. On External Dump No.6&7 (

Ī	1	1	Ĭ.			1			Top& Slope)
2016	0	0	50000	50000	50000	0	0	20	1. On External Dump No.6&7 (Top& Slope)
2017	0	0	100000	100000	100000	0	5000	30	1. On External Dump No 6&7 (Top & Slope)
2018	6500	0	60000	60000	66500	0	0	0	1. On External Dump 6&7 (Top) 2. on Road side (New Coal transport Road)
2019	62750	0	0	0	62750	0	0	21.1	1. Near Ganga Nagar 2. Plain Area in Between External Dump No 6&7 and Laxman Both Side
2021	31998	52500	0	52500	84498	0	18750	27.79 9	Avad Nagar (Magazine Plot). Avad Nagar (Road Side)
2022	48450	0	0	0	48450	0	29613	19.38	Bhatora Basahat Magzine side
2023	19415	0	0	0	19415	0	0	7.766	Near Shakti Nagar Pond
Total	301782 6	33265 0	1103320	1435970	4453796	19803.3	30448 8		
Plante d area (Ha)	689.465	137.6	367.2	504.8	1194.265				

GAP PLANTATION DETAILS								
Year of Gap Area No. of saplings plantation in Ha. Planted			Location					
2020-21	17	55950	Mangaon Dump, (Laxman Project)					
2021-22	2	5000	Shramil Chouk to Dipka Chouk					
2022-23	23.69	82915	External Dump 6&7 (slope)					
2023-24	43.405	106577	Awad Nagar Behind Kabaristhan, Between NTPC & private rail track, Behind Magazine & Infront of Railway Colony Shakti Nagar					

नोडल ऑफीसर (पर्यावरण/यन) Modal Officer (ENV/Forest) SECL/Gevra Area एस.ई.सी.एल./गेवरा क्षेत्र