STATE ENVIRONMENT IMPACT ASSESSMENT AUTHORITY HARYANA Bay No. 55-58, Prayatan Bhawan, Sector-2, PANCHKULA.

Tel: 0172-2565232 E-mail Id: <u>seiaa.hry@gmail.com</u>

No. SEIAA(125)/HR/2020/ 5/o

Dated: 62 /10/2020

To

M/s ERPL Warehouse Park Private Limited, One Indiabulls Centre, 11th Floor, Tower 2 A, Senapati Bapat Marg, Mumbai, Maharashtra

Subject:

District Mewat (Nuh), Haryana. Environment Clearance for Warehouse/Logistic/ Industrial Storage Project located in the Revenue Estate of the Village Sehsaula, Taluka, Tauru,

- constituted by MoEF & CC, GoI vide their Notification dated 30.01.2019, in its meeting held on 13.07.2020 awarded "Gold" rating / grading to the project. furnished in response to the observations of the State Expert Appraisal Committee (SEAC) with the application viz., provisions under the EIA Notification, 2006 on the basis of the mandatory documents enclosed Notification, 2006. The proposal has been appraised as per prescribed procedure in the light of Member Secretary, SEIAA, Haryana received on 12.03.2020 and subsequent letter dated 13.07.2020 seeking This letter is in reference to your application dated 06.01.2020 addressed to prior Environmental Clearance for the Form-1, Form1-A, Conceptual Plan and additional clarifications above project under the
- Mewat (Nuh), Haryana. The details of the project as given below: Storage Project located in the Revenue Estate of the Village Sehsaula, Taluka, Tauru, District [2] It is inter-alia, noted that the project involves the Warehouse/Logistic/ Industrial

Sr.	Par	Particulars
No.		
1.	Online Proposal Number	SIA/HR/MIS/135870/2020
2.	Latitude	28°14'11.13"N
3.	Longitude	77° 1'28.54"E
4.	Plot Area	2,16,001.15 Sqm
5.	Net Plot Area	2,16,001.15 Sqm
6.	Proposed Ground Coverage	101275.82 Sqm
7.	Proposed FAR	101275.82 Sqm
.∞	Non FAR Area	33,958.17 Sqm
9.	Total Built Up area	1,35,233.99 Sqm
10	Total Population	3450
11.	Total Green Area with %	43281.37 (20% of Plot Area)
12.	Rain Water Harvesting Pits (with size)	53 Pits (Effective Depth= 4m, Diameter = 3.68 m with dual bore)
13.	STP Capacity	150 KLD
14.	Total Parking (Nos)	Trucks = 235 Four Wheelers = 470 Two Wheelers = 470
15.	Organic Waste Converter	1 (125 Kg/ batch)
16.	Maximum Height of the Building	18 meter

Power Requirement Power Backup Total Water Requirement Domestic Water Requirement Fresh Water Requirement Treated Water Waste Water Generated Solid Waste Generated Biodegradable Waste Number of Towers R+U Value of Material used (Glass) Total Cost of the project: Incremental thought ii) Construction Cost CER EMP Budget Incremental Load in respect iii) PM 2.5 Load in respect iv) PM 2.5 Construction Phase: ii) Water Requirement & Source iii) STP (Modular)	1 number (CTFC 50)	iv) Anti-Smoke Gun		
7. Power Requirement 8. Power Backup 9. Total Water Requirement 1. Domestic Water Requirement 2. Treated Water 3. Waste Water Generated 4. Solid Waste Generated 5. Biodegradable Waste 6. Number of Towers 7. Number of Towers 7. Total Cost of i) Land Cost the project: ii) Construction Cost 7. CER FMP Budget 6. Incremental ii) PM 2.5 1. Load in respect of: iii) PM 2.5 1. Load in respect iii) Power Back-up 7. Phase: ii) Water 8. Requirement & Source 9. Source	1	iii) STP (Modular)		
7. Power Requirement 8. Power Backup 9. Total Water Requirement 1. Domestic Water Requirement 1. Fresh Water Generated 2. Treated Water 3. Waste Water Generated 4. Solid Waste Generated 5. Number of Towers 6. Number of Towers 7. Total Cost of i) Land Cost the project: 7. Total Cost of ii) Construction Cost the project: 8. EMP Budget 8. FMP Budget 9. Incremental Load in respect iii) PM 2.5 10. Construction 11. PM 10 12. PM 2.5 13. PM 2.5 14. PM 2.5 15. PM 2.5 16. PM 2.5 17. PM 2.5 18. PM 2.5 19. PM 2.5 19	Antismog gun Source: Local auti	Source		
7. Power Requirement 8. Power Backup 9. Total Water Requirement 1. Domestic Water Requirement 2. Treated Water 3. Waste Water Generated 4. Solid Waste Generated 5. Number of Towers 6. Number of Material used (Glass) 7. Total Cost of i) Land Cost the project: ii) Construction Cost CER EMP Budget 6. Incremental Load in respect of: iii) PM 2.5 Load in respect iii) PM 10 Construction 6. Construction 7. Power Back-up 8. Power Back-up	Treated 10 KLD (construction), 6 KLD for	Requirement		
7. Power Requirement 8. Power Backup 9. Total Water Requirement 1. Domestic Water Requirement Fresh Water Requirement 2. Treated Water 8. Waste Water Generated 1. Solid Waste Generated 2. Biodegradable Waste Biodegradable Waste Number of Towers 1. R+U Value of Material used (Glass) Total Cost of the project: CER FMP Budget Incremental Load in respect of: Incremental Load in respect iii) PM 2.5 Incremental Load in respect iii) PM 100 iv) NO2 v) CO	1 DG set of 62.5 KVA		Construction Phase:	32.
Power Requirement Power Backup Total Water Requirement Domestic Water Requirement Fresh Water Requirement Treated Water Waste Water Generated Solid Waste Generated Biodegradable Waste Number of Towers R+U Value of Material used (Glass) Total Cost of i) Land Cost the project: ii) Construction Cost CER EMP Budget Incremental Load in respect of: iii) PM 25 iii) SO2 iii) SO2 iv) NO2	$4.58 \mu g/m^3$			3
Power Requirement Power Backup Total Water Requirement Domestic Water Requirement Fresh Water Requirement Treated Water Waste Water Generated Solid Waste Generated Biodegradable Waste Number of Towers R+U Value of Material used (Glass) Total Cost of the project: ii) Construction Cost CER EMP Budget Incremental Load in respect iii) PM 2.5 iii) PM 10 iii) SO2	6.61 µg/m ³			
Power Requirement Power Backup Total Water Requirement Domestic Water Requirement Fresh Water Requirement Treated Water Waste Water Generated Solid Waste Generated Biodegradable Waste Number of Towers R+U Value of Material used (Glass) Total Cost of the project: CER EMP Budget Incremental Load in respect ii) PM 2.5 iii) PM 10	$1.5 \mu \text{g/m}^3$			
Power Requirement Power Backup Total Water Requirement Domestic Water Requirement Fresh Water Requirement Treated Water Waste Water Generated Solid Waste Generated Solid Waste Generated R+U Value of Material used (Glass) Total Cost of the project: i) Land Cost the project: ii) Construction Cost CER EMP Budget Incremental i) PM 2.5	$1.05 \mu \text{g/m}^3$	1	aa	
Power Requirement Power Backup Total Water Requirement Domestic Water Requirement Fresh Water Requirement Treated Water Waste Water Generated Solid Waste Generated Solid Waste Generated R+U Value of Material used (Glass) Total Cost of the project: CER EMP Budget	$1.05 \mu g/m^3$		Incremental	31.
Power Requirement Power Backup Total Water Requirement Domestic Water Requirement Fresh Water Requirement Treated Water Waste Water Generated Solid Waste Generated Biodegradable Waste Number of Towers R+U Value of Material used (Glass) Total Cost of the project: CER ii) Construction Cost	302 Lakhs Capital Recurring cost		EMP Budget	30.
Power Requirement Power Backup Total Water Requirement Domestic Water Requirement Fresh Water Requirement Treated Water Waste Water Generated Solid Waste Generated Biodegradable Waste Number of Towers R+U Value of Material used (Glass) Total Cost of the project: ii) Construction Cost	2.67 Crores		CER	29.
Power Requirement Power Backup Total Water Requirement Domestic Water Requirement Fresh Water Requirement Treated Water Waste Water Generated Solid Waste Generated Biodegradable Waste Number of Towers R+U Value of Material used (Glass) Total Cost of i) Land Cost	120.39 Cr.	ii) Construction Cost	the project:	
Power Requirement Power Backup Total Water Requirement Domestic Water Requirement Fresh Water Requirement Treated Water Waste Water Generated Solid Waste Generated Biodegradable Waste Number of Towers R+U Value of Material used (Glass)	57.61 Crores	i) Land Cost	Total Cost of	28.
Power Requirement Power Backup Total Water Requirement Domestic Water Requirement Fresh Water Requirement Treated Water Waste Water Generated Solid Waste Generated Biodegradable Waste Number of Towers	3.15 watt/m ²	iterial used (Glass)	R+U Value of Ma	27.
Power Requirement Power Backup Total Water Requirement Domestic Water Requirement Fresh Water Requirement Treated Water Waste Water Generated Solid Waste Generated Biodegradable Waste	ildings	S	Number of Towe	26.
Power Requirement Power Backup Total Water Requirement Domestic Water Requirement Fresh Water Requirement Treated Water Waste Water Generated Solid Waste Generated	501.27 Kg/day	aste	Biodegradable W	25.
Power Requirement Power Backup Total Water Requirement Domestic Water Requirement Fresh Water Requirement Treated Water Waste Water Generated	828.27 Kg/day	rated	Solid Waste Gene	24.
Power Requirement Power Backup Total Water Requirement Domestic Water Requirement Fresh Water Requirement Treated Water	123 KLD	erated	Waste Water Ger	23.
Power Requirement Power Backup Total Water Requirement Domestic Water Requirement Fresh Water Requirement	179 KLD		Treated Water	22.
Power Requirement Power Backup Total Water Requirement Domestic Water Requirement	92 KLD	irement	Fresh Water Requ	21.
Power Requirement Power Backup Total Water Requirement	92 KLD	Requirement	Domestic Water	20.
Power Requirement Power Backup	271 KLD	irement	Total Water Requ	19.
Power Requirement	250x6+500x4+62.5x1 KVA= 3562.5 KVA	AND RECORDS IN A CASE	Power Backup	18.
	4 MVA (i.e 3200 KW)	ent ·	Power Requirem	17.

CER ACTIVITIES

Total 35	5 Village 7	Bidhuwas 7 Village 7	Chhajupur 7	Maindla 7 Village 7	Sehsaula 7	(In Lakhs)	supply	A O POINT
*35 (*2 ponds)	0	0	0	*17.5	*17.5	(In Lakhs)	narvesting structure	
35	7	7	7	7	7	(In Lakhs)	Water Supply Project in Mewat area	
70	14	14	14	14	14	(In Lakhs)		
91.1	18.2	18.2	18.2	18.2	18.2	(In Lakhs)		Street, or other particular and the second
267	53.2	53.2	53.2	53.2	53.2	(In Lakhs)		Company of the Compan

ENVIRON	ENVIRONMENT MANAGEMENT PLAN	AN
COMPONENT	CAPITAL COST (Rs. IN LACS)	RECURRING COST/ANNUM (Rs. IN LACS)
the first on the state of the	OPERATION PHASE	
Sewage Treatment Plant	30	1.5
Rain water Harvesting Pits	160	2
Acoustic enclosure/stack for DG	20	5
sets		
Solid Waste Management / OWC	OWC-25, Bins-01	2.2
Environmental Monitoring and six		5
Green Area/ Landscape Area	10	0.9
Environment Cell Scope:		5
 Implement the environmental 		
management plan, Operating and upgrading the existing		
Environment management facilities like Hazardons		
ıen		al aliana year
 To ensure regular compliance 		
of NGT Orders, Circulars from MoEF&CC and EPCA.		
 Regular environmental 		
monitoring.		

CONSTRU	CONSTRUCTION PHASE (Cost in Lakhs)	<u>s)</u>
COMPONENT	CAPITAL COST	RECURRING
	(Rs. IN LACS)	COST/ANNUM (Rs. IN LACS)
Anti-Smog Gun	22	. V
EMP cost of Construction	8	0.5
phase(green net, tarpaulin cover to		222
cover the construction material)	AND THE RESERVE OF THE PROPERTY OF THE PROPERT	SOURISTS, I'V.
Tractors/Tanker cost for Water	18	4
sprinkling in construction phase	TASE LOS QUELLAS CONTRACTOR	rdi liseu
Wheel wash arrangement during	4	State of L
construction phase		X 151 151
Sanitation for labours (mobile	4	0.25
toilets/septic tank)		
Total	302	27.35

compliance with the with the following stipulations mentioned below:clearance for the project under Category 8(a) of EIA Notification 2006 subject to the strict State Environment Impact Assessment Authority in its 125th meeting held on 07.10.2020 project mentioned above, subject to compliance with the stipulated conditions. Accordingly, the decided to response to its observations, have recommended the grant of environmental clearance for the relevant documents submitted by the project proponent and additional clarification furnished in agree The State Expert Appraisal Committee, Haryana after due consideration of the with the recommendations of SEAC to accord necessary environmental

7 Specific Conditions:

- : Measure, Accidental Release measure, Exposure and control (Personal Measure) at The PP and consultant agree to display the First Aid measure, Fire Fighting
- 2 support from the Haryana Pond and Waste Water Management Authority PP shall restore, reclaim and maintain the pond at nearby village Sehsaula, , Chhajupur, Bidhuwas and Padheni to the project site with technical
- S recycled/reused for flushing. DG cooling, Gardening and HVAC Sewage shall be treated in the STP based on latest Technology with tertiary treatment i.e. Ultra Filtration. The Treated effluent from STP shall be Ultra
- 4 being used for flushing in terms of faecal coli forms and other pathogenic bacteria. The Project Proponent would devise a monitoring plan to the satisfaction of the State Pollution Control Board so as to continuously monitor the treated waste water
- 5 studies from toilet seats using recycled treated waters and fresh waters for flushing, supplied for flushing (specially the bacterial counts), comparative bacteriological implementation of conditions related to quality and quantity of recycle and reuse of The PP shall provide separate toilet for ladies and gents. quality of water being supplied through spray faucets attached to toilet seats Project Proponents efficiency of treatment systems, quality of treated would commission a third party water
- 6 shall be composted in Organic waste convertor. Adequate area shall be provided for Separate wet and dry bins must be provided for facilitating segregation of waste. waste dumping site through authorized vender. segregation, Solid Waste shall be segregated into wet garbage and inert materials. Wet Garbage waste composting. management The Inert waste from the project will be sent to solid within the premises which will include area
- the project is marinated and improved upon after the implementation of the project. up to ensure that the current level of service of the roads within a 05 kms. radius of agencies in this 05kms radius of the site in different scenarios of space and time Apart, a detailed Traffic management plan as submitted shall be habilitation being carried out or purpose to be carried out by the project or other This plan should be based on cumulative impact of all development and increased traffic management and traffic decongestion plan shall be drawn implemented in letter and spirit
- ∞ every 80sqm of land should be planted and maintained. 31 number of the Existing canopy cover are desirable. Water intensive and/or invasive species should not be No tree cutting has been proposed in the instant project. A minimum of 1 tree for shall be provided for green area development.

 The PP shall obtain 5% of the total power load that is 160 KW through the solar plantation of native species. for landscaping. As proposed 43281.37 counted for this purpose. The landscape planning The species with heavy foliage, broad leaves and wide (20% of plot area) of net plot area should include
- 9.
- 10. relevant agencies including town planning authority before commencement of work. All the construction shall be done in accordance with the local building relevant The Project Proponent shall obtain all necessary clearance/permission from all byelaws. authority before commencement of
- 11. pollution) Act, 1981 and the Water (Prevention and control of pollution) Act, 1974. Consent to establish/operate for the project shall be obtained Control Board as required under the Air (Prevention and Control of
- 12. National Building Code including protection measures from lightening etc. The Approval of the Competent Authority shall be obtained for structural safety of code due to earthquakes, adequacy of firefighting equipments etc. as
- 13 suppression of dust during construction phase and shall use the treated water provide the Anti smog gun mounted on vehicle in the project for
- 14 reduce the carbon footprint. shall install the Eco-Friendly Green Transformer based on Ester oil to
- 15 the approval from CGWA. CGWA before the start of the project and also obtained the CTO from HSPCB after shall obtain the permission regarding withdrawal of ground water
- 16 the project area. The PP shall not allow to park the vehicles on the roads or revenue Rasta outside

- 17. 1989 in the proposed project The PP shall not store Schedule-II and Schedule-III chemicals as per MSIHC Rules,
- 18 The PP shall not store any pharmaceutical products at the project site
- 19 shall not allow establishment of any category A or B type industry in the
- 20 upload the EC on portal and issue advertisement in newspaper for wide publicity carry out the quarterly awareness programs for the staff and also
- 21. The PP shall get geo-technical study conducted before start of the project
- 22 the CGWB norms. 53 Rain Water Harvesting pits shall be provided for ground water recharging as per
- 23. and carry out quarterly maintenance and cleaning of 53 RWH pits The PP shall install Digital water level recorder for monitoring the water recharge
- 24. permission will be taken from the concerned authority before outsourcing. No construction shall be done at the Khasra No. 35//24, 25,34//21/1/2, Low Lying area at the project site shall be leveled with the excavated soil from the In case the soil be required from any outside source, necessary
- 25 NOC dated 14.01.2020 18/2/2, 19 that is included in Bhutalaka Bund (Notified area) referred in the Forest
- 26. of water supply is ensured The PP shall not start the operation of the project till the permanent potable source
- 27. started only after complying the CLU conditions. under Forest required and as amended in case the CLU mandates for it. Construction shall be The PP shall Conservation Act, obtain the necessary permission for construction of approach road 1980 if approach from notified forest road
- 28. and PP will have to seek fresh Environment Clearance Any change in stipulations of EC will lead to Environment Clearance void-ab-initio
- 29. movement of traffic during Construction or Operational phase of upcoming project around the site to ascertain that there would be no adverse effect or impediment in Extensive studies have been undertaken regarding Traffic flow & Level of Services
- 30. While carrying out the "Air Dispersion modeling" inbound and outbound vehicles 1222 (PCU/hr.) along with the emission and 3 running hours of 11 DG sets (having capacity 8x250 KVA + 2x200 KVA + 1x62.5 KVA) of DG sets has been
- 31. fuel to be used would be as per related Guidelines of GRAP & amp; strictures/injunctions passed by Hon'ble EPCA/NGT and further National Clean Air would be implemented. Running of DG sets/ Captive Power during construction or operational phase and fuel to be used would be as per related Guidelines of GRAP & amp; Office Order No. HSPCB/SSC/2020/4320-44 dated 25/06/2020 of
- 32. CC and various judicial orders applicable for the DG sets. Installation and running of the DG sets would be as per the guidelines of MoEF&
- 33. Mist guns would be installed as per the judicial orders.
 34. The type and nature of material to be stored w
- 34 recommendation and appraisal of SEAC. No hazardous material would be stored stored would strictly
- Storage/Warehouse facility would follow the issued or amended guidelines of MoEF & CC, Gol/ SPCB/CPCB in letter and spirit. & CC, Gol/ SPCB/CPCB in letter and spirit.

B. Statutory Compliance:

- \equiv relevant agencies including town planning authority for ground coverage, FAR and should be in accordance with zoning plan approved by Competent Authority with the local building byelaws. before commencement of work. All the construction shall be done in accordance project proponent shall obtain all necessary clearance/permission from
- [2] National Building Code including protection measures from lightening etc The approval of the Competent Authority shall be obtained for structural safety of due to earthquakes, adequacy of firefighting equipment etc as per
- \Box purpose involved in the project.
 The project proponent shall The project proponent shall obtain forest clearance under the provisions of Forest (Conservation) Act, 1986, in case of the diversion of forest land for non-forest
- 4 The project proponent shall obtain clearance from the National Board for Wildlife, if applicable.

- [2]The project proponent shall obtain Consent to Establish/Operate under the provisions of Air (Prevention & Control of Pollution) Act, 1981 and the Water (Prevention & Control of Pollution) Act, 1974 from the Haryana State Pollution
- [6] The project proponent shall obtain the necessary permission for drawl of ground water /surface water required for the project from the competent authority. A certificate of adequacy of available power from the agency supplying power to
- [2]the project along with the load allowed for the project should be obtained
- ∞ be obtained, as applicable, by project proponents from the respective competent Chief Controller of Explosives, Fire Department, Civil Aviation Department shall other statutory clearances such as the approvals for storage of diesel from
- [9] and Batteries waste (Management Handling Rules, 2001 as amended in 2020) shall be followed. (Management) Rules, 2016, and the Plastics Waste (Management) Rules, provisions of the Solid Waste (Management) Rules, 2016, 2016
- [10]The project proponent shall follow the ECBC Act/ECBC-Rules prescribed by the State Government. Bureau of Energy Efficiency, Ministry of Power strictly in addition of bylaws of

I. Air quality Monitoring and Preservation

- <u>-</u>; Notification GSR 94(E) dated 25.01.2018 of MoEF&CC regarding Mandatory Implementation of Dust Mitigation Measures for Construction and Demolition Activities for projects requiring Environmental Clearance shall be complied with.
- Ξ exceedance in ambient air quality at the site. A management plan shall be drawn up and implemented to contain the current
- Ξ released (e.g. PM₁₀ and PM_{2.5}) covering upwind and downwind directions during monitoring for common/criterion parameters relevant to the the construction period. The project proponent shall install system to carryout Ambient Air Quality main pollutants
- iv) combined capacity of all proposed DG sets. Use of ultra low Sulphur diesel. The Diesel power generating sets proposed as source of backup power should be of enclosed type and conform to rules made under the Environment (Protection) Act, Control Board location of the DG sets may be decided with in consultation with State Pollution The height of stack of DG sets should be equal to the height needed for the
- bringing in sand, cement, murram and other construction materials prone to under construction, continuous dust/ wind breaking walls all around the site (at building as well as the site. These measures shall include screens for the building Dust, smoke & other air pollution prevention measures shall be provided for Construction site shall be adequately barricaded before the construction begins causing dust pollution at the site as well as taking out debris from the site least 3 meter height). Plastic/tarpaulin sheet covers shall be provided for vehicles
- \leq to prevent dust pollution Sand, Murram, loose soil, cement, stored on site shall be covered adequately so as
- vii)
- viii) suppress dust. Wet jet shall be provided for grinding and stone cutting. Unpaved surfaces and loose soil shall be adequately sprinkled with water to
- X. demolition and construction waste shall be managed as per the provisions of the on the roads or open spaces outside) before they are properly disposed. All construction and demolition debris shall be stored at the site (and not dumped Construction and Demolition Waste Rules 2016.
- × sulphur diesel type and shall conform to Environmental (Protection) prescribed The diesel generator sets to be used during construction phase shall be ultra low for air and noise emission standards.
- X. sets to mitigate the noise pollution. Ultra low sulphur diesel shall be used. The location of the DG set and exhaust pipe height shall be as per the provisions of the Central Pollution Control Board (CPCB) norms gaseous emissions from DG set shall be dispersed through adequate stack as per CPCB standards. Acoustic enclosure shall be provided to the

Xii) For indoor air quality the ventilation provisions as per National Building Code of

II. Water Quality Monitoring and Preservation

- =; other sustainable urban drainage systems (SUDS) are allowed for maintaining the drainage pattern and to harvest rain water water. No construction shall be allowed to obstruct the natural drainage through The natural drain system should be maintained for ensuring unrestricted flow of on wetland and water bodies. Check dams, bio-swales, landscape, and
- Ξ Buildings shall be designed to follow the natural topography as much as possible Minimum cutting and filling should be done.
- iii) Total fresh water use shall not exceed the proposed requirement as provided in the
- Š be measured and recorded to monitor the water balance as projected by the project well as to SEIAA, The quantity of fresh water usage, water recycling and rainwater harvesting shall The record shall be submitted to the Regional Office, MoEF&CC as Haryana along with six monthly Monitoring reports.
- 5 consideration and the balance water available. This should be specified separately for ground water and surface water sources, ensuring that there is no impact on total annual water availability with the local authority, the quantity of water A certificate shall be obtained from the local body supplying water, specifying the committed, the quantity of water allotted to the project under
- (I At least 20% of the open spaces as required by the local building bye-laws shall be pervious. Use of Grass pavers, paver blocks with at least 50% opening, landscape etc. would be considered as pervious surface.
- vii) Installation of dual pipe plumbing for supplying fresh water for drinking, cooking and bathing etc and other for supply of recycled water for flushing, landscape irrigation, car washing, thermal cooling, conditioning etc. shall be done.
- viii) flow faucets tap aerators etc) for water conservation shall be incorporated in the Use of water saving devices/ fixtures (viz. low flow flushing systems; use of low
- (X giving dual plumbing system be done. system. In case of single stack system separate recirculation lines for flushing by Separation of grey and black water should be done by the use of dual plumbing
- × concrete, curing agents and other best practices referred. demand during construction should be reduced by use of pre-mixed
- X. water recharging as per the CGWB norms. should be followed as per the Ministry of Urban Development Model Building byelaw provision is not available, adequate provision for storage and recharge The local bye-law provisions on rain water harvesting should be followed. If local 2016. Rain water harvesting recharge pits shall be provided for ground
- XII) approval from the Competent Authority. harvested and stored for reuse. The ground water shall not be withdrawn without minimum one recharge bore per 5,000 square meters of built up area and storage capacity of minimum one day of total fresh water requirement shall be provided. A rain water harvesting plan needs to be designed where the recharge bores of where ground water recharge is not feasible, the rain water should be
- xiii) All recharge should be limited to shallow aquifer.
- xiv) No ground water shall be used during construction phase of the project.
- (VX Any ground water dewatering should be properly managed and shall conform to the approvals and the guidelines of the CGWA in the matter. Formal approval shall be taken from the CGWA for any ground water abstraction or dewatering. The quantity of fresh water usage, water recycling and rainwater harvesting shall
- XVI) along with six monthly Monitoring reports.

 Sewage shall be treated in the STP with tertiary treatment. The treated effluent be measured and recorded to monitor the water balance as projected by the project proponent. The record shall be submitted to the Regional Office, MoEF&CC
- xvii) gardening. As proposed, no treated water shall be disposed in to municipal drain. No sewage or untreated effluent water would be discharged through storm water shall be recycled/re-used for flushing, AC make up water and
- xviii)

- Xix) promoted. Environment, treated water shall be discharged as per statutory norms notified by Ministry of before the project is commissioned for operation. Treated waste water shall be independent expert and a report in this regard shall be submitted to the Ministry The installation of the Sewage Treatment Plant (STP) shall be certified by an Onsite sewage treatment of capacity of treating 100% waste water to be installed on site for landscape, flushing, cooling tower, and other end-uses. Excess Forest and Climate Change. Natural treatment systems shall be
- (XX Necessary measures should be made to mitigate the odour problem from STP Periodical monitoring of water quality of treated sewage shall be conducted
- (IXX Central Public Health and Environmental Engineering Organization (CPHEEO) Manual on Sewerage and Sewage Treatment Systems, 2013. collected, conveyed and disposed as per the Ministry from the onsite sewage treatment, including septic tanks, shall be of Urban Development, shall be

II. **Noise Monitoring and Prevention**

- <u>:</u> monitored during construction phase. Adequate measures shall be made to reduce stipulated standards by CPCB/SPCB. ambient air and noise level during construction phase, so as to conform to the Incremental pollution loads on the ambient air and noise quality shall be closely during day and night as per Noise Pollution (Control and Regulation) Rules, 2000. levels shall conform to residential area/commercial
- E) Noise level survey shall be carried as per the prescribed guidelines and report in this regard shall be submitted to Regional Officer of the Ministry as a part of six-
- Ξ monthly compliance report.

 Acoustic enclosures for DG sets, noise barriers for ground-run bays, ear plugs for operating personnel shall be implemented as mitigation measures for noise impact due to ground sources

IV. **Energy Conservation Measures**

- <u>.</u> comply with the ensured. Buildings in the States which have notified their own ECBC, Compliance with the Energy Conservation Building Code (ECBC) of Bureau of Energy Efficiency as per ECBC Act, 2017 read with ECBC Rules, 2018 shall be State ECBC also which is no case shall be less than 25% as
- Outdoor and common area lighting shall be LED.
- ≣: **=:** thermal mass etc. shall be incorporated in the building design. Concept of passive solar design that minimize energy consumption in buildings by using design elements, such as building orientation, landscaping, efficient roof R & U-values shall be as per ECBC specifications. building envelope, appropriate fenestration, increased day lighting design and Wall, window, and
- 3 be in place before project commissioning. area outside the building should be integral part of the project design and should Energy conservation measures like installation of CFLs/LED for the lighting the
- 2 building bye-laws requirement, whichever is higher. generation equivalent to 1% of the demand load or as per the state level/local wind or other Renewable Energy shall be installed to meet electricity
- ¥i) and institutional building or as per the requirement of the local building bye-laws, on grid. Separate electric meter shall be installed for solar power. Solar water heating shall be provided to meet 20% of the hot water demand of the commercial Solar power shall be used for lighting in the apartment to reduce the power load on grid. Separate electric meter shall be installed for solar power. Solar water water demand from solar water heaters, as far as possible. whichever is higher. Residential buildings are also recommended to meet its hot
- \<u>`</u>: requirement and submit quantification saving report for each component The PP will submit report indicating compliance of each parameter of ECBC

V. Waste Management

- こ the M.S.W. generated from project shall be obtained. indicating the existing civic capacities of handling and their adequacy to cater to certificate from the competent authority handling municipal solid wastes,
- Ξ approval of competent authority. the neighboring communities and be disposed taking the necessary precautions for Disposal of muck during construction phase shall not create any adverse effect on and health aspects of people, only in approved sites with the
- E) Separate wet and dry bins must be provided in each unit and at the ground level garbage and inert materials. facilitating segregation of waste. Solid waste shall be segregated into wet
- iv) converting them into compost to be used as manure. kg/person/day must Organic Waste Converter within the premises with a minimum capacity of 0.5 be installed. Leaves to be put in earmarked pits for
- 5 which a written tie up must be done with the authorized recyclers. All non-biodegradable waste shall be handed over to authorized recyclers for
- <u>₹</u>. as per applicable rules and norms with necessary approvals of the State Pollution Any hazardous waste generated during construction phase, shall be disposed off
- vii) These include Fly Ash bricks, hollow bricks, AACs, Fly Ash Lime Gypsum materials, shall be required for at least 20% of the construction material quantity Use of environment friendly materials in bricks, blocks and other construction
- VIII) Blocks, Compressed Earth Blocks, and other environment friendly materials. Fly ash should be used as building material in the construction as per the provision of Fly Ash Notification of September, 1999 and amended as on 27th August, 2003 and 25th January, 2016. Ready mixed concrete must be used in building construction.
- (X managed so as to strictly conform to the Construction and Demolition Rules, Any wastes from construction and demolition activities related thereto shall be
- × recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercury contamination. Used CFLs and TFLs should be properly collected and disposed off/sent for

VI. Green Cover

- j. necessary, tree regulatory No tree can be felled/transplant unless exigencies demand. Where absolutely authority. as may be prescribed by the Forest Department. Plantations to felling shall be ority. Old trees s should be retained based on girth concerned
- **=**: maintained ensured species (cut) to species (planted). A minimum of 1 tree (5' tall) for every invasive species should not be used for landscaping. planning should include foliage, broad leaves and wide canopy cover are desirable. Water intensive and/or The existing trees will be plantation of native species. The species with heavy for every 80 sqm of land should be planted and counted for this purpose. The landscape
- Ξ ensured species (cut) to species (planted). Area for green belt development shall be provided as per the details provided in the project document. Authority, compensatory plantation in the ratio of 1:10 (i.e. planting of 10 trees Where the trees need to be cut with prior permission from the concerned local I tree that is cut) shall be done and maintained. Plantations to be
- Į. buildings, roads, paved areas, and external services. It should be stockpiled appropriately in designated areas and reapplied during plantation of the proposed Topsoil should be stripped to a depth of 20 cm from the areas proposed for vegetation on site.

VII. Transport

i) private (URDPFI), shall be prepared to include comprehensive networks. mobility Road should plan, be as designed per MoUD motorized, non-motorized, with due best practices consideration public, and guidelines for

environment, and safety of users. The road system can be designed with these

- Hierarchy of roads with proper segregation of vehicular and pedestrian
- 9 Traffic calming measures
- Proper design of entry and exit points
- Parking norms as per local regulation.
- Ξ applicable air and noise emission standards be operated only during non-peak condition and should have a pollution check certificate and should conform to Vehicles hired for bringing construction material to the site should be in good
- iii) components of the plan which involve the participation of these departments. and the traffic management plan shall agencies in this 05 Kms. radius of the site in different scenarios of space and time habitation being carried out or proposed to be carried out by the project or other project is maintained and improved upon after the implementation of the project. ensure that the current level of service of the roads within a 05 kms. radius of the A detailed traffic management and traffic decongestion plan shall be drawn up to Urban Development department and the P.W.D./ competent authority for road This plan should be based on cumulative impact of all development and increased and shall also have their consent to be duly validated and certified by the State the implementation of

VIII. **Human Health Issues**

- 1 carriage of construction material and construction debris or working in any area with dust pollution shall be provided with dust mask. All workers working at the construction site and involved in loading, unloading,
- Ξ For indoor air quality the ventilation provisions as per National Building Code of
- Ξ Assessment (HIRA) and Disaster Management Plan shall be implemented Emergency preparedness plan based on the Hazard identification and Risk
- įv) all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, the project. may be in the form of temporary structures to be removed after the completion of mobile Provision shall be made for the housing of construction labour within the site with STP, safe drinking water, medical health care, crèche etc. The housing
- Occupational health surveillance of the workers shall be done on a regular basis.
- ₹. € operations of the project. A First Aid Room shall be provided in the project both during construction and

IX. Corporate Environment Responsibility

- <u>=</u>; regarding Corporate Environment Responsibility. Ministry's OM vide F.No. 22-65/2017-IA.III dated 1st May 2018, as applicable, project proponent shall comply with the provisions contained in
- E) norms/conditions and/or shareholders/stake holders. The copy of the board resolution in this regard shall be submitted to the MoEF&CC as a part of sixinfringements/deviation/violation operating procedures to have proper checks and balances and to bring into focus The company shall have a well laid down environmental policy duly approved by the Board of Directors. The environmental policy should prescribe for standard monthly report. norms/conditions. infringements/deviation/ The company violation shall of the have of the environmental/forest/wildlife environmental/forest/ defined system of reporting wildlife
- iii) Executive, who will directly to the head of the organization. A separate with qualified personnel shall be Environmental Cell both at the project and company head quarter qualified personnel shall be set up under the control of senior
- Š any other purpose. protection measures shall be kept in separate account and not to be diverted for responsibility matrix of the company shall be prepared and shall be duly approved Action plan for implementing EMP and environmental competent authority. Year wise progress of implementation of action plan shall be The year wise funds earmarked for conditions along with environmental

- reported to the Ministry/Regional Office along with the Six Monthly Compliance
- 5 with the "Six Monthly Compliance Report" positively. the Chartered Accountant showing the dispersal of funds in said schemes along PP must submit the Balance sheet/Account statement duly attested & signed by

X. Miscellaneous

- language within seven days indicating that the project has been according environment clearance and the details of MoEFCC/SEIAA website where newspapers of the District or project proponent shall prominently advertise ers of the District or State, of which one shall be within seven days indicating that the project his it at least in in the vernacular accorded
- =: addition to the relevant offices of the Government who in turn has to display the proponents to the Heads of local bodies, Panchayats and Municipal Bodies same for 30 days from the date of receipt. of the environmental clearance shall be submitted by the project
- Ei) environment clearance conditions, including results of monitored data on their website and update the same on half-yearly basis. The project proponent shall upload the status of compliance of the stipulated
- Į. ministry of Environment, Forest and Climate Change at environment clearance compliance The project proponent shall submit six-monthly reports on the status of the portal and soft copy of the same to the SEIAA, Haryana. of the stipulated environmental conditions on the website of the
- <u>S</u> put on the website of the company. year in Form-V to the concerned State Pollution Control Board as prescribed under the The project proponent shall submit the environmental statement for each financial Environment (Protection) Rules, 1986, as amended subsequently and
- Vi) operation by the project. authorities, commencing the land development work and start of production date of project proponent shall inform the Regional Office as well as the Ministry, date of financial closure and final approval of the project by the concerned
- Yii) Pollution Control Board and the State Government. The project authorities must strictly adhere to the stipulations made by the State
- viii) the Expert Appraisal Committee. The project proponent shall abide by all the commitments and recommendations made in the form-IA, Conceptual Plan and also that during their presentation to
- X. change of area of this project. (MoEF&CC)/SEIAA, Haryana. The project proponent shall seek fre environmental clearance under EIA notification 2006 if at any stage there prior approval of the Ministry of Environment, Forests and Climate Change No further expansion or modifications in the plan shall be carried out without The
- $\stackrel{\sim}{\times}$ void-ab-initio and PP will have to seek fresh Environment Clearance Any change in planning of the approved plan will leads to Environment Clearance
- XI) Environment Clearance to SEIAA. The PP should give unambiguous affidavit giving land promoters in accordance your ownership and possession of land legal the case referred for
- Xii) revocation of this environmental clearance and attract action under the provisions of Environment (Protection) Act, 1986. Concealing factual data or submission of false/fabricated data may result in
- XIII) any of the above conditions is not satisfactory. The Ministry/SEIAA may revoke or suspend the clearance, if implementation of
- xiv) The Ministry/SEIAA reserves the right to stipulate additional conditions if found The Company in a time bound manner shall implement
- (vx The Regional Office of this Ministry shall monitor compliance of the stipulated conditions. The project authorities should extend full cooperation to the officer (s) of the Regional Office by furnishing the requisite data/information/monitoring

- XVI) The above conditions shall be enforced, inter-alia under the provisions of the amendments and Rules and any other orders passed by the Hon'ble Supreme Control of Pollution) Act, 1981, the Environment (Protection) Hazardous and Other Wastes (Management and Transboundary Court of India/High Courts and any other Court of Law relating to the subject Water (Prevention & 2016 and the Public Liability Control of Pollution) Act, 1974, the Air (Prevention & Insurance Act, 1991 along with their Movement)
- xvii) by any Court/Tribunal. The Project proponent shall not violate any judicial orders/pronouncements issued
- хүііі) project has been started before obtaining prior Environmental Clearance initiated against the Project Proponent if it was found that construction of the Under the provisions of Environment (Protection) Act, 1986, legal action shall be
- XIX) Any appeal against the this Environmental Clearance shall lie with the National Green Tribunal, if preferred, within a period of 30 days as prescribed under Section 16 of the National Green Tribunal Act, , 2010.
- XX The project proponent shall put in submitted to SEIAA within 3 months of issuance of this letter mentioned in MoEF, GoI OM No. months period. Latest Corporate Environment Policy J-11013/41/2006-IA II (I) dated 26.4.2012 Corporate Environment Policy should
- (IXX Notification no. S.O.121/PA2/1900/S.4/97 dated 28.11.1997. The project proponent shall ensure the compliance of Forest Department, Haryana
- iixx proponent. Besides the developer/applicant, compliance of Environmental Safeguards/ Environmental Clearance letter and project proponent can not absolve himself The project proponent is responsible for compliance of all conditions in name/names the license/CLU has been granted by the Town & Country Planning compliance of Environmental Safeguards/ conditions imposed in the Environmental Clearance letter shall also lie on the licensee/licensees in whose /herself of Department, Haryana. the responsibility by shifting it to any contractor engaged by project the responsibility to ensure
- xxiii) there is change in the planning of the proposed project. The project proponent shall seek fresh Environmental clearance if at any stage
- xxiv) drinking/domestic purposes. project proponent shall install RO plant for purification of water for
- (VXX to the proposed warehouse complex before actually using the same. The project proponent shall obtain revalidation of permission of NHAI for access
- xxvi) in transportation shall be made. Pollution control measures for oil/diesel waste due to large no of Trucks involved
- xxvii) concerned Authority before commissioning the project. The project proponent shall get approval of scheme for firefighting from the
- xxviii) The project proponent shall not construct any service apartment in the warehouse
- xxix) sufficiently above the level of the approach road to the Project. Levels of the other areas in the Projects shall also be kept suitably so as to avoid flooding. Project Proponent shall keep the plinth level of the building blocks
- The project proponent shall construct a sedimentation basin in the lower level of the project site to trap pollutant and other wastes during rains.
- xxxi) The project proponent shall provide proper rasta of proper width and proper strength for the project before the start of construction.
- xxxii) above 30 meter as per National Building Code The project proponent shall provide fire control room and fire officer for building
- xxxiii) in the public drainage system and shall seek permission of HUDA before the start The project proponent shall discharge excess of treated waste water/storm water
- xxxiv) The project proponent shall maintain the distance between STP and water supply
- (VXXX For disinfection of the treated wastewater ultra-violet radiation or ozonization
- xxxvi) The project proponent shall strive to minimize water in irrigation of landscape by minimizing grass area, irrigation system, using native variety, xeriscaping and mulching, utilizing scheduling irrigation only after checking

xxxvii) The Project Proponent shall use zero ozone depleting potential material in insulation, refrigeration, air-conditioning and adhesive. Project Proponent shall also provide Halon free fire suppression system.

Standards for discharge of environmental pollutants as enshrined schedules of rule 3 of Environment Protection Rule complied with. 1986 shall Ħ. be various

- xxxix) The project proponent shall ensure that the of DG sets is more than the highest 800 KVA shall be as per CPCB latest standards for high capacity DG sets. tower and also ensure that the emission standards of noise and air are within the CPCB latest prescribed limits. Noise and Emission level of DG sets greater than
- (Ix)between 0.98 lag to 1 at the point of connection. All electric supply exceeding 100 amp, 3 phase shall maintain the power factor
- xli) resorted for conservation of power and water. Coil type cooling DG Sets shall be used for saving cooling water consumption for water cooled DG Sets. Integrated Point Load Value and minimum outside fresh air supply humidity during summer and winter seasons should be kept at optimal level Variable speed drive, best Co-efficient of Performance (Cop), as well as optimal based HVAC system should be adopted and only treated water shall be used by HVAC in project proponent for The project proponent shall not use fresh water for HVAC and DG cooling. Air use evaporative order to reduce cooling, cooling technology and double stage cooling system for water consumption. Further if it is at all needed. The Project Proponent shall temperature, relative
- XIII) quality grain oriented, low loss silicon steel and virgin electrolyte grade copper. The project proponent shall obtain manufacturer's certificate also for that The project proponent shall ensure that the transformer is constructed with high
- xliii) sufficiently high. Stack shall be designed in such a way that there is no stack project proponent shall ensure that exit velocity from the stack should be
- xliv) as per the laid down law of land. Compliance report should be sent to this office till life of the project. resident welfare association/Housing co-operative societies shall responsible to comply conditions laid down in EC. In case of violation the action would be taken date of issuance of EC letter. The environment clearance conditions applicable till down-wash under any meteorological conditions.

 The validity of this environment clearance letter is valid up to 7 years from the space project in case of Residential project will continue to apply. The
- $x^{l}v$ If project is not completed within the validity period then the project proponent shall submit the application for extension of validity within one month before the lapse of validity period of Environment Clearance 1e. 7 years.
- xlvi) address of communication The project proponent should intimate to the Authority well before shifting their

Chairman,

State Level Environment Impact Assessment Authority, Haryana, Panchkula.

Endst. No. SEIAA(125)/HR/2020/

Dated:

10/2020

A copy of the above is forwarded to the following:

- -New Delhi-110003 Director (IA Division), MoEF & CC, GoI, Indra Paryavaran Bhavan, Zor bagh Road-
- 2 Bay's no. 24-25, Sector 31-A, Dakshin Marg, Chandigarh-160018. Regional office, Ministry of Environment, Forests & Climate Change, Govt. of India,
- S Chairman, Haryana State Pollution Control Board, C-11, Sector-6, Panchkula
- 4 Madhya Marg, Chandigarh- 160018. General, Town & Country Planning Haryana, Plot No. 3, Sector
- 5. Concerned File/ Office Copy

Chairman,

State Level Environment Impact Assessment Authority, Haryana, Panchkula.