Muck Disposal Plan

Name of Proposal: -"Development of Economic Corridors, Inter-corridors, feeder routes and Coastal Road to improve the efficiency of freight movement in India (Lot-3/Odisha & Jharkhand/Package-2) Raipur-Vishakhapatnam (Ch. 0.000 - Ch. 124.661 km) (Length 124.661 km) in the State of Chhattisgarh under Bharatmala Pariyojana. (Forest Proposal is for between km 42+844 to Km 124661)."

INTRODUCTION

Construction of this projectroad having total length of 124.661 km is a green field alignment having PRoW 60 meter in general and 45 meter in Forest Area, embankment height (in general) 2.00 to 2.5 meter located on plane terrain. In a small section of project road cutting and tunnelling is proposed and to raise the height of embankment additional earth material is required and muck generated in tunnelling & cutting portion will be will be reutilized in project work. Required details are tabulated below;

SL Particulars 1 Calculation of muck to be generated. Swell factor to be applied. Since, the project road alignment is mostly located in plain area having some scope of tunneling (2650 m) and hill cutting, muck will be generated. Since, project road length is about 124.661 km length having PRoW 60 meter in general and 45 meter in forest/ hilly area with average embankment height 2.0-to-2.5-meter, entire generated muck will be re-utilized in road work to raise the embankment. No muck will be remaining to dispose. It is to be noted that to raise Final Road/ Level (FRL)/ Road Embankment, significant quantity of earth material will be required instead of generation of muck. 2. Quantity of muck to be utilized in the project activities As stated in above column, disposal of Muck is very unlikely. However, some construction debris are likely to be generated and which will	be	elow;		
Since, the project road alignment is mostly located in plain area having some scope of tunneling (2650 m) and hill cutting, muck will be generated. Since, project road length is about 124.661 km length having PRoW 60 meter in general and 45 meter in forest/ hilly area with average embankment height 2.0-to-2.5-meter, entire generated muck will be re-utilized in road work to raise the embankment. No muck will be remaining to dispose. It is to be noted that to raise Final Road/ Level (FRL)/ Road Embankment, significant quantity of earth material will be required instead of generation of muck. 2. Quantity of muck to be utilized in the project activities As stated in above column, disposal of Muck is very unlikely. However, some construction debris are likely to be generated and which will	SL	Particulars	Remarks	
located in plain area having some scope of tunneling (2650 m) and hill cutting, muck will be generated. Since, project road length is about 124.661 km length having PRoW 60 meter in general and 45 meter in forest/ hilly area with average embankment height 2.0-to-2.5-meter, entire generated muck will be re-utilized in road work to raise the embankment. No muck will be remaining to dispose. It is to be noted that to raise Final Road/ Level (FRL)/ Road Embankment, significant quantity of earth material will be required instead of generation of muck. 2. Quantity of muck to be utilized in the project activities As stated in above column, disposal of Muck is very unlikely. However, some construction debris are likely to be generated and which will	1	Calculation of muck to be generated. Swall		
tunneling (2650 m) and hill cutting, muck will be generated. Since, project road length is about 124.661 km length having PRoW 60 meter in general and 45 meter in forest/ hilly area with average embankment height 2.0-to-2.5-meter, entire generated muck will be re-utilized in road work to raise the embankment. No muck will be remaining to dispose. It is to be noted that to raise Final Road/ Level (FRL)/ Road Embankment, significant quantity of earth material will be required instead of generation of muck. 2. Quantity of muck to be utilized in the project activities As stated in above column, disposal of Muck is very unlikely. However, some construction debris are likely to be generated and which will		factor to be applied.	Since, the project road alignment is mostly	
2650 m) and hill cutting, muck will be generated. Since, project road length is about 124.661 km length having PRoW 60 meter in general and 45 meter in forest/ hilly area with average embankment height 2.0-to-2.5-meter, entire generated muck will be re-utilized in road work to raise the embankment. No muck will be remaining to dispose. It is to be noted that to raise Final Road/ Level (FRL)/ Road Embankment, significant quantity of earth material will be required instead of generation of muck. 2. Quantity of muck to be utilized in the project activities As stated in above column, disposal of Muck is very unlikely. However, some construction debris are likely to be generated and which will			tunneling (
generated. Since, project road length is about 124.661 km length having PRoW 60 meter in general and 45 meter in forest/ hilly area with average embankment height 2.0-to-2.5-meter, entire generated muck will be re-utilized in road work to raise the embankment. No muck will be remaining to dispose. It is to be noted that to raise Final Road/ Level (FRL)/ Road Embankment, significant quantity of earth material will be required instead of generation of muck. 2. Quantity of muck to be utilized in the project activities As stated in above column, disposal of Muck is very unlikely. However, some construction debris are likely to be generated and which will				
124.661 km length having PRoW 60 meter in general and 45 meter in forest/ hilly area with average embankment height 2.0-to-2.5-meter, entire generated muck will be re-utilized in road work to raise the embankment. No muck will be remaining to dispose. It is to be noted that to raise Final Road/ Level (FRL)/ Road Embankment, significant quantity of earth material will be required instead of generation of muck. 2. Quantity of muck to be utilized in the project activities As stated in above column, disposal of Muck is very unlikely. However, some construction debris are likely to be generated and which will			generated. Since project road longth is about	
general and 45 meter in forest/ hilly area with average embankment height 2.0-to-2.5-meter, entire generated muck will be re-utilized in road work to raise the embankment. No muck will be remaining to dispose. It is to be noted that to raise Final Road/ Level (FRL)/ Road Embankment, significant quantity of earth material will be required instead of generation of muck. 2. Quantity of muck to be utilized in the project activities As stated in above column, disposal of Muck is very unlikely. However, some construction debris are likely to be generated and which will		18	124.661 km length having PROW 60 motor in	
average embankment height 2.0-to-2.5-meter, entire generated muck will be re-utilized in road work to raise the embankment. No muck will be remaining to dispose. It is to be noted that to raise Final Road/ Level (FRL)/ Road Embankment, significant quantity of earth material will be required instead of generation of muck. 2. Quantity of muck to be utilized in the project activities As stated in above column, disposal of Muck is very unlikely. However, some construction debris are likely to be generated and which will			general and 45 meter in forest/ hilly area with	
entire generated muck will be re-utilized in road work to raise the embankment. No muck will be remaining to dispose. It is to be noted that to raise Final Road/ Level (FRL)/ Road Embankment, significant quantity of earth material will be required instead of generation of muck. 2. Quantity of muck to be utilized in the project activities As stated in above column, disposal of Muck is very unlikely. However, some construction debris are likely to be generated and which will			average embankment height 2.0-to 2.5 motor	
road work to raise the embankment. No muck will be remaining to dispose. It is to be noted that to raise Final Road/ Level (FRL)/ Road Embankment, significant quantity of earth material will be required instead of generation of muck. 2. Quantity of muck to be utilized in the project activities As stated in above column, disposal of Muck is very unlikely. However, some construction debris are likely to be generated and which will	1.		entire generated muck will be re-utilized in	
will be remaining to dispose. It is to be noted that to raise Final Road/ Level (FRL)/ Road Embankment, significant quantity of earth material will be required instead of generation of muck. 2. Quantity of muck to be utilized in the project activities As stated in above column, disposal of Muck is very unlikely. However, some construction debris are likely to be generated and which will			road work to raise the embankment. No muck	
It is to be noted that to raise Final Road/ Level (FRL)/ Road Embankment, significant quantity of earth material will be required instead of generation of muck. 2. Quantity of muck to be utilized in the project activities As stated in above column, disposal of Muck is very unlikely. However, some construction debris are likely to be generated and which will			will be remaining to dispose	
(FRL)/ Road Embankment, significant quantity of earth material will be required instead of generation of muck. 2. Quantity of muck to be utilized in the project activities As stated in above column, disposal of Muck is very unlikely. However, some construction debris are likely to be generated and which will			It is to be noted that to raise Final Road/ Level	
2. Quantity of muck to be utilized in the project activities of earth material will be required instead of generation of muck. As stated in above column, disposal of Muck is very unlikely. However, some construction debris are likely to be generated and which will			(FRL)/ Road Embankment, significant quantity	
2. Quantity of muck to be utilized in the project activities Quantity of muck to be utilized in the project activities As stated in above column, disposal of Muck is very unlikely. However, some construction debris are likely to be generated and which will			of earth material will be required instead of	
activities As stated in above column, disposal of Muck is very unlikely. However, some construction debris are likely to be generated and which will	_		generation of muck	
very unlikely. However, some construction debris are likely to be generated and which will	2.	Quantity of muck to be utilized in the project	As stated in above column, disposal of Muck is	
debris are likely to be generated and which will		activities	very unlikely. However, some construction	
			debris are likely to be generated and which will	
be utilized (like in embankment, leveling			be utilized (like in embankment, leveling,	
making approach road, worker camp etc) in			making approach road, worker camp etc) in	
project work and no disposal is required.	2	D.L.	project work and no disposal is required.	
3. Balance quantity of muck which requires No Balance quantity is estimated, construction	3.	dianage quantity of muck which requires	No Balance quantity is estimated, construction	
related debris will be utilized in project work.	1	disposal/ management plan.	related debris will be utilized in project work.	
Carriage of muck from the muck generation Not applicable, due to above mentioned reason	4	Carriage of muck from the muck generation	Not applicable, due to above mentioned reason	
in column no. 1 & 2.	_	site to the dumping site.	in column no. 1 & 2.	
I work and the consent of Idild Not applicable, due to above mentioned reason	5.	Ownership of land and the consent of land	Not applicable, due to above mentioned reason	
1 owners in case mack disposal is proposed on I in column no. 1 & 2		owners in case muck disposal is proposed on	in column no. 1 & 2.	
non-forest land.	_			
Photograph & carrying capacity of proposed Not applicable, due to above mentioned reason	- 1	rnotograph & carrying capacity of proposed	Not applicable, due to above mentioned reason	
in column no. 1 & 2.	- -	dumping site (Muck disposal site)	in column no. 1 & 2.	
7 Development of dumping site-construction of Not applicable, due to above mentioned reason	/	Development of dumping site-construction of	Not applicable, due to above mentioned reason	



	retaining walls and other structure as per requirement of the site. The objective is to completely stop rolling down of the muck.	
8	Pohabilitation of I	Not applicable

Note: - Cost to be incurred on the above activities has to be given component wise. Details of dumping site including length, width and height of structures to be erected must be mentioned.

Undertaking by user agency has to be given to the effect that:

1. Muck management plan will be implemented by user agency and in case of non-implementation of plan; they will be liable to penalty / action at their cost

2. The proposed dumping site is located away from river/stream/ Nala-NA

Date: - 28/06/2021

Place:-Dhamtari

Project Director
NHAI – PIU Dhamtari , Chhattisgarh

Name: - Savyasachi Choudhury

PROJECT DIRECTOR NHAI, PIU, Dhamtari (C.G.)