


Muck Disposal/Management Plan

The Existing bituminous layer will be milled by milling machines and collected at plant site by sing latest technology of recycling of the milled material, which is regenerate by adding admixture and emulsion. Thus the obtained mix will be reused in the construction of project highways. This practice permissible under the Specification for Highways published by Ministry of Road Transport and Highways (MORTH).

Hence, the project itself will not produce any muck to be disposed. It is further stated that muck produced is very valuable material and is mixture of grit and bitumen which is not advisable to through it off.




 परियोजना महाप्रबन्धक
 उ०प्र० राज्य राज मार्ग प्राधिकरण
 क्षेत्रीय कार्यालय, मुजफ्फरनगर


 (सि. से. विभाग)
 विभागाध्यक्ष
 राज्य राज मार्ग प्राधिकरण-मुजफ्फरनगर

ining and Up - gradation for Muzaffarnagar to Saharanpur (Via Deoband) Road SH - 59 From PWD KM 06+000 to PWD KM 59+000

Muck Produced from Flyover @ Deoband and Underpass X 4

Refilling for Concrete foundation in Flyover @ Deoband and Underpass X4

...e No Muck Quantity has been produce or Balance to be destroyed.....

उपसंचालक
परिक्षाजना महाप्रबन्धक
उपसंचालक
उपसंचालक