TAMIL NADU TRANSMISSION CORPORATION LIMITED

ABSTRACT

Electricity - Coimbatore Region - Coimbatore Operation circle Establishment of 110/22-11 SS at Somayapalayam with 1x25 MVA,110/22 kV power transformer and 2x10 MVA,110/11 kV power transformer - Administrative approval - Accorded.

TECHNICAL BRANCH

(Per).FB.TANTRANSCO Proceedings No.1

Dated: 14.12.2010

Karthigai. 28

Thiruvalluvar Aandu 2041.

READ:

1.Lr.No.CE/D/CBI^E/AEE/Plg/F.Somayapalayam/D.No.581/10,Dt.

08.06.2010 and its subsequent correndences

2. Minutes of the 10th meeting of the Board of Directors of

TANTRANSCO held on 07.12.2010 in item.No.16.

PROCEEDINGS:

- 1. The Tamil Nadu Transmission Corporation Limited hereby approves the proposal for establishment of 110/22-11 kV SS at Somayapalayam with 1x25 MVA,110/22 kV power transformer and 2x10 MVA,110/11 kV power transformer in Coimbatore Operation circle of Coimbatore Region at an estimated cost of Rs.987.31 lakhs Gross and Nett. The detailed estimate and report are annexed to these proceedings.
- 2. The expenditure is chargeable to TANTRANSCO Funds Capital Expenditure Coimbatore Operation circle A/C code No: 14.655.
- 3. By virtue of the provisions contained in sub-section (2) (a) of section 185 of the Electricity Act, 2003, the TANTRANSCO being the Transmission utility, Licensee and successor entity of Tamil Nadu Electricity Board will exercise the powers of the Telegraph Authority under the provisions of section 164 of the Electricity Act, 2003, which have already been conferred upon the Board under section 51 of the Indian Electricity Act, 1910.
- 4. The work is to be taken up after ensuring budget provision.

// BY ORDER OF THE BOARD//

S.KALYANI CHIEF ENGINEER / PLANNING & RC

Encl: Report and detailed estimate.

Fy 18/12/10

To

The Chief Engineer / D/ Coimbatore Region (2 Copies)

Copy to:

The Managing Director/TANTRANSCO/Chennai-2

The Director /Transmission Projects/ TANTRANSCO/Chennai - 2 (2 Copies)

The Director / Operation / TANTRANSCO/Chennai - 2

The Director/Distribution/TANGEDCO/Chennai-2

The Director/Finance/ TANTRANSCO/ Chennai -2

The Director/Finance/TANGEDCO/Chennai-2

The Chief Engineer/Transmission projects/Chennai-2

The Superintending Engineer/ Coimbatore EDC/North-

The Superintending Engineer/ Operation/ Coimbatore

The Superintending Engineer / GCC / Coimbatore

The Superintending Engineer / Transmission -I/ Chennai - 2

The Superintending Engineer /Transmission -II/ Chennai -2

The Superintending Engineer /RE&I(D) /Chennai -2

The Superintending Engineer/System Studies / Chennai - 2

The Resident Audit Officer (AGO'S Unit) / Chennai -2

B.P.Section (Administrative Branch) (2 Copies)

Board office (A10 section)

Stock file

// FORWARDED BY ORDER//

EXECUTIVE ENGINEER/MASTER PLAN (i/c)

End. NO!- SE/CEDC/N/Che/AEC.41/AEI/F. SMP 93/ D. NO:-2082/10 dt

Copy to EE/OLN/S. D. Palayan, Estolar le Vadamadeuri ? For

AEE/OLN/S. D. Palayan, Ext/OLN/Korth/ML,

AE/OLN/South/FDLL, AE/OLN/Somajamphlayan,

AE/OLN/Bharthain wilversin, Adolm/Kanwai.

AE/OLN/P.N. Pudler

For indomention, and newsay alin.

DESPATORES

Im sottop d'inten

REPORT TO ACCOMPANY THE ESTIMATE

This proposal envisages establishment of 110/22-11 kV SS at Somayapalayam with 1x25 MVA,110/22 kV power transformer & 2x10 MVA,110/11 kV power transformer in Coimbatore Operation circle of Coimbatore Region at an estimated cost of Rs.987.31 lakhs Gross and Nett.

NEED

The areas in and around Somayapalayam such as Pannimadai, Vadavally etc, are being fed by S.N.Palayam 110/11 kV SS and Thudiyalur 110/22 kV SS. The details of the substations and feeders feeding these areas are detailed below;

> S.N.Palayam 110/11 kV SS is having 4x16 MVA, 110/11 kV power transformers. The sustained peak on this SS is 51.92 MVA. The power transformers are loaded to 81.13 % of their capacity with a load growth of 7.4 %. Two 11 kV feeders are feeding a portion of the above area. They are furnished below:

SI. No	Name of the feeder	C.L in MVA	Length of # in km	Peak reached in MVA	Voltage regulation	Line loss in LU
1.	11 kV Maruthamalai feeder	10.029	13.165	6.52	18.81 %	12.67
2.	11 kV P.N.Pudur feeder	11.052	7.0	6.07	14.82 %	10.98

> Thudiyalur 110/22 kV SS is having 2x25 MVA, 110/22 kV power transformer. The sustained peak on this SS is 38.91 MVA. The power transformers are loaded to 77.8 % of their capacity with a load growth of 11.53 %. Two 22 kV feeders are feeding the remaining portion of the above area. They are furnished below:

SI. No	Name of the feeder	C.L in MVA	Length of # in km	Peak reached in MVA	Voltage regulation	Line loss in LU
1.	22 kV Somayapalayam feeder	17.750	8.61	6.58	11.59 %	16.46
2	22 kV Kanuvai feeder	21.650	7.24	8.97	8.25 %	8.7

From the above, it may be seen that the voltage regulation of 11 kV Maruthamalai feeder, 11 kV P.N.Pudur feeder off S.N.palayam 110 kV SS, 22 kV Somayapalayam feeder and 22 kV Kanuvai feeder off Thudiyalur 110 kV SS have exceeded the permissible limit of 8%. Also, the loading on the existing power transformers in the two substations has exceeded 70% of their capacities.

There is no possibility of transferring the load to the nearby substations since, load on the nearby substations have reached more than 70% their power transformer capacity. The CE/D/Coimbatore has reported the following;

This area is situated between Seeranaickenpalayam and western Ghat, there is no margin in the nearby substations to cater the expected load growth. The above said areas are located in between Vadavalli, Coimbatore Corporation and Thudiyalur area along the foot hills of the western Ghat. The existing substations are feeding prime locations like Bharathiyar University, Tamil Nadu Agricultaral University and industrial units of Kanuvai and Somayapalayam area. Now, the Registrar, Bharathiyar University has given load requirement for a demand of 7 MVA in this area.

In addition, M/s. ELCOT has also proposed to establish IT center within the Bharathiyar University campus. Further, 2 nos of HT applications for a demand of 1.6 MVA is pending in this area. Enormous load growth is expected in the near future and also new Satellite townships are developing in and around Vadavalli, Bharathiyar University and Somayapalayam areas. Hence, the proposed and expected demand could not be effected in S.N.palayam 110 kV SS and Thudiyalur 110 kV SS. To feed the above areas, there is a need for new SS at perfect load centre.

Establishment of new 33 kV SS at Selvapuram and Kaleeswaranagar and establishment of 110/22-11 kV SS at Edayarpalayam have been included in the 11th master plan for which technical feasibility has been ascertained. The suitable land for these substations could not be able to identified. Further, introduction of 110/33 kV ratio at Coimbatore 110/11 kV SS to feed these above 33 kV SS is not possible since, there is no space available for erection of additional power transformers in view of proposed 230/110 kV SS at the premises of Coimbatore 110 kV SS.

Further, suitable lands are not available in the Selvapuram and Kaleeswaranagar area. Alternatively, a government poromboke land measuring an extent of 4.00 acres in Somayapalayam instead of Edayarpalayam has been found suitable. Therefore, in order to improve the voltage regulation of the above feeders, reduce line loss, to provide load relief to the existing substations, to accommodate the future load growth in and around Somayapalayam area and to new HT services, establishment of a new substation at Somayapalayam is very much essential.

Reduction in line loss:-

On establishing a new 110/22-11 KV SS at Somayapalayam, the feeder regulation details of the feeders from which loads are proposed to be transferred are detailed below;

SI.	Name of the feeder	C.L in	Volt.	Line loss in
No Name of the reeder		MVA	regn	LU
1.	22 kV Thudiyalur – Somayapalayam #	7.375	1.41%	0.203
2.	22 kV Thudiyalur – Kanuvai #	6.525	2.74 %	0.393
3.	11 kV S.N.palayam - Maruthamalai #	5.139	5.65 %	0.68
4.	11 kV S.N.Palayam - P.N.pudur #	4.836	3.15%	0.41

On establishing a new 110/22-11 KV SS at Somayapalayam, the savings in line loss will be 42.87 LU per annum ie, Rs 144.90 lakhs per annum.

Decaus of Power transformer Capacity proposed:

A load of 11.106 of 11 kV load and 25.5 MVA of 22 kV load is proposed to be transferred to the (proposed) Somayapalayam 110/22-11 kV SS from the following SS:-

- 1. S.N.palayam 110/11 kV SS 11.106 MVA of 11 kV connected load with anticipated peak of 7.404 MVA and
- 2. Thudiyalur 110/22 kV SS 25.5 MVA of 22 kV connected load with anticipated peak of 17 MVA

Hence, in order to cater an anticipated peak of 7.404 MVA on 11 kV side and 17 MVA on 22 kV side, it is proposed to install 1x25 MVA, 110/22 kV power transformer and 2x10 MVA,110/11 kV power transformers at the proposed SS. Initially the SS will be commissioned with one no. 10 MVA, 110/11 KV power transformer and 25 MVA, 110/22 kV power transformer and when the loading on the 10 MVA power transformer reaches 70% of its capacity, the second 10 MVA, 110/11 kV power transformer will be erected.

Feeding Arrangements;

Details of Source SS;

Ctunt	or source ss ,					
a.	Name of the substation	Othakkalmandapam 230/110 kV SS				
b.	230/110 KV auto transformer capacity	3x100				
c.	Peak reached in MVA	267.33				
d.	Proposed addition in MVA	45 MVA				
e.	Anticipated peak in MVA	312.33 MVA				
f.	Whether auto tr. capacity of the source SS is adequate:					
	Not adequate. In order to	avoid overloading, administrative				
	approval for establishment of 230/110 k	V SS at Karamadai has been accorded				
	vide B.P.(CH).No.566 dt 27.10.2007. Th	e erection works are under progress.				
	On commissioning of Karamadai 230	kV SS, the loading capacity of				
	Othakkalmandapam will be adequate.					

Details of the source feeder:

a.	Name of the feeder	110 KV Othakkalmandapam -				
	* * * * * * * * * * * * * * * * * * * *	Thudiyalur II				
b.	Size/Loading capacity of the conductor	Panther, 84 MVA				
C.	Present loading in MVA	91.28				
d.	Proposed addition in MVA	45				
e.	Anticipated load in MVA	136.28				
f.	Whether conductor size is adequate:					
	Not adequate. Administrative	approval for conversion of the existing				
	110 kV SC Coimbatore - Othakkalmand	apam line with Leopard conductor into				
	110 KV DC line on DC tower with Panther conductor, from loc 1-3 and 6B-83					
	has been accorded vide B.P(CH).No 540 dt 15.10.2007. Erection work is under					
11	progress. On completion of the above v	vork, Ukkadam 110 kV SS (3x16 MVA)				
	which is being fed by 110 kV Othakkalr	mandapam – Thudiyalur II line will be				
	transferred to 110 kV Othakkalmandapa	m - Coimbatore II. Afterwards the line				
	capacity will be adequate.					

DETAILS OF WORK:

- > Establishment of Somayapalayam 110/22-11 kV SS with 1x25 MVA, 110/22 kV power transformers and 2x10 MVA, 110/11 kV power transformers with associated equipments.
- > LILO of 110 kV Othakkalmandapam Thudiyalur line at Somayapalayam 110 kV SS for a distance of 6.5 kms.

LAND AVAILABILITY:

4 acres of Government poromboke land in Somayapalayam village has been identified for establishment of 110/22-11 kV SS. Formal concurrence for issuing the enter upon permit has been obtained from the District Collector/Coimbatore to carry out the work subject to payment of guideline value of Rs.14.60 lakhs. The land should be acquired within two months after getting administrative approval.

EXECUTIVE ENGINEER/MASTER PLAN (i/c)

DETAILED ESTIMATE FOR ESTABLISHMENT OF 110/22-11 KV SS WITH 1x25 MVA,110/22 KV POWER TRANSFORMER AND 2x10 MVA, 110/11 KV POWER

EMANUETEMER AT SOMAYAPALATATIN COMDATORE EDG/NORTH (Combatore

0	per	ati	on	ci	rcl	e)	١.
_	P			-		-	, .

	Operation circle).						
SI. No	DESCRIPTION	QTY	Rate in Lakhs	PER	Amount in Lakhs	Total in Lakhs	
1	CIVIL WORKS						
	Land Cost				14.600		
2	Control Room		,8	v.	24.610		
	Station yard & cable duct				5.000		
4	Lead Road				4.000		
5	Fencing / Compound Wall		8.0		5.000		
6	Water system				3.000		
					57.210	57.210	
1	Electrical works	1007 10000					
1	110 kV AB Switch with Earth blade	2 Nos	0.983	E	1.966		
2	110 kV AB switch w/o Earth blade	7 Nos	0.749	E	5.243		
3	110 kV SF6 breaker	2 Nos	8.078	E	16.156		
4	110 kV CTs (Single Phase)	6 Nos	1.744	E	10.464		
5	110 kV PTs (single phase)	3 Nos	1.219	E	3.657		
6	110 kV LAS (Single phase)	6 Nos	0.332	E	1.992		
7	22 kV AB switch	5 Nos.	0.160	E	0.800		
1	33 kV SF6/VCB (1LV+ 2fdr)	3 Nos.	4.53	E	13.590 3.636		
i	33 kV CTs(Single phase)	9 Nos.	0.404	E	0.534	_	
	22 kV PT	3 Nos	0.178	E	0.0840		
	22 kV LAS (Station type)	3 Nos. 6 Nos.	0.006	E	0.036		
	22 kV LAS (Distribution type)	10 Nos.	0.171	E.	1.710	i	
10000000	11 kV AB switch	6 Nos.	1.459	E	8.754		
	11 kV VCB (2LV+4 fdr) 11 kV CTs (Single phase)	18 Nos.	0.158	E	2.844		
	11 kV PT	3 Nos.	0.228	E	0.684		
	11 kV LAS (Station type)	6 Nos.	0.0213		0.128	2	
	11 kV LAS (Station type)	12 Nos.	0.0027		0.033		
	Plinth for breakers	11 Nos.	0.200		2.200		
	Earthing, Painting and Yard lighting				3.150		
	Control and relay panel						
21	Pr.Tr. GC. C&R Panel	2 No	2.617	Е	5.234		
	Pr.Tr. LV. C&R Panel	3 Nos	4.897		14.691		
	22 kV C&R (2 feeder) panel	1 No	3.122		3.122		
	11 kV C & R (2 feeder) panel	2 Nos	3.122	1	6.244		
22	Annunciator Panel(100 windows)	1 No	1.098	1	1.098		
	Control cable			Ls	5.000		
0.000	Fire fighting equipments		4,0	-	1.000		
	Scientific instruments				1.000		
	!				1.000		
1	T&P Furniture & Materials	1 11-	0.634	E	0.634		
	110 V DC Panel	1 No	2.71		5.420	(
	110 V, 300 AH Battery&Charger	2 sets	1.000		1.000	1	
	AC Panel	1 No	1.000		0.010		
30	P&T Phone				0.010		

DETAILED ESTIMATE FOR ESTABLISHMENT OF 110/22-11 KV SS WITH 1x7 MVA,110/22 KV POWER TRANSFORMER AND 2x10 MVA, 110/11 KV POWER TRANSFORMER AND 2x10 MVA, 110/

	Operation circle).						
SI. No	DESCRIPTION	QTY	Rate in Lakhs	PER	Amount in Lakhs	Total in Lakhs	
1	100 KVA, 11 kV/433 V Station Tr	1 No.	1.406	E	1.406		
32	Sub-total				124.519		
	Contingencies		,		1.245		
	Cost of Materials				125.765		
	Labour & Transport @15%				18.865		
	Total for materials and labour				144.629		
1	25 MVA,110/22 kV Pr.Tr	1 No	178.533	E	178.533		
	10 MVA,110/11 kV Pr.Tr	2 Nos	69.038	E	138.076		
1	Plinth, Labour & Transfort for Pr. Trs	3 loc	3.151	loc	9.453		
1	Earthing	3 loc	0.500	loc	1.500		
1	22 kV capacitor bank	2.4 mvar	9.581	mvar	22.994		
	11 kV capacitor bank	2.4 mvar	6.847	mvar	16.433		
	Sub-total				511.619		
43	Establishment & Supervision charges @	15%			76.743		
1	Total				588.361	588.361	
	110 kV structure	1 No	41.699	E	41.699		
	22 kV structure	1 No	3.75	E	3.750		
1	11 kV structure	1 No	1.883	E	1.883		
47	Erection of 110 kV DC line on DC	6.50 km	36.890	km	239.79		
	towers with Panther conductor (LILO						
	of 110 kV Othakkalmandapam -						
i	Thudiyaiur II feeder at						
48	Somavapalavam) 22 kV link line with 7/4.09 mm ACSR	5 kms	3.532	km	17.66		
	conductor						
49	11 kV link line with 7/4.09 mm ACSR	10 kms	3.696	km	36.96	341.737	
1	conductor						
50	Total Gross and Nett					987.31	

Executive Engineer/Master plan