

# GOVERNMENT OF ODISHA DEPARTMENT OF WATER RESOURCES

### **CATCHMENT AREA TREATMENT (CAT)**

FOR

#### KARAPANI IRRIGATION PROJECT



DIST: SUNDARGARH, ODISHA

Sundargarh January 2019 Executive Engineer IB Investigation Division Sundargarh



#### 1. Introduction

The Catchment Area Treatment (CAT) targets overall improvement in the environmental conditions of the region. All the activities are aimed at treating the degraded and potential areas of severe soil erosion. The plan provides benefits due to biological and engineering measures.

The CAT Plan would cover the following aspects:

- Identification of free draining catchment
- Assessment of Land Use, Soil, Slope in the catchment based on Remote Sensing (RS) /Geographic Information System (GIS) and Validation through field survey
- Erosion levels the watershed and prioritization of water sheds will be done by appropriate methods.
- As per the requirement of Ministry of Environment & Forests and Climate Change (MoEF & CC),
   Government of India, the treatment measures will be proposed for the area falling higher priority erosion categories. Both Engineering measures as well as Biological treatment measures will be proposed in the CAT plan.
- The cost of the administrative set up and mitigative measures will include recommendation from State Forest Department for all forest lands and from the Soil Conservation Department for non – forest land.

#### 2. Need

Reservoirs formed by dams on rivers are subject to sedimentation. The process of sedimentation embodies the sequential processes of erosion, entertainment, transportation, deposition and compaction of sediment. The study of erosion and sediment yield from catchments is of utmost importance as the deposition of sediment in reservoir reduces its capacity, and thus affecting the water availability for the designated use. The eroded sediment from catchment when deposited on streambeds and banks causes threading of river reach. The removal of top fertile soil form catchment adversely affects the agricultural production. Thus, a well-designed catchment area treatment plan is essential to ameliorate the above —mentioned adverse process of soil erosion.

The CAT plan highlights the management techniques to control erosion in the catchment area of a water resource project. The life span of a reservoir is greatly reduced due to erosion in the catchment

To Investigation Division

area. Adequate preventive measures are thus needed for the treatment of catchment for its stabilization against future erosion.

Quantifying soil erosion and reservoir sedimentation is necessary for prioritizing catchments for treatment and development of a suitable treatment mix. It is, therefore, also required that the effect of various treatments on controlling soil erosion are quantitatively known. River gauging data are the best information source for undertaking the above activities. As such data are not available for this catchment, so estimation procedure is adopted. At the present level of data availability and based on the past experience, **Sedimentation (Silt) Yield Index (SYI)** appears to be an acceptable parameter for use in catchment prioritization work.

SYI is calculated using an empirical formula. Based on the numerical value of SYI, catchments are categorized into five priority classes from Very High (SYI>1300) priority to Very Low (SYI<1000) priority. The method was proposed by All India Soil Survey and Land Use Planning (AISSLUP) currently known as Soil and Land Use Survey of India (SLUSI) based on several studies. The method has been used to prioritize catchments in India totaling in area of millions of hectares. It is reported that, the SYI procedure is reliable for determining priority watersheds. The empiricism in this method is manifest in the selection of unit area (mapping unit) and assigning an appropriate value of delivery ratio to it. SYI method is widely used because of the fact that it is easy to use and lesser data requirement. Moreover, it can applied to larger areas like sub watersheds etc.

#### 3. Methodology adopted

Database on natural resources, terrain conditions, soil type of the catchment area is a pre-requisite to prepare CAT plan. Various thematic maps were prepared and used in preparation of the CAT plan, in Geographic Information System (GIS) platform.

The methodology adopted for development of CAT plan for the project is as under:

- Catchment boundary delineation from Survey of India Topo sheets
- Watershed boundary form watershed Atlas of India and website of Soil and Land Use Survey
  of India (SLUSI) and the micro watershed boundary collected from Watershed Mission of
  Odisha
- Land use/Land cover map preparation from recent 5.8m resolution LISS-IV Multi Spectral Satellite image

Executive Engineers of the season of the sea

2

- Contour digitization from Survey of India OSM topo sheet and generation of slope map
- Soil map preparation from National Bureau of Soil Survey and Land Use Planning (NBSS&LUP)
- Assigning weightage value of mapping units based on slope, land use and soil texture and
   Delivery ratio based on distance from nearest stream
- Estimation of Soil Loss using Silt Yield Index
- Watershed Prioritization
- Selection of locations of treatment and Catchment Treatment (CAT) Plan
- Cost Estimate

Thematic data integration and erosion index modeling was done using relevant map layers in GIS.

Silt Yield Index (SYI) of various micro watersheds within the free catchment was estimated. Watershed management approach were proposed for optimal use of soil and water resources within the catchment with the broad objective of

- increasing infiltration into soil
- control excessive runoff
- manage & utilize runoff for useful purpose

#### 3.1. Brief Description of Karapani Dam

This project aims at construction of a 1312 M. long and 30.50 M. high earth dam having a central ogee gated spillway of 60.50 M. length. All the alternatives of dam axis have been explored and the present one has been approved by the Engineer-in-Chief, P & D, Orissa. The total catchment area at the dam site is 121.00 Sq. Km. The total annual inflow into the reservoir is 5061.80 Ha. M, corresponding to a 75 % dependable year. The project has an average water utilization of 71.86 % considering 29 years data. The earth dam is proposed to be of homogeneous section with provisions of vertical sand chimney to drain the seepage water through the filter drains and rock-toe.

The 605 M. long central spillway shall be ogee type & gated. The crest level of the spillway is 182.50 M. fitted with 4 Nos. of radial gates of 12m X 8m size. The spillway is designed to discharge maximum flood of 1240.00 Cumecs. The project shall provide irrigation to C.C.A of 3500 Ha. The project will irrigate 3325 Ha. in kharif and 2100 Ha, in rabi by means of two main canals. The length of left main canal is 12.00 Km. (approx.) and right main canal is 4.98 Km. Minors and Sub-minors' network shall be provided as per the requirement after detailed survey is done. Besides creating above irrigation potential, 20 % of the water



has reserved for riparian use at the downstream & upstream as per suggestion of Central Water Commission. The project is entirely in the state of Orissa and hence the question of interstate aspect does not arise. The Catchment of Karapani Irrigation project is enclosed at <a href="Plate-1">Plate-1</a>

### 3.2. Irrigation planning

The project comes under Lahunipara Block of Sundargarh district which is a hilly and drought prone area. The present land use practice and the traditional farming is primitive and continuing from generations. The modern methods of cultivation are yet to be practiced due to the erratic behavior of the monsoon. Paddy is the principal crop generally grown by the people of this locality. At present the area under cultivation is about 2734 Ha having very less yield. After completion of the project irrigation to an area of 3325 Ha. in Kharif and 2100 Ha. in Rabi with an annual irrigation of 5425 Ha shall be developed. Besides, the project will also provide drinking water and other riparian use at the downstream and upstream.

### 3.3. Main Canal distribution System

There are two main canals i.e. left and right of length 12 Km. and 4.98 Km. respectively. Both the canals shall be contour canals.

#### Land Levelling:


Since a large area of the ayacut is undulated, land levelling in the command area cannot be done. This activity shall be automatically undertaken by the beneficiaries of the command area after development of the irrigation facilities. Also, other beneficiary-oriented schemes can be extended by the D.R.D.A at subsidized rates.

### Cropping Pattern and crop water requirement

Before irrigation, paddy is the main crop generally grown by the people of this locality. Due to uncertainty of rainfall in the ayacut neither any high yielding variety paddy nor any cash crops are cultivated. After creating assured irrigation high yielding paddy as well as crops like vegetables, groundnuts, maize and other oilseeds will be cultivated. State Agricultural Department provides technical know-how as well as advice for better crop yields. Crop water requirement based on statement of State Agriculture Department for different months have been calculated as per guidelines of Ministry of Agriculture.

to Investigation Division

4



#### 3.4. Reservoir Stimulation Study

Period of Simulation is 1977-78 to 2005-06 (hydrological year). First of all, sediment analysis is carried out with reference to I. S. Code No. IS-5477 (part I)-1969 (Methods for fixing the capacities of Reservoirs) for 50 years and 25 years. Revised Area Capacity are computed with assumption of new zero elevation. Finally, new zero elevation with reference to 50 year's silt loads is 171.65 M. and in case of 25 year's silt load is 170.50 M. Hence D.S. L is fixed at an elevation of 174.00M. Evaporation loss data is adopted from Rukura medium irrigation project report already approved by the C.W.C. F. R.L is finalized by hit & trial at an elevation of 190.50 M. which will take care to supply the irrigation needs to an area of 3500 Ha. of C.C.A. For simulation studies, 25 years sedimented revised area capacity curves are used. Simulation studies are carried for 29 years and the percentage of success is 86.20 %. The percentage of water utilization is 71.86 %.

#### Water Account Statement

The Water Account statement reflects the percentage of utilization of water potential maximum up - to 71.86 %. The project aims at maximum utilization of water by providing irrigation up - to 95 % of C.C.A. in kharif, 60 % of C.C.A. in rabi and 155 % of C.CA. as annual irrigation.

Table-1: Abstract of forest land involved in Dam base & Reservoir

SI No.	Name of the Village	Forest Area (Ha.)	Non-Forest Area (Ha.)	Total Area (Ha.)
1	Angul	14.504	44.553	59.057
2	Sulavadihi	27.867	116.293	144.160
3	Barghat	3.977	10.195	14.172
4	Dhanijam	11.218	65.297	76.515
5	Ranja	18.604	97.333	115.937
6	Lunga RF	3.626	0.000	3.626
7	Kundeibera RF	2.616	0.000	2.616
	Total	82.412	333.672	416.084

Table-2: Abstract of forest land involved in Canal

SI No.	Name of the Village	Forest Area (Ha.)	Non-Forest Area (Ha.)	Total Area (Ha.)
1	Barghat	0.130	2.185	2.315
2	Dhanijam	0.652	1.222	1.874
3	Haldikudar	1.696	2.246	3.942
4	Jadibahal	0.275	6.625	6.900



SI No.	Name of the Village	Forest Area (Ha.)	Non-Forest Area (Ha.)	Total Area (Ha.)
5	Kantakudar	5.779	2.934	8.713
6	Sadhubahal	2.902	2.529	5.431
7	Khajurinali	0.000	2.234	2.234
8	Mahuldihi	4.508	10.603	15.111
9	Sialikudar	0.271	5.953	6.224
10	Sihidiha	2.614	6.775	9.389
11	Kundeibera RF	1.718	0.000	1.718
	Total	20.545	43.306	63.851

The FRL of this project has been kept at 190.50 M. MWL & FRL are the same as no difference has been allowed for flood lift. By creation of the reservoir total 400.59 Ha. of land will be submerged out of which 78.97 Ha. (approx.) is forest land.


#### 4. Thematic Map Generation


As mentioned in the methodology, various thematic layers like catchment, watershed, drainage, contour, slope, land use, soil were prepared in Geographic Information System (GIS) platform using satellite image, OSM Sol Topo Sheet and other secondary source data. For seamless integration of different thematic layers and interactive spatial analysis, the themes were generated UTM (Universal Transverse Mercator) projection system. This projection system is used in the recent publication Open Series Map (OSM) of Sol and is also suggested in National Map Policy. Datum used for the projection is WGS 1984 and Zone is UTM 44 North.

#### 4.1.Catchment and Watershed map

The catchment boundary of Karapani dam was delineated from Sol topo sheets F45N1 & F45N2, looking at the contours and drainage. The contour and drainage map of the project is enclosed at *Plate-2*. Since the catchment is very small, it was decided to prepare the CAT plan at Micro Watershed level instead of Watershed level. The micro watersheds are prepared using the information available in Watershed Atlas of India, website of Land Use Survey of India (SLUSI) and the micro watershed boundary collected from Watershed Mission of Odisha. The micro watershed map is enclosed at *Plate-3*.







#### 4.2. Slope Map

The Slope map was derived from contours shown on Sol topo sheet. After marking the catchment area, all the contours and spot heights shown on the topographical maps were mapped with 'Z' value (height above MSL in m). Since the area is mostly flat and contours are wide spaced, the spot heights collected in DGPS (differential GPS) during ground truthing of land use were also used as input.

A surface was created using the elevation values stored in the form of contours or points. A Digital Terrain Model (DTM) of the area was then prepared, which was used to derive a slope map. The slope was divided in classes of slope percentages. The areas falling under various standard slope categories have been tabulated in Table-3 and the counter & slope map is enclosed at Plate-4 & 5 respectively.

Table-3: Area falling under different slope category

Slope Category	Slope (%)	Area in Km <sup>2</sup>	Area in %
Gently Slopping	0-15	18.24	16.46
Moderately sloping	15-30	6.99	6.31
Strongly sloping	30-45	10.18	9.19
Steeply sloping	45-60	69.11	62.37
Very steeply sloping	60-75	6.28	5.67
Total		110.80	100

#### 4.3. Land Use/ Land Cover Map

Land Use map was prepared from recent 5.8m resolution LISS-IV Multi Spectral satellite image collected from National Data Centre of National Remote Sensing Centre (NRSC), Hyderabad. Details of Satellite Image are given bellow.

Satellite:

IRS-P6

Sensor: LISS-IV MX (Multi Spectral)

Date of Pass:

1st April 2015

Path:


103

Row:

057

The image was geo-referenced using the common Ground Control Points (GCP) of Survey of India topographical sheets and satellite image with the help of feature registration techniques in standard








image processing software. The satellite image map is enclosed at <u>Plate-6</u>. As the catchment area is very small, visual interpretation of the geo-referenced satellite data was done by qualified professionals using standard enhancement techniques followed by detail ground truthing to enhance the quality of image interpretation. The classified land use map of the catchment area is depicted in <u>Table-4</u> and the map is enclosed at <u>Plate-7</u>.

Table-4: Area falling under different Land Use

Description	Area in Km <sup>2</sup>	Area in %
Open Forest	83.97	75.785
Wasteland with scrub	9.05	8.168
Cultivation	17.69	15.966
Plantation	0.09	0.081
Total	110.80	100.00

#### 4.4.Soil Map

Soil map was prepared by digitizing the soil map collected from National Bureau of Soil Survey and Land Use Planning (NBSS & LUP) for Odisha and undivided Madhya Pradesh. The soil map is depicted at <u>Plate-8</u> and catchment area coming under different soil category is depicted in <u>Table-5</u>.


Table-5: Area falling under different soil category


Code	Description	Texture	Area in km²	Area in %
1	Deep, well drained, fine-loamy soils with loamy surface, moderate erosion and moderate stoniness	Loamy	18.25	16.47
2	Moderately deep, well drained fine loamy soils with loamy surface and moderate erosion	Loamy	3.48	3.14
3	Moderately deep, well drained, gravelly loamy soils with loamy surface and severe erosion	Loamy	8.14	7.35
4	Moderately shallow, well drained, gravelly loamy soils with loamy surface and moderate erosion	Loamy	80.93	73.04
	Total		110.8	100.00


### 5. Estimate of Soil Loss intensity using Silt Yield Index (SYI) method

The Sedimentation (Silt) Yield Index Model (SYI), considering sedimentation as product of erosivity, erodibility and arial extent was conceptualized in the AISLUS, as early as 1969 and has been in operational use since then to meet the requirements of prioritization of smaller hydrologic units. The erosivity determinants are the climatic factors and soil and land attributes that have direct or reciprocal bearing on the unit of the detached soil material.









The Silt Yield Index (SYI) is defined as the Yield per unit area and SYI value for hydrologic unit is obtained by taking the weighted arithmetic mean over the entire area of the hydrologic unit by using suitable empirical equation.

In SYI methodology, each Erosion Intensity Unit (EIU) is assigned a weightage value. When considered collectively, the weightage value represents approximately the relative comparative erosion intensity. The slope, soil and land use theme of the catchment were combined using union tool in GIS and EIU were formed using different combination of soil, slope and land use categories.

SYI was calculated using following empirical formula:

$$SYI = \frac{\sum (Ai \times Wi \times Di) \times 100}{AW}$$

Ai = Area of i<sup>th</sup> unit (EIU) Wi = Weight:

Di = Delivery Ratio of the i<sup>th</sup> unit EIU

[ where i = 1 to n (n is the No. of EIU)]

Wi = Weightage value of the i<sup>th</sup> unit EIU Aw = Total area of Micro-watershed

#### Weightage Value (W)

Weightage Value is a combination of two factors K and X. A basic factor of K = 10 was used in determining the weightage values. The value of 10 indicates a static condition of equilibrium between erosion and deposition. Any addition to the factor K = 10 was used in determining the weightage values. The value of 10 indicates a static condition of equilibrium between erosion and deposition. Any addition to the factor K = 10 was used in determining the weightage values.

#### **Delivery Ratio (D)**

Delivery ratios were assigned for each of the erosion intensity unit. The delivery ratio suggests the percentage of eroded material that finally finds entry into reservoir. Area of each EIU in each micro watershed was then estimated.

Delivery ratios were assigned to all erosion intensity units depending upon their distance from the nearest stream. The criteria adopted for assigning the delivery ratio are as follows:

Nearest Stream	Delivery Ratio
0 - 0.9 km	1.00
1.0 - 2.0 km	0.95
2.1 - 5.0 km	0.90
5.1 - 15.0 km	0.80
15.1 - 30.0 km	0.70

Executive Engineer or

1.0 km, 2.0 km, 5.0 km, 15.0 km and 30.0 km buffers were created around the main stream and reservoir using GIS. EIUs falling in different buffer zone were assigned the Delivery ratio of the respective buffer zone.

Prioritization of Micro Watershed based on SYI findings

The objective of the SYI method is to prioritize micro watershed in a catchment area for treatment. For prioritizing the micro watersheds, these are to be divided in to different categories based on their SYI. The SYI values for classification of various categories of erosion intensity rates are depicted below

Priority categories	SYI Values
Very high	> 1300
High	1200-1299
Medium	1100-1199
Low	1000-1099
Very Low	<1000


The micro watershed wise SYI and category of erosion is depicted in <u>Table-6</u>.


Table-6: Soil Erosion Priority Category of Micro Watersheds

SL	MWS Code	SYI	Priority
1	4H1C2G1C	1148	Medium
2	4H1C2H1A	1215	High
3	4H1C2I1B	1216	High
4	4H1C2G2C	1258	High
5	4H1C2H1B	1265	High
6	4H1C2I2A	1266	High
7	4H1C2I1A	1267	High
8	4H1C2G2B	1292	High
9	4H1C2G1B	1295	High
10	4H1C2H2C	1315	Very High
11	4H1C2G1A	1332	Very High
12	4H1C2H2D	1354	Very High
13	4H1C2H2A	1358	Very High
14	4H1C2G2A	1375	Very High
15	4H1C2H2B	1376	Very High

Area under very high categories is proposed to be treated at the project. A base map showing land use, reserve forest boundary, slope, major drains and priority watershed is enclosed at <u>Plate-9</u> for micro planning of the catchment area treatment plan as the step areas are more prone to soil erosion, looking at the land use and topography 4H1C2H2A, 4H1C2H2B, 4H1C2H2C and 4H1C2H2D micro watersheds finally selected for treatment which is directly draining to the Karapani river. The detail map for preparation of treatment plan is enclosed at <u>Plate-10</u>. The topographic map, drainage







and contour map and land use and slope map of the sub watershed is enclosed at <u>Plate-11, 11b</u> and <u>11c</u> respectively.

#### 7. Demography of the watershed

The village map of the sub watersheds is enclosed at <u>Plate-12</u>. The demography of the villages of Micro Watershed 4H1C2H2A, 4H1C2H2B, 4H1C2H2C and 4H1C2H2D as per Census 2011 are depicted below.

Table-7: Demography of Watersheds as per Census 2011

All areas in Hectore

						Name of Street		×
Name of the village	Population	Male	Female	SC	ST	Literate	Worker	
Badjal	699	359	340	3	673	192	388	
Fuljhar	2052	1108	944	80	172	726	716	
Uskuda	649	325	324	0	558	154	375	
Ranja	270	137	133	0	270	91	145	
Talaginia	610	306	304	0	590	162	281	

#### 8. Catchment Area Treatment (CAT) Plan


Following Engineering and Biological measures are planned for the catchment area treatment depending upon the requirement and suitability:


- a. Biological measures
  - Assisted Natural Regeneration
  - Block Plantation/Afforestation
  - Fodder land development
- b. Engineering measures (Water Harvesting Structures)
  - Loose boulder wall-gully plugging in small hilly streams
  - Stone masonry check dams in major drains
- c. Others
- Awareness campaign for farm management, control grazing etc.
- Drinking Water facilities to Villagers


As most of the area is agricultural land (81.92%), awareness campaign will be done for farm management (negatives of burning farm residuals, adoption of proper cropping pattern etc.), digging of farm pond, controlled grazing in graze land, etc.

Executive Engineer Division

11







#### 8.1 Assisted Natural Regeneration

Assisted Natural regeneration is suggested in 50ha in open forests available within the watersheds. The sites to be treated are depicted in <u>Plate-13</u>. The detail estimate is depicted at <u>Annexure-1</u>.

#### 8.2 Block Plantation/Afforestation

The village wise revenue forest and govt. land is depicted in the below.

Table-8: Availability of Govt. and forest land

All areas in Ac. Name of the village **Govt Land** Forest Land Gochar Land Badjal 239.49 36.2 11.4 Fuljhar 3491.78 207.36 76.14 Uskuda 4892.3 0 0 Ranja 1044.55 257.57 30 Talaginia 1566.79 260.02 89.92

As 260.02 ha of forest land is available in Talaginia villages, but there is no forest growth, it is proposed to block plantation of 75 hectors in the village. The detailed estimate is enclosed at **Annexure-2.** 


#### 8.3 Fodder land development

To minimize the pressure on forest for grazing, it is suggested to develop fodder land in the watershed.

Table-9: Availability of Gochar land

Name of the village	Population	Gochar land
Badjal	699	11.4
Fuljhar	2052	76.14
Uskuda	649	0
Ranja	270	30
Talaginia	610	89.92





Looking at the availability of Gochar land and population, it is proposed to develop 4 blocks (of 10 ha each) of fodder land development in each villages of watersheds except Fuljhar & Talaginia. The detail estimate is given at <u>Annexure-3</u>.

#### 8.4 Loose boulder wall-gully plugging in small hilly streams

Gully erosion, including ephemeral gully erosion, refers to the cutting of narrow channels resulting from concentration of sheet and rill flow of runoff water. Ephemeral gullies are small channels of approximately 3 to 12 inches deep. Gullies may be one to several feet deep. Gully erosion occurs when rill erosion is neglected. The tiny grooves develop into wider and deeper channels, which may assume a huge size. This state is called 'gully 'erosion. Gullies are the most spectacular evidence of the destruction of soil. The gullies usually deepen and widen with every heavy rainfall. They cut up large fields into small fragments and, in course of time, make them out of shape for cultivation.

Gully plugging work is required for reduction of runoff velocities within permissible limits and for controlling gully erosion of micro-watersheds. Appropriate gully plugging works would be selected from brush wood check dams, palisading works, gabion structures, sunken pits, etc. A provision is kept for 40 gullies plugging in the streams. The typical Estimate of Gully Plugging is depicted at <u>Annexure-4.</u>

#### 8.5 Earthen Check Dam with concrete core Wall – in major drains


Check dams' range in size, shape and cost. It is possible to build them out of easily available materials and even at a very little cost. Decision of building such a dam depends on its location. Essentially a check dam has an earthen dam and masonry spillway.

It cuts the velocity and reduces erosive activity, the stored water improves soil moisture of the adjoining area and allows percolation to recharge the aquifers Spacing between the check dams should be such that water spread of one should be beyond the water spread of the other Height depends on the bank height, varies from 1m to 3m and length varies from less than 3m to 10m. A provision is kept for 20 Masonry Check in the streams. The typical Estimate of earthen check dam with concrete core is depicted at <u>Annexure-5</u>

The locations of proposals for all treatments other than ANR activities are depicted in <u>Plate-14</u>. The detail year wise cash flow estimate is depicted at <u>Annexure-6</u>.

Literature Engineer on

13



### 9. Cost Estimate

SL	Item	Rate in Rs.	Unit	Physical	Financial (Rs, in Lakh)
Bic	ological Measure				
1	Enrichment of Plantation/Re-densification (ANR with gap plantation @600 plants)	70,485.24	На	50	35.24
2	Afforestation including maintenance (Block Plantation @ 1600 plants/ha (6 months seedlings)	1,73,871.39	На	75	130.40
3	Grass land (Fodder land) development including grass reserves over 40.0ha (10 ha one unit)	13,00,000	На	40	52.00
Eng	gineering Measure				5,4757
4	Loose Boulder wall gully plugging	4771.53	No	40	1.91
5	Earthen Check Dam with Concrete Core	2,47,253	No	20	49.45
Oth	ners				
6	Awareness campaign for farm management, control grazing etc.	-	-	-	5.00
7	Drinking Water facilities and socio- economic development to Villagers	-	-	-	10.00
	Total				284.00

Total cost of Biological, Engineering & other measure a silt observation at site

Rs. 284.00 lakh


Administrative Expenditure/ Monitoring & Supervision @10%

Rs. 28.4 Lakh

Total

Rs. 312.40 Lakh

Charling Engineeries



## COST NORM FOR AIDED NATURAL REGENERATION (ANR) @ 600 PLANTS PER HECTARE Wage rate 298.00/Day.

SI no.	Items of work	Preferable Period of Execution OTH YEAR	Labour in Mandays	Labour cost	Material cost	Total cost in RS
1	Survey, Demarcation and Pillar Posting, GPS Reading with mapping	Nov/Dec	2	596	0	596
2	Site Preparation	Nov/Dec	2	596	0	596
3	Silvicultural Operation including clearance of weed, climber cutting, high stump cutting, singling of shoots etc.	Jan/Feb	5	1490	0	1490
4	Nursery cost (6 months old seedling) part @ Rs.12.43/-seedling (Rs.8.67 in 0th year + Rs.3.76 in 1st year) for 660 seedlings (600+60)	Jan-Mar	16.5	4917	1102	6019
5	Contingency and Unforeseen Expenditures			0	198	198
		SUB TOTAL	25.5	7599	1300	8899
6	Monitoring & Supervision charge 5 % of the					444.95
		RAND TOTAL	25.5	7599	1300	9343.95
		1ST YEAR				
1	Nursery cost (6 months old seedling) balance @ Rs.3.76 for 660 seedlings	Apr-June	8	2384	241.5	2625.5
2	Pitting 30 cm cube size	Feb/Mar	18	5364	0	5364
3	Carriage and planting including casualty replacement	Jul/Aug	15	4470	0	4470
4	Complete weeding, Soil working, Manuring	Aug/Sep	18	5364	0	5364
5	Cost of Vermi compost @ 200 gms/plant @ Rs.20/-per kg =Rs.2400.00 and Granúlar Insecticide 5 gms/plant @ Rs.80/- per kg= Rs.240.00	Aug/Sep	0	0	2640	2640
	Cost of Chemical fertiliser					
6	(a) Urea 70 gms/plant in two subsequent doses@ Rs.6/-per kg Rs.252.00	Jul/Aug	0	0	972	972
	(b) NPK 50 gms/plant @ Rs.24/- per kg= Rs.720.00 as basal dose					
7	Fireline Tracing and Inspection Path	Feb/Mar	3	894	0	894





	the total cost	RAND TOTAL	14	4172	0	4380.6
5	Monitoring & Supervision charge 5 % of					208.6
		SUB TOTAL	14	4172	0	4172
4	Watch & ward (whole year)	Apr-Mar	7	2086	0	2086
3	Fireline Tracing and Inspection Path	Feb/Mar	1	298	0	298
2	Soil working	Aug/Sep	3	894	0	894
1	Complete weeding and cultural operations	Aug/Sep	3	894	0	894
		3RD YEAR		0.000		
	<u>'</u>	RAND TOTAL	31	9238	3362.8	13230.84
9	Monitoring & Supervision charge 5 % of the total cost					630.04
	les v	SUB TOTAL	31	9238	3362.8	12600.8
8	Expenditures		0	0	193	193
111	Contingency and Unforeseen					
7	Watch & ward (whole year)	Apr-Mar	7	2086	0	2086
6	Soil Conservation Measures (Renovation of staggered trenches etc.)	Sep/Oct	8	2384	0	2384
5	Fireline Tracing and Inspection Path	Feb/Mar	1	298	0	298
	60 plants 300 gms@ Rs.80/-per kg=Rs.24.00					
4	(a) Vermicompost 200gms/plant Rs.20/- per kg=Rs.2400.00 (b) Granular Insecticides 5 gms/plant for	-Sep/Oct	0	0	2424	2424
	Cost of Fertiliserand insecticide	эсру ост	- 0	1700		1700
3	operations Soil working and manuring	Sep/Oct Sep/Oct	6	1788 1788	0	1788 1788
1	seedling, carriage and planting  Complete weeding and cultural	Jul/Aug	3	894	745.8	1639.8
	Casualty Replacement including cost of	ZNU YEAK		T	Г	
		RAND TOTAL  2ND YEAR	104	30992	4207	36958.5
12	Monitoring & Supervision charge 5 % of t		404	20000		1759.5
		SUB TOTAL	104	30992	4207	35199
11	Contingency and Unforeseen Expenditures		0	0	353	353
10	Watch & ward	Aug-Mar	7	2086	0	2086
9	Soil Conservation Measures (Staggered trenches of dimension 2 m X 0.5 m X0.5 m @ 60 nos per ha) or its equivalent	Sep/Oct	20	5960	0	5960
8	silvicultural Operation involving clearance of weeds, cutting of climbers, singling of shoots etc	Sep/Oct	15	4470	0	4470





		4TH YEAR				
1	Fireline Tracing and Inspection Path	Feb/Mar	1	298	0	298
2	Watch & ward and cultural operations	Apr-Mar	2	596	0	596
	SUB TOTAL		3	894	0	894
3	Monitoring & Supervision charge 5 % of the total cost					44.7
	GRAND TOTAL		3	894	0	938.7
		5TH YEAR				
1	Fireline Tracing and Inspection Path	Feb/Mar	1	298	0	298
2	Watch & ward and cultural operations	Apr-Mar	2	596	0	596
		SUB TOTAL	3	894	0	894
3	Monitoring & Supervision charge 5 % of the total cost					44.7
	(	RAND TOTAL	3	894	0	938.7
		6TH YEAR				
1	Fireline Tracing and Inspection Path	Feb/Mar	1	298	0	298
2	Watch & ward and cultural operations	Apr-Mar	2	596	0	596
		SUB TOTAL	3	894	0	894
3	Monitoring & Supervision charge 5 % of the total cost					44.7
		GRAND TOTAL	3	894	0	938.7
		7TH YEAR				***************************************
1	Fireline Tracing and Inspection Path	Feb/Mar	1	298	0	298
2	Watch & ward and cultural operations	Apr-Mar	2	596	0	596
		SUB TOTAL	3	894	0	894
3	Monitoring & Supervision charge 5 % of the total cost					44.7
		RAND TOTAL	3	894	0	938.7
		8TH YEAR				
1	Fireline Tracing and Inspection Path	Feb/Mar	1	298	0	298
2	Watch & ward and cultural operations	Apr-Mar	2	596	0	596
		SUB TOTAL	3	894	0	894
3	Monitoring & Supervision charge 5 % of the total cost					44.7
		GRAND TOTAL	3	894	0	938.
		9TH YEAR				
1	Fireline Tracing and Inspection Path	Feb/Mar	1	298	0	298
2	Watch & ward and cultural operations	Apr-Mar	2	596	0	596
2						





J	the total cost					77./
	GRAND TOTAL		3	894	0	938.7
		10TH YEAR				
1	Fireline Tracing and Inspection Path	Feb/Mar	1	298	0	298
2	Watch & ward and cultural operations	Apr-Mar	2	596	0	596
		SUB TOTAL	3	894	0	894
3	Monitoring & Supervision charge 5 % of the total cost					44.7
		GRAND TOTAL	3	894	0	938.7
		ABSTRACT				
SI.	Year	No. Person Day	Labour cost @298.00/- per day	Material cost	Monitorin g & Supervisi on charge 5 % of the total cost	Total cost in (Rs)
1	Oth year	25.5	7599	1300	444.95	9343.95
2	1st year	104	30992	4207	1759.95	36958.95
3	2nd year	31	9238	3362.8	630.04	13230.84
4	3rd year	14	4172	0	208.6	4380.6
5	4th year	3	894	0	44.7	938.7
6	5th year	3	894	0	44.7	938.7
7	6th year	3	894	0	44.7	938.7
8	7th year	3	894	0	44.7	938.7
9	8th year	3	894	0	44.7	938.7
10	9th year	3	894	0	44.7	938.7
11	10 <sup>th</sup> year	3	894	0	44.7	938.7
	Tota	195.5	58259	8869.8	3356.44	70485.24

Forest Range Officer Kullposh

Obleena

#### COST NORM FOR BLOCK PLANTATION @1600 PLANTA PER HECTARE (6 month old seedling) Wage Rate @ R.s. 298/- per day

SI. No	Items of work	Preferable period of execution	Labour in Mandays	cost (Rs)	Material cost (Rs)	Total cost (Rs)
1	2 OTH YEAR (ADVANCE WORK) F	3 DE DI ANTINIO	4 CODEDATIO	5	6	7
1	Survey, demarcation and pillar posting	Nov/Dec	2	596	0	596
2	Site preparation	Nov/Dec	12	3576	0	3576
3	Alignment and stacking of pits	Jan/Feb	2	596	0	596
4	Digging of pits (30 cm cube)	Feb/March	40	11920	0	11920
_	Nursery cost (6 months old seedling ) part @Rs. 12.43/-	resylviaren	40	11320		11520
	seedling (RS.8.67 in 0 <sup>th</sup> year + Rs.3.76 in 1 <sup>st</sup> year) for 1760					
5	seedlings (1600+160)	lan March	44	13112	2939	16051
3	Total	Jan-March	100	29800	2939	16051 <b>32739</b>
6	Monitoring & Supervision charge 5% of the total cost		100	29800	2939	1636.95
0	Grand Total		100	29800	2939	34375.95
	1ST YEAR/PLAN	ITING VEAD	100	29800	2939	34375.95
	Nursery cost (6 months old seedling ) balance @Rs.3.76/-	I ING TEAK				T
	for 1760 seedlings	Apr-June	21.5	6407	593	7000
-	101 1700 Securings	Aprisure	21.3	0407	333	7000
8	Fencing For an average of 250 meters/ha @Rs.76.80/- per	May/June	38		8560	
0	meter for bamboo twigs and bamboo thorn fencing	iviay/Julie	36	11324	8300	19884
-	Carriage & planting, Casualty Replacement and application			11324		13664
9	of insecticides, manure etc.	Jul/Aug	21	6258	0	6258
	Cost of insecuciae and fertilizer (a)NPK	Jul/Aug	21	0238	0	0238
	@50 gms/plant as basal dose = 80kg @ Rs.24 / -per kg =Rs.1920.00 (b) Urea @					
10	70 gms/plant in two subsequent doeses @ Rs.6/-per kg= Rs.672.00 (c)	Jul/Aug			3232	
	Granular insecticide(Themet, Forate etc.) @5 gms/plant@Rs.80-					
11	/per kg= Rs.640.00	A /C	-	0	0	3232
	1st weeding (complete weeding) Manuring Urea 35 gm	Aug/Sep	7	2086	0	2086
	2nd Weeding (complete weeding)	Aug/Sep	5	1490	0	1490
13	Soil working (50 cms. Radius around plants) & manuring Urea	Sep/Oct	5	1490	0	1490
1	358ms per plant	Sep/Oct	7	2086	0	2086
-	Soil conservation measures in the form of straggerd	оор, ост				
15	trenches of size 2 mx0.5 m x0.5 m@ 30 nos per ha	Sep/Oct	10	2980	0	2980
16	Fire line tracing & inspection path	Feb/March	3	894	0	894
17	Watch&Ward	Aug/March	7	2086	0	2086
-70.0	Total	,g,	124.5	37101	12385	49486
18	Monitoring & Supervision charge 5% of the total cost					2474.3
	Grand Total		124.5	37101	12385	51960.3
	2ND YEAR MA	INTENANCE				
19	Casualty replacement ( 10 % ) with Nursery cost	Jul/Aug	4	1192	1988.8	3180.8
20	Weeding (complete weeding)	Sep/Oct	6	1788	0	1788
	Cost of fertilizer (NPK @70 gms/plant) ( Rs.24/-per kg &					
21	Insecticide @5 gms/plant for 160 plants 800 Gms @ Rs.80/ per kg)	Sep/Oct		0	2752	2752

The locality of Engineer Christics

Ciblecate

Forest Range Officer

Kullposh

22	Repair and maintenance of Bamboo fence including material cost	May/June	20	5960	5080	11040
23	Sol working (50 cms. Radlus around plants)	Oct/Nov	7	2086	0	2086
24	Application of fertilizer & insecticide	Sep/Oct	4	1192	0	1192
25	Fire line tracing (2 m wide fire line over 400 m long)	Feb/March	3	894	0	894
26	Watch & Ward	Apr-March	15	4470	0	4470
	Total		59	17582	9820.8	27402.8
27	Monitoring & Supervision charge 5% of the total cost					1370.14
	Grand Total		59	17582	9820.8	28772.94
	3RD YEAR MA	INTENANCE				
28	Weeding and application of fertilizer	Aug/Sep	7	2086	0	2086
29	Cost of fertilizer (NPK @ s0 gms/plant) 1960 Rs.24/-per kg			0	1920	1920
30	Repair and maintenance of Bamboo fence including material cost	May/June	20	5960	1000	6960
	Soil working (50 cms. Radius around plants) & application of					
31	fertilizer	Oct/Nov	7	2086	0	2086
22	Fire line tracing (2 m. wide fire line over 400 m length)& cultural	- 1/14				
32	operation	Feb/March	3	894	0	894
33	Watch& Ward	Apr-March	15	4470	0	4470
	Total		52	15496	2920	18416
34	Monitoring & Supervision charge 5% of the total cost					920.8
	Grand Total		52	15496	2920	19336.8
_	4TH YEAR MA	INTENANCE				
35	Fire line tracing (2 m. wide fire line over 400 m length)& cultural operation	Feb/March	3	894	0	894
36	Watch& Ward	Apr-March	15	4470	0	4470
30	Total	Apr-iviarch	18	5364	0	5364
37	Monitoring & Supervision charge 5% of the total cost	<del>                                     </del>	10	5504	U	268.2
37	Grand Total		18	5364	0	5632.2
	5TH YEAR MA	INTENANCE	10	3304		3032.2
_	Fire line tracing (2 m. wide fire line over 400 m length)& cultural	INTENANCE		T T		
38	operation	Feb/March	3	894	0	894
	Watch& Ward	Apr-March	15	4470	0	4470
	Total		18	5364	0	5364
40	Monitoring & Supervision charge 5% of the total cost					268.2
	Grand Total		18	5364	0	5632.2
	6TH YEAR MA	INTENANCE		1		
1	Fire line tracing (2 m. wide fire line over 400 m length)& cultural	Ī ī		T		
٠1	operation	Feb/March	3	894	0	894
42	Watch& Ward	Apr-March	15	4470	0	4470
	Total		18	5364	0	5364
43	Monitoring & Supervision charge 5% of the total cost					268.2
	Grand Total		18	5364	0	5632.2
	7TH YEAR MA	INTENANCE				
	Fire line tracing (2 m. wide fire line over 400 m length)& cultural					
44	operation	Feb/March	3	894	0	894
45	Watch& Ward	Apr-March	15	4470	0	4470
_	Total		18	5364	0	5364
46	Monitoring & Supervision charge 5% of the total cost		NAME OF THE OWNER OWNER OF THE OWNER OWNE			268.2
	Grand Total		18	5364	0	5632.2





47	Fire line tracing (2 m. wide fire line over 400 m length)& cultural operation	F=1-/0.1		0.5.1	75	on contract on the
	Watch& Ward	Feb/March	3	894	0	894
40	Total	Apr-March	15	4470	0	
49	(C) -		18	5364	0	
49	Monitoring & Supervision charge 5% of the total cost					268.2
	Grand Total		18	5364	0	4470 5364 268.2 5632.2 894 4470 5364 268.2 5632.2 7otal co. (Rs) 34375.9 51960.3 28772.9 1936.8 5632.2 5632.2 5632.2 5632.2 5632.2
_	Fire line tracing (2 m. wide fire line over 400 m length) & cultural	INTENANCE				
50	operation	F =  - /0.4  -	_			
51	Watch& Ward	Feb/March	3	894	0	
	Total	Apr-March	15	4470	0	
52	Monitoring & Supervision charge 5% of the total cost		18	5364	0	
32	Grand Total		1000000	-2000000000		
_	D. DESTANDON DESTANDA DE CONTROL		18	5364	0	5632.2
_	Fire line tracing (2 m. wide fire line over 400 m length)& cultural	INTENANCE				
53	operation (2 m. wide fire line over 400 m. length)& cultural	Fob/84	_	001		
54	Watch& Ward	Feb/March	3	894	0	
54	Total	Apr-March	15	4470	0	1,000,000
55	particular managers		18	5364	0	
33	Monitoring & Supervision charge 5% of the total cost  Grand Total					
			18	5364	0	5632.2
_	ABSTRA	ACT				
			Labour	Materia	Monitoring &	
SI.	YEAR	No. Person	cost @	I cost	Supervision	Total cos
No		Day	I RS.298/- I		charge 5%	(Rs)
			per day	(Rs)	of the total	
					cost	
1	Oth year	100	29800	2939	1636.95	34375.95
2	1st year	124.5	37101	12385	2474.3	51960.3
3	2nd year	59	17582	9820.8	1370.14	28772.94
4	3rd year	52	15496	2920	920.8	
5	4th year	18	5364	0	268.2	
6	5th year	18	5364	0	268.2	
7	6th year	18	5364	0	268.2	
8	7th year	18	5364	0	268.2	
9	8th year	18	5364	0	268.2	
10	9th year	18	5364	0	268.2	
<u>1</u>	10th year	18	5364	0	268.2	5632.2
	Total:	461.5	0001	9	200.2	3032.2

To Investigate Sundargarn



### Cost estimates of Grassland Development Including Grass Reserves for one unit (10 Ha.)

<u>Rupees in Lakh</u>
As per Guideline of Dept. of Animal Husbandry and Dairying & Fisheries, Gol (2016)

SL	Item	CPR, Gochar land / community land / waste land which need treatment of soil
1. (	Capital Investment	
A	Demarcation of boundary, fencing/ (trench / brushwood / barbed wire)	0.75
В	Land Development (10 hectares) @10 lakhs per ha. (including soil treatment and weeding)	1.00
С	Farm sheds – for equipment, seed, manure, and office	1.50
D	Purchase of agricultural implements	0.50
Е	Creation of irrigation facilities: wells, pumps, power line, water tank, pump room, pipelines etc.	3.75
	Sub- Total	7.50
2. F	Recurring Expenditure	
A	Wages of supervisory staff	0.20
В	Seeds, fertilizer/ manure, insecticides	0.40
С	Cultivation charges	1.00
D	Irrigation electricity / fuel charges	0.30
Е	Maintenance of Store/dead stock	0.30
F	Maintenance of Store/dead stock	0.30
	Sub-Total	2.50
17-	Grand Total	10.00
	Add for inflation of 3 years @10% per annum = 10.00x 3 x 10% =	3.00
	Total	13.00

To Investigate And Davis, 1911

Forest Range Officer Kuliposh

### Gully with 1.3 m width, 0.6 m bottom width and depth 0.6 m

#### (As per Manual of Land and Water Management)

SI. No	Details of work	Man days	Rate	Amount in Rs.
1	Survey, alignment, demarcation	1	298	298
2	Earth work excavation in stony earth mixed with gravel within initial lead and lift Edging out of gully 2x0.5x0.85x2.25x0.6 = 1.15 Foundation for stone packing1x2.3x1.8x0.3 = 1.24 D/S guard wall 1x1.3x0.5x0.6 = 0.39 Side wall 2x2.13x0.5x0.3 = 0.64 Total = 3.42	1.74	298	518.52
3	a. Dry stone packing in the foundation of structure	2.6 MD	298	774.8
4	U/S dumping (deflected by 45 deg.)  1x{(1.3+2.2)/2}x 0.45x0.3 = 0.24 Head wall and D/S dumping 1x1.3x0.9x0.3 = 0.35 Apron  1x1.3x0.9x0.3 = 0.35 Side walls  2x3.95x0.5x0.33=1.19 D/S guard wall  1x1.3x0.5x0.6 = 0.39 m³  b. Dry stone packing in super structure  U/S dumping 1x{(3.2+2.3)/2x0.45 (0.45+0)/2=0.27 D/S dumping 1x2.3x0.45x(0.45+0.2)/2 = 0.33 Head wall  1x2.3x0.45x0.45 = 0.47 Apron 1x0.9x1.3x0.15  =0.18 Side walls 2x3.95x0.5x0.3 =1.30  Total (a+b) = 5.07m³  Farth work in hard soil for side band of 10m length in	Material 5.07 m <sup>3</sup>	488.40	2476.19
4	Earth work in hard soil for side bund of 10m length in both side of structure 2x10x {(1.05+ 0.45) /2}x0.3 =4.5-3.42 = 1.08 i.e excavated earth in the foundation will be adjusted for the side bund	0.6 MD	298	178.8
<u>5</u>	Fine dressing and turfing locally available grass within initial lead and lift both side slopes $2x10x0.42 = 8.40$ Top $1x10x0.45 = 4.50$ For 2 no. bunds $2x12.90 = 25.80$ sq m	0.8 MD	298	238.4
6	Vetiver plantation with locally collected vetiver sleeves in D/S of the structure with Spacing (0.23x 0.23) sq m over 1.3 mt span and 1.0mt width of 3 rows including foliar spraying with Urea. No. of sleeves required = (2.3/0.23)x3 = 30 nos.	0.2 MD	298	59.6
	Sub Total			4544.31
7	Contingencies and unforeseen charges (5%)			227.22
	Total			4771.53

Note: Labor rate as per the letter no 11688/LC, Bhubaneswar, dated 07.11.2019 of Labour Commissioner, Odisha, Bhubaneswar and material & conveyance cost as per schedule of rates (Works Dept. GoO)

Executive Engineer Line Con

Obleens

Forest Range Officer Kuliposh

#### <u>Earthen Check dam with 10m Concrete Core wall</u> (As per Manual of Land and Water Management)

	Labor	cost	
Ordinary Labour	310 man-days	298/-	92,383.00/-
Skilled Labour (Mason etc.)	15 man-days	388/-	5820.00/-
Total			98203.00/-
	Materia	Il Cost	
Cement	230 bags	305.00/-	70,150/-
Sand	15 truck	1370.00/-	20,550/-
Brick	2500 Nos.	7.50/-	18,750/-
Aggregate (40 mm)	5 truck	6000	30,000/-
Bamboo	60 nos.	160/-	9,600/-
Total			1,49,050/-

Total Cost: 98203.00 + 1,49,050.00=Rs.2,47,253.00/-

Note: Labor rate as per the letter no 11688/LC, Bhubaneswar, dated 07.11.2019 of Labour Commissioner, Odisha, Bhubaneswar and material & conveyance cost as per schedule of rates (Works Dept. GoO)

Literature Et diffe et con

Forest Range Officer Kuliposh

Obleena

	11	7	6	Ω		***			521.20	
				7,555	4	ω	2		1	IS
Total	Administrative Expenditure/Monitoring & Supervision @ 10%	Total cost of Biological & Engineering measure	Drinking Water facilities and socio- economic development to Villagers	Awareness campaign for farm management, Control grazing etc.	Earthen Check Dam with Concrete Core	Loose Boulder Wall gully plugging	Fodder land Development per 10ha	Afforestation including maintenance (Block Plantation @ 1600 plants/ha (6 months seedlings)	Enrichment of Plantation/Redensification (Aided Natural Regeneration) 600/ha	Item
47.80	4.35	43.45	0.00	0.00	0.00	0.00	13.00	25.78	4.67	0
77.51	7.05	70.46	0.00	0.00	0.00	0.00	13.00	38.98	18.48	ъ
110.06	10.01	100.05	5.00	2.50	49.45	1.91	13.00	21.58	6.61	2
40.92	3.72	37.20	5.00	2.50	0.00	0.00	13.00	14.51	2.19	3
5.17	0.47	4.70	0.00	0.00	0.00	0.00		4.23	0.47	4
5.16	0.47	4.69	0.00	0.00	0.00	0.00		4.22	0.47	5
5.16	0.47	4.69	0.00	0.00	0.00	0.00		4.22	0.47	6
5.16	0.47	4.69	0.00	0.00	0.00	0.00		4.22	0.47	7
5.16	0.47	4.69	0.00	0.00	0.00	0.00		4.22	0.47	8
5.16	0.47	4.69	0.00	<b>0</b> .00	0.00	0.00		4.22	0.47	9 .
5.16	0.47	4.69	0.00	0.00	0.00	0.00		4.22	0.47	10
312.40	28.40	284.00	10.00	5.00	49.45	1.91	52.00	130.40	35.24	Total



Forest Range Officer
Kuilposh